3 Decks

# ~~IRON OR~~ STEEL STEAMER.

TUES. 14 AUG 1900

Received at London Office

State if Report is also sent on the Machinery of the Vessel Yes.

Date of completion of report 9th August 1900 Port of Greenock No. 12765

Survey held at Port Glasgow & Greenock. Date, First Survey 13th June 1899 Last Survey 6th August 1900

On the Steel Screw Steamer "JUPITER" Schooner Rig 2 Masts.

THREE DECKED VESSEL.

CLASS ✠100 A1

| | |
|---|---|
| **TONNAGE under Tonnage Deck** | 4515·80 |
| *Between Tonnage Dk. and 3rd and 4th Dk.* | |
| **Total under Upper Dk.** | |
| *No. of Poop* | 99·03 |
| *Do. of Bridge House* | |
| *Do. of Forecastle* | 66·50 |
| *Do. of Houses on Dk.* | 78·31 |
| *Do. of excess of Hatchways* | 33·34 |
| *Do. above Crown of Engine Room* | 103·02 |
| **Gross Tonnage** | 4896·00 |
| *Less Crew Space* | 79·48 |
| *Less above Crown of Engine Room* | 32·99 |
| **Tonnage for Fees** | 4783·53 |
| *Less Engine Room* | 1566·72 |
| *Less Navigation Spaces* | 32·99 |
| **Register Tonnage** (as above Beams) | 3216·81 |

| | Feet. |
|---|---|
| **Half Breadth** (moulded) | 25·89 |
| **Depth** *from upper part of Keel to top of Upper Deck Beams (with the normal round up of beam)* | 30·96 |
| **Girth** *of Half Midship Frame (as per Rule)* | 53·08 |
| | 109·93 |
| *Deduct 7 feet* | 7·00 |
| **1st Number** | 102·93 |
| **Length** *on deck from after part of stem to fore part of stern post* | 388. |
| **2nd Number** | 39937. |
| **Proportions**—*Breadth to Length* | 7·49. |
| *Depth to Length—Upper Deck to top of Keel* | 12·53. |
| *Main Deck ditto* | |

Master Abilio de Abarte.

Year of appointment (1) As Master in service of owner of present vessel—18 (2) As Master of this vessel 18

Built at Port Glasgow.

When built 1900 Launched 25th June 00

By whom built Russell & Co.

Owners Francisco Martinez Rodas.

Managers " " "

(Where necessary to be entered in Reg. Book.)

Residence Bilbao

Port belonging to Bilbao

Destined Voyage Cardiff to load. If Surveyed while Building, Afloat, or in Dry Dock Gurnl Dock.

**LENGTH** on Deck as per Rule ... Feet. 388 Inches. 0 | **BREADTH** Moulded .... Feet. 51 Inches. 9½ | **DEPTH, ACTUAL**—Top of Floors to top of Upper Dk. Beams Feet. 27/8 Inches. 15/16 7½ | No. of Decks with flat laid Two | No. of Tiers of Beams Two.

*Dimensions of Ship per Register,* Length 389·2 breadth 52·1 depth 27·1. Moulded depth, ft. 29 ins. 11 To Upper Dk. Round of Upper Dk. Beam, Actual 12½ ins.

## FRAMING.

| | Inches in Ship | Inches in Ship | 20ths in Ship | Inches per Rule Or as | Inches per Rule Approved | 20ths per Rule |
|---|---|---|---|---|---|---|
| **FRAME,** Angles, ~~or T, E or L Bars~~ for ⅓ length amidships | 6 | 3½ | 10 | 6 | 3½ | 10 |
| Do. for ⅓ at each end | 6 | 3½ | 9 | 6 | 3½ | 9. |
| Do. in way of Double Bottoms at Solid Floors | 3½ | 3½ | 10 | 3½ | 3½ | 10 |
| ,, ,, ~~at intermdt. Plts.~~ | | | | | | |
| Distance of Frames from moulding edge to moulding edge, all fore and aft | 25 | | | 25. | | |
| **REVERSED FRAME.** Angles | 6½ | 3½ | 10·9 | 6½ | 3½ | 10·9 |
| **DEEP FRAMING,** depth of girder | 9½ | | | 9½ | | |
| **~~FLOORS,~~** depth and ~~thickness of Plate~~ ~~at mid line for ⅓ length amidship~~ | all parts of double bottom in Boiler space increased 1/20 in thickness. | | | | | |
| ~~in way of Engines and Boilers~~ | | | | | | |
| ~~thickness at the end of vessel~~ | | | | | | |
| ~~depth as ⅓ the half breadth as per Rule~~ | | | | | | |
| ~~height extended at the Bilges~~ | | | | | | |
| **FLOORS ~~& BRACKETS~~** in **Cell Dble Bottoms** | | | 9·8 | | | 9·8 |
| ,, Distance apart | 25 | | | 25. | | |
| **CENTRE GIRDER,** in Double bottom, depth and thickness | 46 | | 12 | 46 | | 12 |
| ,, ,, Angles, Top | 4 | 4 | 10 | 4 | 4 | 10 |
| ,, ,, Bottom | 4½ | 4½ | 12 | 4½ | 4½ | 12 |
| **SIDE GIRDERS,** number on each side & thickness | 2 10 | | 8 | 2 10 | | 8. |
| ,, Angles | 3½ | 3½ | 9 | 3½ | 3½ | 9. |
| **MARGIN PLATE,** depth (exclusive of flange) and thickness | 32 | | 10 | 32 | | 10 |
| ,, Angles to Outside Plating | 4 | 4 | 10 | 4 | 4 | 10. |
| **INNER BOTTOM PLATING,** breadth and thickness of **Middle Line Strake** | 54 | | 11·10 | 54 | | 11·10. |
| ,, ,, in Engine and Boiler space | | | 11 10 | | | 11·10 |
| ,, ,, Remainder in Holds | | | 8 | | | 8. |
| **BEAMS, Upper Deck,** ~~Single Angle~~, Bulb ~~Angle~~, Plate ~~or T or Bulb~~ | 10½ | | 10 | 10½ | | 10 |
| ,, Angles on upper edge | 3½ | 3½ | 8 | 3½ | 3½ | 8. |
| ,, Average space | 50 | | | 50. | | |
| **BEAMS, Middle Deck,** ~~Single Angle~~, Bulb ~~Angle~~, Plate ~~or T or Bulb~~ | 12 | | 11 | 12 | | 11 |
| ,, Angles on upper edge | 3½ | 3½ | 9 | 3½ | 3½ | 9. |
| ,, Average space | 50 | | | 50. | | |
| **~~BEAMS, Lower Deck,~~** ~~Single Angle, Bulb Angle, Plate or T or Bulb~~ | | | | | | |
| ,, ~~Angles on upper edge~~ | | | | | | |
| ,, ~~Average space~~ | | | | | | |
| **~~BEAMS, Hold, or Orlop,~~** ~~Plate or T or Bulb~~ | | | | | | |
| ,, ~~Angles on upper edge~~ | | | | | | |
| ,, ~~Average space~~ | | | | | | |
| **BEAMS, Poop Deck,** ~~Angle~~, Bulb Angle, ~~Plate or T or Bulb~~ | 8½ | 3 | 12 | 8½ | 3 | 12 |
| ,, ~~Angles on upper edge~~ | | | | | | |
| ,, Average space | 50 | | | 50. | | |
| **BEAMS, Bridge Deck,** Angle, Bulb Angle, Plate or Tee Bulb | 9 | 3½ | 12 | 9 | 3½ | 12 |
| ,, ~~Angles on upper edge~~ | | | | | | |
| ,, Average space | 50 | | | 50. | | |
| **BEAMS, Forecastle Deck,** ~~Angle~~, Bulb Angle, ~~Plate or T or Bulb~~ | 9 | 3½ | 13 | 9 | 3½ | 13 |
| ,, ~~Angles on upper edge~~ | | | | | | |
| ,, Average space | 50 | | | 50. | | |
| **PILLARS, In 'tween Deck,** size and spacing | 2⅞ | | 50 | 2⅞ | | 50 |
| ,, **Hold** ,, ,, | 4⅛ | | 50 | 4⅛ | | 50 |
| ,, **Quarter 'tween Dks.** ,, ,, | 2⅞ | | 100 | 2⅞ | | 100 |
| ,, **in Hold** ,, ,, | 4⅛ | | 100 | 4⅛ | | 100 |
| **~~WEB-FRAMES, In Fore Body,~~** ~~No. and spacing~~ | | | | | | |
| ,, ,, ~~brdth. & thickness~~ | | | | | | |
| ,, ,, ~~No. of Side Stringers~~ ,, ,, | | | | | | |
| **WEB-FRAMES, In E. & B. Space,** No. & spacing | 2 10 | | | 2 10 | | |
| ,, ,, brdth. & thickness | 24 | | 10 | 24 | | 10 |
| **~~WEB-FRAMES, In After Body,~~** ~~No. and spacing~~ | | | | | | |
| ,, ,, ~~brdth. & thickness~~ | | | | | | |
| ,, ,, ~~No. of Side Stringers~~ ,, ,, | | | | | | |
| ~~Single Angles or Tee Bars to~~ **~~Web Frames~~** | | | | | | |
| **~~BRACKET PLATES to Stringers between Web Frames,~~** depth and thickness | | | | | | |

## FORGINGS or CASTINGS.

| | Inches in Ship. | Inches per Rule. Or as Approved. |
|---|---|---|
| **~~KEEL, Bar or Side Plates,~~** depth and thickness | | |
| **STEM,** moulding and thickness | 11 × 3⅛ | 11 × 3⅛ |
| **STERN-POST** for Rudder do. do. | 11 × 7½ | 11 × 7½ |
| ,, for Propeller | 11 × 7½ | 11 × 7½ |
| **MAIN PIECE** of **Rudder,** diameter at head | 10 | 10 |
| ,, ,, do. at heel | 7½ | 7½ |

**RUDDER,** how constructed Forged Single Plate.

Can the Rudder be unshipped afloat? Yes.

## KEELSONS & STRINGERS.

| | Inches in Ship | Inches in Ship. | 20ths of Inches in Ship. | Inches per Rule Or as | Inches per Rule As Approved | 20ths of Inches per Rule Approved. |
|---|---|---|---|---|---|---|
| **~~CENTRE LINE KEELSON,~~** Vertical Plate above ~~Bosses, Through Plate, or Intercostal Plate~~ | | | | | | |
| ,, ~~Rider Plate~~ | | | | | | |
| ,, ~~Bulb Plate to Intercostal Keelson~~ | | | | | | |
| ,, ~~Horizontal Plates on Floors~~ | | | | | | |
| ,, ~~Angles~~ | | | | | | |
| **~~SIDE KEELSON,~~** ~~Angles~~ | | | | | | |
| ,, ~~Bulb or Plate above floors, for lng.~~ | | | | | | |
| ,, ~~Intercostal Plate, for length~~ | | | | | | |
| ,, ~~Attached to outside Plating with Angle~~ | | | | | | |
| **BILGE KEELSON,** Angles 3 No. | 6½ | 4½ | 13 | 6½ | 4½ | 13. |
| ,, ~~Bulb or Plate above floors, for lng.~~ Girder 24 deep. | | | | | | |
| ,, Intercostal Plate for whole length | 20 | | 11 | 20 | | 11. |
| ,, Attached to outside Plating with Angle | 7 | 3½ | 10 | 7 | 3½ | 10. |
| **BILGE STRINGER** Angles 3 No. | 6½ | 4½ | 13 | 6½ | 4½ | 13. |
| ,, ~~Bulb Plate for length~~ Girder 24 deep | | | | | | |
| ,, Intercostal Plate for whole length | 20 | | 11 | 20 | | 11 |
| ,, Attached to outside Plating with Angle | 7 | 3½ | 10 | 7 | 3½ | 10 |
| **SIDE STRINGER** Angles 3 No. | 6½ | 4½ | 13 | 6½ | 4½ | 13. |
| ,, ~~Bulb~~ or Intercostal Plate, for whole lng. | 20 | | 11 | 20 | | 11 |
| ,, Attached to outside plating with Angle | 7 | 3½ | 10 | 7 | 3½ | 10 |

| | | | | | | |
|---|---|---|---|---|---|---|
| **Upper Deck Stringer Plates,** br'dth & thickness | 61 | | 12 | 61 | | 12 |
| ,, Angle on ditto | 5 × 5 × | | 11 | 5 × 5 × | | 11. |
| ,, ~~Tie Plates fore and aft, outside Hatchways~~ | | | | | | |
| ,, Deck.* ~~Iron or~~ Steel, for whole lng. | | 867 | | | | 867. |
| ,, ~~Wood Deck, Material & thickness~~ | | | | | | |
| **Middle Deck Stringer Plate,** br'dth & thickness | 61 | | 10 | 61 | | 10 |
| ,, Angles on ditto, No. 2 | 4 × 4 × | | 9 | 4 × 4 × | | 9. |
| ,, ~~Tie Plates outside Hatchways~~ | | | | | | |
| ,, ~~Diagonal Tie Plates on Bms., No. of prs.~~ | | | | | | |
| ,, Deck.* ~~Iron or~~ Steel, for whole lng. | | 867 | | | | 867. |
| ,, ~~Wood Deck, Material & thickness~~ | | | | | | |
| **~~Lower Deck Stringer Plate,~~** br'dth & thickness | | | | | | |
| ,, ~~Angles on ditto, No.~~ | | | | | | |
| ,, ~~Tie Plates outside Hatchways~~ | | | | | | |
| ,, ~~Deck.* Material and thickness~~ | | | | | | |
| **~~Hold or Orlop Stringer Plate,~~** br'dth & thickness | | | | | | |
| ,, ~~Angles on ditto, No.~~ | | | | | | |
| ,, ~~Tie Plates outside Hatchways~~ | | | | | | |
| ,, ~~Deck.* Material and thickness~~ | | | | | | |
| **Poop Deck Stringer Plate,** breadth & thickness | 30 | | 7 | 30 | | 7. |
| ,, Angle on ditto | 3 × 3 × | | 7 | 3 × 3 × | | 7 |
| ,, ~~Tie Plate~~ | | | | | | |
| ,, Deck. Material and thickness Steel | | | 7. | | | 7. |
| **Bridge Deck Stringer Plate,** br'dth & thickness | 40 | | 9 | 40 | | 9. |
| ,, Angle on ditto | 3½ × 3 × | | 9 | 3½ × 3 × | | 9. |
| ,, Tie Plates under House | 3" | | 12 | 3" | | 12 |
| ,, Deck. Material and thickness do. Steel | | | 7 | | | 7 |
| **Forecastle Deck Stringer Plate,** br'dth & th'kns | 30 | | 7 | 30 | | 7 |
| ,, Angle on ditto | 3 × 3 × | | 7 | 3 × 3 × | | 7 |
| ,, Tie Plates | 12 | | 7 | 12 | | 7 |
| ,, Deck. Material and thickness S. Steel | 3" | | 7 | 3". | | 7 |

* If Iron or Steel Deck, state if whole or in part, and if Wood Deck is laid thereon.

## BULKHEADS. STIFFENERS.

| | Number. | Thickness. | Horizontal Size. | Horizontal Spacing. | Vertical Size. | Vertical Spacing. | Single or Double Frames. | Height up. |
|---|---|---|---|---|---|---|---|---|
| **W. T. BULKHEADS** | 7 | 6 8 | 6 7 | 9 × 3 × 12/20 ths | 48 | 6 × 3 × 12/20 ths | 30 | Double | 6 to Upper Dk 16 to Middle Dk |
| **PARTITION** ,, | | | | | | | | |
| **LONGITUDINAL** ,, | webplates & Semi-box beams. | | | | | | | |

Are the outside Plates doubled two spaces of Frames in length? Yes Rule 1/4 L

Are the Sluice Valves and Watertight Doors in efficient working order? Yes.

Form No. 1B.

12765

## PLATING.

| STRAKES. | AS IN SHIP. Amidship. Breadth. | Amidship. Thickness. | Forward. Thickness. | Aft. Thickness. | PER RULE OR AS APPROVED. Amidship. Breadth. | Amidship. Thickness. |
|---|---|---|---|---|---|---|
| | Inches. | Inches or 20ths | Inches or 20ths | Inches or 20ths | Inches. | Inches or 20ths |
| Flat Plate Keel (If Bar Keel, state Rivetting) | 36 | 20 | 14 | 14 | 36 | 20 |
| Garboard or A Strake | 54 | 16 | 13 | 13 | 54 | 16 |
| B " | 54 | 11 | 9 | 9 | 54 | 11 |
| C " | 50 | 12 | 10 | 10 | 50 | 12 |
| D " | 54 | 11 | 9 | 9 | 54 | 11 |
| E " | 46 | 13 | 11 | 11 | 46 | 13 |
| F " | 54 | 13 | 10 | 10 | 54 | 13 |
| G " | 46 | 14 | 11 | 11 | 46 | 14 |
| H " | 54 | 12 | 9 | 9 | 54 | 12 |
| J " | 46 | 13 | 10 | 10 | 46 | 13 |
| K " | 54 | 12 | 9 | 9 | 54 | 12 |
| L " | 46 | 13 | 10 | 10 | 46 | 13 |
| M " | 54 | 12 | 9 | 9 | 54 | 12 |
| N " | 46 | 10 | 10 | 10 | 46 | 16 |
| ~~Sheerstrake~~ O " | 48 | 17 | 11 | 11 | 48 | 17 |
| P " | | | | | | |
| Q " | The boss plates & the plates above & below the same | | | | | |
| R " | are 7/20 thick Aft, than the plating at amidships). | | | | | |

State actual thickness in way of Double Bottom. Calls 20/13

Write 'Short Strake' opposite its corresponding letter.

Doubling of ~~Flat Plate Keel~~

Length and thickness { ~~of Bilges~~ ..... at ends of Bilge 13 and 17 ft long

{ of Sheerstrakes.

{ ~~of Strake below~~

| | | | | | | | | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Poop Sides | | | | 7 | | 7 | Sgle | 2½ | ¾ | 3 | Dble | ¾ | 2⅝ | | | 5 | |
| Bridge Sides | | | 10 ⅝ 9 | | | 10 ⅝ 9 | Dble & Sgle | 4½ - 2½ | ¾ | 3 | " | ¾ | " | | | " | |
| Forecastle Sides | | 7 | | | | 7 | Sgle | 2½ | ¾ | 3 | " | ¾ | " | | | " | |

## RIVETING.

### EDGES.

| | Single or Double. | Breadth of Lap. | Rivets. Diam. | Rivets. Spacing cr. to cr. | Butts. Double or Treble and for what Length. | Rivets. Diam. | Rivets. Spacing cr. to cr. | Straps. Breadth. | Straps. Thickness. 16ths or 20ths | If Lapped. Breadth. | If Lapped. For what Length. Feet. |
|---|---|---|---|---|---|---|---|---|---|---|---|
| | | Inches. | Inches. | Inches. | | Inches. | Inches. | | | | |
| Flat Plate Keel | Dble | 6 | 1 | 4 | Dble 3/5 l | 1 | 3½ | | | 14 | Whole |
| Garboard or A Strake | " | 6 5/4 | 1 7/8 | 4 3½ | Dble whole | 1 7/8 | 3½ | | | 10 69 | " |
| B " | " | 5 5/4 | 7/8 | 3½ | " " | " | " | | | 9 | " |
| C " | " | " | " | " | " " | " | " | | | " | " |
| D " | " | " | " | " | " " | " | " | | | " | " |
| E " | " | " | " | " | " " | " | " | | | " | " |
| F " | 5/4 | 6 7/8 | 1 | 3½ 4 | " " | " | " | | | " | " |
| G " | 6 5/4 | 1 7/8 | 4 | 3½ | " " | 1 | 3½ | | | 10½ | " |
| H " | 5/4 | 7/8 | 3½ | | " " | 7/8 | 3⅜ | | | 9 | " |
| J " | " | " | " | | " " | " | " | | | " | " |
| K " | " | " | " | | " " | " | " | | | " | " |
| L " | " | " | " | | " " | " | " | | | " | " |
| M " | " | " | " | | " " | " | " | | | " | " |
| N " | 5/4 | 6 7/8 | 1 | 3½ 4 | Dble 3/4 l | " | " | | | 10 69 | " |
| ~~Sheerstrake~~ O " | 6 3 | 1 7/8 | 4 | 3½ do | do | 1 | 3½ | | | 14 69 | " |
| P " | | | | | | | | | | | |
| Q " | | | | | | | | | | | |
| R " | | | | | | | | | | | |

### BUTTS.

| | Rivets. Diam. | Rivets. Spacing cr. to cr. | Straps. Breadth. | Straps. Thickness. 16ths or 20ths | If Lapped. Breadth. | If Lapped. For what Length. Feet. |
|---|---|---|---|---|---|---|
| | Inches. | Inches. | | | Inches. | |
| Flat Plate Keel | 1 | 3½ | | | 14 | Whole |
| Garboard or A Strake | 1 7/8 | 3½ | | | 10 69 | " |
| B " | " | " | | | 9 | " |
| C " | " | " | | | " | " |
| D " | " | " | | | " | " |
| E " | " | " | | | " | " |
| F " | " | " | | | " | " |
| G " | 1 | 3½ | | | 10½ | " |
| H " | 7/8 | 3⅜ | | | 9 | " |
| J " | " | " | | | " | " |
| K " | " | " | | | " | " |
| L " | " | " | | | " | " |
| M " | " | " | | | " | " |
| N " | " | " | | | 10 69 | " |
| ~~Sheerstrake~~ O " | 1 | 3½ | | | 14 69 | " |
| P " | | | | | | |
| Q " | | | | | | |
| R " | | | | | | |

Manufacturer's name or trade mark of the Iron or Steel (state process of manufacture of Steel) used for Frames, Floors, Beams, Keelsons, Tie and Stringer Plates, Plating, &c.: Siemens Martin Steel from Glasgow, Dalzell, Hallside Parkhead · Lanarkshire & Glengarnock Iron from Newport · N. Wales & South Durham.

Has the Steel been tested as required by the Rules? Yes.

**Upper Deck** \ **Butts,** ~~treble~~ double riveted for ½ length amidship.
**Stringer Plate** / **Straps,** ~~single, double or~~ overlapped for whole length ~~amidship~~.
**Middle Deck** \ **Butts,** treble riveted for whole length amidship.
**Stringer Plate** / ~~Straps, single, double or~~ overlapped for length ~~amidship~~.
**Butts of Bilge & Side Stringers and Tie Plates,** treble ~~or~~ and double riveted?
**Inner Bottom Plating,** riveting of **Edges** Dble & Sgle **Butts** Double
**Centre Girder Butts,** treble riveted **Keelson Butts,** treble riveted.
**Frames,** riveted through Plates with 7/8 in. Rivets, about 6/8 apart.
**Rivets,** state whether Iron or Steel Iron.

**FRAMES** extend in one length from Outside line of Stank side, and Stank side to Sunnside

**REVERSED FRAMES** on floors and frames extend from Stank side to Stank side, all to Upper ~~or~~ & for ½ length, at ends to Upper & Main Decks alternately, double alternate frames at large tweendecks, all to Upper Deck in after Peak, alternately to Fourth Dk, and equal to Double in Engine & Boiler Space.

## MASTS, SPARS, &c.

| | Material. | Total Length. | Diameter and Thickness: At Partners. | Heel. | Hounds ~~or~~ & Head. | No. of Plates in round. | Angles: Number. | Angles: Size. | Riveting: Seams. | Riveting: Butts. |
|---|---|---|---|---|---|---|---|---|---|---|
| | | Feet. | Inches. | Inches. | Inches. | | | | | |
| Lower Masts: Fore | Steel | 57. 7½ | 21 × 7/20 | 18 × 7/20 | 16½ × 4/20 | Two | ✓ | ✓ | Single | Treble & Double |
| Main | | 58-6 | " " | " " | " " | | ✓ | ✓ | " | " " |
| ~~Mizen~~ | | | | | | | | | | |
| ~~Bowsprit~~ | | | | | | | | | | |

Topmasts, ~~Yards and~~ Remainder of **Spars** Wood

**Rigging,** Material and Size, **Shrouds** 3½" G.S.W. **Stays** 4¼" G.S.W.

**Sails,** One Complete Suit of Schooner Sails, and the following spare sails —

## EQUIPMENT No. 45777. LETTER J. ANCHORS. ✠ Mechanical Tests by John C. Craig 7/8 on 1/4 on 3/4 on

| Number of Certificate. | Anchors. | Weight, Ex. Stock: Cwts. | qrs. | lbs. | Weight of Stock: Cwts. | qrs. | lbs. | Test, per Certificate: Tons. | cwts. | qrs. | lbs. | Weight Required by Table 22: Cwts. | qrs. | lbs. | Description of Anchor. | Makers. | Where and when tested and Superintendent. |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| 38541 | 1st Bower ✠ | ✠ 58 | 3 | 0 | | | | 47 | 12 | 2 | 0 | 58 | 2 | 0 | Stockless | Byers Reliance Sd Co | 23rd April 1900 |
| 38536 | 2nd " | ✠ 58 | 2 | 0 | | | | 47 | 10 | 0 | 0 | 58 | 2 | 0 | " | " | " |
| 38667 | 3rd " | ✠ 50 | 0 | 21 | | | | 42 | 10 | 2 | 14 | 49 | 3 | 0 | " | " | 10th May " |
| | 4th " | | | | | | | | | | | | | | | Tested by H. J. Milford. | |
| | Collective weight | 167 | 1 | 21 | | | | | | | | 166 | 3 | 0 | | | |
| 20560 | Stream | 14 | 0 | 25 | 3 | 1 | 17 | 15 | 16 | 3 | 14 | 14 | 0 | 0 | Ordinary | Parkes & Co. Ltd. Tipton | 20th Sept 1899 |
| 42589 | Kedge | 6 | 3 | 24 | 1 | 3 | 2 | 9 | 5 | 0 | 0 | 7 | 0 | 0 | " | " " | Nethertown 2nd Aug 1899 H.M. Key |

If Proof Rolls verse of Plates.

If Stockless state Mechanical Tests.

## CHAIN CABLES.

| Number of Certificate. | Fathoms. | Size. | Test per Certificate Tons. | Weight of Chain Cable: Supplied. | Per Table 22. | Fathoms and Size per Table 22. | Description. | Makers of Cables. | When and where tested, and Superintendent. |
|---|---|---|---|---|---|---|---|---|---|
| 19401 | 135 | 2 7/16 | 120 17 | 54 2 18 | 48 3 0 | 270 2 7/16 | Stud link | H. P. Parkes & Co. Ltd. Tipton | 27th Jan/00 |
| 19402 | 135 | 2 7/16 | 120 17 / 38 15 | 325 0 15 / 379 3 5 | | | " " | " " | " " |
| ~~Iron Stream Chain~~ or Steel Wire | 90 | 4¼ | 47 | | | 90 4¾ | | Tested by C. E. Perrin. Steel Wire by Webster & Co. Ltd. Adelphi | |

## HAWSERS AND WARPS.

| Material | Fathoms. | Size. | Breaking Test of Steel Wire Towline. | Fathoms and Size per Table 22. |
|---|---|---|---|---|
| Towline | 108 | 4¾ | 47 | 120. 4¾ S.W. |
| Hawser | 180 | 2¾ | 15½ | 180. 8" |
| Warp | 180 | 2⅜ | 11. | 180. 7 |

Specimens produced. and others.

**Boats** 4. Boats.

**Pumps,** Number as per approved plans Downton to Bulk Heads Diameter of Barrel Hand Pumps to Fore Peak State whether they are in efficient working order Yes.

**Windlass** is Emerson Walker & Thompson (Steam) **Capstan** —

**Engine Room Skylights.**—How constructed? Steel

What arrangements for deadlights in bad weather? Teak flaps and bulls eyes

**Coal Bunker Openings.**—How constructed? Bulb. angle. How are lids secured? Watch bars. Height above deck? 9"

Number of **Scuppers,** and numbers and dimensions of **Freeing Ports, &c.** 6 Scuppers on each side, and 6 M.P. one each side

**Ceiling in Holds,** thickness and material 2½ **Ceiling 'tween Decks,** thickness and material? No. 27 × 24 · 26 × 22 · 25 × 21 (Main Deck) No. 27 × 24 · 26 × 22 · 25 × 21 (Upper Deck)

**Cargo Hatchways.**—How formed? Plates & angles in the usual manner. **Hatches,** If strong and efficient? Yes.

State size **No. 1 Hatch** (Forward) 25.0 × 16 × 6" **No. 2 Hatch** 27.0 × 16.0 **No. 3 Hatch** 29.0 × 16.0 **No. 4 Hatch** 25.0 × 16.0"

Number of **Web Plates, Shifting Beams** and **Fore** and **Afters** to each Hatch No. 1. 2 Mds. 3. Frames. No. 2. 2 Mds. 3. Frames. No. 3. 2 Mds. 3. Frames. No. 4. 2 Mds. 3. Frames. **No. of Breasthooks** 7 **No. of Crutches** 2 ✓ deep floors.

**Bulwarks,** height above deck and description Plates 48 × 9/20. Main Rail, material and size 6 × 3 × 9/20 B.A.

The above is a correct description.

Builder's Signature (here only) Russell & Co. per OMA

Surveyor's Signature Thos Phillips Wm Johnstone

Surveyor to Lloyd's Register of British and Foreign Shipping.

Form No. 13.

**Correspondence.**—State dates and initials of letters respecting this case (*Reference should be made to any correspondence connected with this case*) 10/3/99 M.

24/3/99 M. 29/3/99 M. 23/10/99 E 27/10/99 E.

**Workmanship.** Are the butts of plating planed or otherwise fitted? Planed.

Is the riveted work properly closed? Yes.

Are the liners between the frames and plates solid single pieces? Yes. Do the holes for riveting plate to frames, butt straps, or plate to plate, &c., conform well to each other? Yes. Are the rivet holes well and sufficiently countersunk in the plate and punched from the faying surfaces? Yes. Do any rivets break into or through the seams or butts of plating? Yes, aft end.

Are the butts of Plating, Stringers, &c., properly shifted and strapped? Yes

Have all the upper and weather decks been tested as required by the Rules (Sec. 23, par. 24)? Yes. State results of tests Satisfactory

Have all the gutterways been tested as required by the Rules (Sec. 23, par. 25)? Yes. State results of tests Satisfactory

**General Remarks** (State quality of workmanship, &c.) This vessel has been built in accordance with the Rules and the approved tracings of the Midship & Longitudinal Sections.

The workmanship is of good quality.

The frames & reversed frames in the double bottom, and the frames outside the cellular bottom between the half length & three fourths length (moved) amidships in the straight part of the vessel have been pigglad to dispense with frame liners to the outside shakes of plating.

There is a camber of 1/10" on the beat of this vessel.

When launching this vessel stuck on the ways. The ways were taken out & refitted and Vessel afterwards successfully launched.

After launching she was placed in Dry Dock for examination of bottom &c. The bottom is as found to have sustained no damage, and the keel had not altered form, for particulars see Damage Survey R/P attached.

*The Surveyor should state the Number of Report and Name of any Sister Vessel.*

**PARTICULARS FOR RECORD in the REGISTER BOOK.**—Length of Poop 31-3 ft., R.Q.D. or Break ✓ ft., Bridge Dk 112-6 ft., F'castle 40-6 ft. (in feet and tenths). When the Poop is joined to the B.D., this should be distinctly stated ✓

No. and Material of Decks (if Iron or Steel) and whether wholly or partially covered with wood, and No. of tiers of Beams (this information is to be given as it should appear in the Register Book) 2 Dks (Steel) & Deep Framing

Official No. ✓ ; Signal Letters ✓

How are the surfaces preserved from oxidation? Inside by Portland Cement & paint Outside by paint

**PARTICULARS OF WATER BALLAST.**—State whether the Double bottom is constructed on the cellular system ~~or with girders on floors~~ Yes.

| Where fitted. | *Length. Feet. | Water Capacity. Tons | Where fitted. | *Length. Feet. | Water Capacity. Tons. |
|---|---|---|---|---|---|
| Double bottom, aft, | 131-3 | 440 | Fore peak tank, | — | — |
| Double bottom, under Engines and Boilers, | 41-8 | 179 | After peak tank, | 12-0 | 5-6 |
| Double bottom, if under Engines only, | — | — | Midship deep tank, | 31-3 | 800 |
| Double bottom, if under Boilers only, | — | — | Other tanks, if fitted, | — | — |
| Double bottom, forward, | 166-10 | 625 | (If necessary, furnish further information by sketch.) | | |

* The wells are not to be included in the lengths of the tanks.

State whether the above have been tested as required by the Rules Yes.

Order for Special Survey No. 2013

Date 11th April 1899

No. 455 in builder's yard

Dates of Surveys held while building

1899 June 13. 21. 27. July 2. 27. Aug 4. 14. 21. 25. 30. Sept 5. 8. 18. 21. 25. Oct 4. 9. 16. 19. 24. 27. 31. Nov 3. 10. 15. 21. 24. Dec 1. 6. 12. 18. 21. 22. 28. 1900 Jan 12. 17. 18. 23. 30. Feb 5. 12. 15. 21. 27. March 5. 12. 21. 26. 30. April 6. 10. 16. 18. 23. 26. 30. May 2. 3. 8. 10. 11. 16. 17. 20. 23. 24. 28. 30. June 4. 7. 8. 11. 13. 14. 15. 18. 19. 20. 21. 22. 26. 29. July 17. 24. 27. Aug 1. 2. 6.

Total No. of Visits 88.

The amount of Entry Fee £ 5 : 0 : 0

Special Survey Fee £ 444 : 12 : 0

~~Travelling Expenses of Party~~ £ — : — : —

Fees applied for, 8-8-1900

Received by me, 9-8-1900

Certificate to be sent to Greenock.

State whether the Vessel has been built under Special Survey Yes

I am of opinion this Vessel should be Classed ✠ 100 A 1, Steel "3 Deck" ~~or without~~ Freeboard, as condition of Class

Thos Phillips Wm Johnstone.

Surveyor to Lloyd's Register of British and Foreign Shipping.

*Committee's Minute* Glasgow. 13 AUG 1900

*Character assigned* ✠ 100 A.1. "Steel" A + C. P. Award

*The Surveyors are requested not to write on or below the Committee's Minute.*

© 2021 Lloyd's Register Foundation