

REPORT ON ELECTRIC FITTINGS.

(OTHER THAN FOR THE PROPULSION OF THE VESSEL)

Received at London Office **14 DEC 1927**Date of writing Report **6.12.1927** When handed in at Local Office **12.12.1927** Port of **GLASGOW.**No. in Survey held at **PORT GLASGOW.** Date, First Survey **23.11.27** Last Survey **30.11.27** 19
Reg. Book. **S.S. MIMIE.** (Number of Visits... **3**)on the **S.S. MIMIE.** Tons { Gross
NetBuilt at **PORT GLASGOW.** By whom built **MESSRS FERGUSON BROS** Yard No. **286** When built **1927.**Owners **THE LONDON MIDLAND & SCOTTISH RLY.** Port belonging to **LONDON.**Electric Light Installation fitted by **MESSRS J. CHARTERS & CO** Contract No. **286** When fitted **1927.**System of Distribution **Double wire looping in system without jointing** ✓Pressure of supply for Lighting **110** ✓ volts, Heating ✓ volts, Power ✓ volts.Direct or Alternating Current, Lighting **D.C.** ✓ Power ✓

If alternating current system, state frequency of periods per second ✓

Has the Automatic Governor been tested and found efficient when the whole load is suddenly thrown on or off **Yes** ✓Generators, do they comply with the requirements regarding rating **Yes** ✓, are they compound wound **Yes** ✓are they over compounded 5 per cent. **Yes** ✓, if not compound wound state distance between each generator ✓

Where more than one generator is fitted are they arranged to run in parallel ✓, is an adjustable regulating resistance fitted in


series with each shunt field **Yes**Are all terminals accessible, clearly marked, and furnished with sockets **Yes**, are they so spaced or shielded that they cannot be accidentally earthed,short circuited, or touched **Yes** Are the lubricating arrangements of the generators as per Rule **Yes**Position of Generators **Engine Room Starboard side**is the ventilation in way of the generators satisfactory **Yes**, are they clear of all inflammable material **Yes**

if situated near unprotected woodwork or other combustible material, state distance of same horizontally from or vertically above the generators

> 12" and **> 48"**, are the generators protected from mechanical injury and damage from water, steam or oil **Yes**are their axes of rotation fore and aft **Yes**Earthing, are the bedplates and frames of the generating plant efficiently earthed **Yes** are the prime movers andtheir respective generators in metallic contact **Yes**Main Switch Boards, where placed **Engine Room Starboard side**

If the generators and main switchboard are not placed in the same compartment, is each generator provided with

a fuse on each insulated pole as near as possible to the terminals of the generator, additional to that provided on the main switchboard ✓

Switchboards, are they placed in accessible positions, free from inflammable gases and acid fumes **Yes**are they protected from mechanical injury and damage from water, steam or oil **Yes**, if situated near unprotectedwoodwork or other combustible material, state distance of same horizontally from or vertically above the switchboards **> 12"** and **> 48"**are they constructed wholly of durable, non-ignitable non-absorbent materials **Enamelled Slate**, is all insulation of high dielectric strength and ofpermanently high insulation resistance **Yes**, if semi-insulating material is used, are all conducting parts insulated from the slabwith mica or micanite or other non-hygroscopic insulating material, and the slab similarly insulated from its framework **Yes**and is the frame effectively earthed **Yes** Are the fittings as per Rule regarding:— spacing or shielding of live parts**Yes**, accessibility of all parts **Yes**, absence of fuses on back of board **Yes**, proportion of omnibusbars **Yes**, individual fuses to voltmeter, pilot or earth lamp **Yes**, connections of switches **Yes**Main Switchgear, description of switchgear for each generator and each outgoing circuit, and arrangement of equalizer switches **One D.P. switch****& 2 S.P. fuses for dynamo. Three S.P. switches each with 240 S.P. fuses****for Annits**Instruments on main switchboard **1** ammeter **1** voltmeter ✓ synchronising device for paralleling purposes.Earth Testing, state what means are provided at the main switchboard for indicating the state of the insulation of the system **One set earth****lamps with switches & fuses** **+ — O — O —**Switches, Circuit Breakers and Fusible Cut-outs, do these comply with the requirements of the Rules **Yes**Joint Boxes Section and Distribution Boards, is the construction, protection, insulation, material, and position of these as per rule **Yes**

©2020

Lloyd's Register
Foundation

011079-011088-0099 1/2

Cables: Single, twin, concentric, or multicore. Single are the cables insulated and protected as per Tables IV or V of the Rules. Yes

Fall of Pressure, state maximum between bus bars and any point of the installation under maximum load < 3 volts.

Cable Sockets and other connections, are the ends of all cables having a sectional area of 0.04 square inch and above provided with soldering sockets Yes

Paper Insulated Cables. If cables are paper covered, is the dielectric at the exposed ends of the conductor protected from moisture by being suitably sealed with insulating compound ✓

Cable Runs, are the cables fixed as far as possible in accessible positions not exposed to drip or accumulation of water or oil, or to high temperature from boilers, steam pipes, uptakes or other hot objects, or to avoidable risk of mechanical damage Yes

Support and Protection of Cables, state how the cables are supported and protected Clipped direct to the steel work & wood work

If cables are run in wood casings, are the casings and caps secured by screws ✓, are the cap screws of brass ✓, are the cables run in separate grooves ✓. If armoured and lead covered cables are secured by metal clips, are the clips spaced as per Table VIII Yes

Refrigerated Chambers, if lights are fitted, are the cables and fittings in accordance with the special requirements ✓

Joints in Cables, state if any, and how made, insulated, and protected None

Watertight Glands and Deck Tubes, are all cables passing through decks and watertight bulkheads provided with deck tubes or watertight glands Yes

Bushes in Beams and Non-watertight Partitions, where unarmoured cables pass through beams and non-watertight partitions, are the holes efficiently bushed Yes state the material of which the bushes are made Lead

Earthing Connections, state what earthing connections are fitted and their respective sectional areas ✓

are their connections made as per Rule ✓

Alternative Lighting, are the groups of lights in the propelling machinery space arranged as per Rule Yes

Emergency Supply, state position and method of control of the emergency supply and how the generator is driven ✓

Navigation Lamps, are these separately wired Yes, controlled by separate switch and separate fuses Yes, are the fuses double pole Yes, are the switches and fuses grouped in a position accessible only to the officers on watch Yes, has each navigation lamp an automatic indicator as per Rule Yes

Secondary Batteries, are they constructed and fitted as per Rule ✓

Fittings, are all fittings on weather decks, in stokeholds and engine rooms and wherever exposed to drip or condensed moisture, watertight Yes, are any fittings placed in spaces in which goods are liable to be stacked in close proximity to them; if so, how are they protected Yes in stores Guarded, are any fittings placed in spaces where inflammable or explosive dust or gases are liable to be present, if so, how are they protected ✓, how are the cables led ✓

where are the controlling switches situated ✓

Searchlight Lamps, No. of ✓, whether fixed or portable ✓, are their fittings as per Rule ✓

Arc Lamps, other than searchlight lamps, No. of ✓, are their live parts insulated from the frame or case ✓, are their fittings as per Rule ✓

Motors, are their working parts readily accessible ✓, are the coils self-contained and readily removable for replacement ✓, are the brushes, brush holders, terminals and lubricating arrangements as per Rule ✓, are the motors placed in well-ventilated compartments in which inflammable gases cannot accumulate and clear of all inflammable material ✓, are they protected from mechanical injury and damage from water, steam or oil ✓, are their axes of rotation fore and aft ✓, if situated near unprotected woodwork or other combustible material, are the motors of the totally enclosed, pipe ventilated, forced draught, drip or flame proof type ✓, if not of this type, state distance of the combustible material horizontally or vertically above the motors ✓ and ✓

Control Gear and Resistances, are the generator field and motor speed regulators, starters and controllers constructed and fitted as per Rule ✓

Lightning Conductors, where lightning conductors are required, are these fitted as per Rule ✓

Ships carrying Oil having a Flash Point less than 150° F. Have the special requirements of the Rules been complied with regarding switches, joint boxes, section and distribution boards, protection of cables, method of distribution, lead of cables, lights and fittings ✓

If portable lamps for use in dangerous spaces are supplied, are they of a type approved by the Home Office ✓

PARTICULARS OF GENERATING PLANT.									
DESCRIPTION OF GENERATOR.	No. of	RATED AT				DRIVEN BY	WHERE DRIVEN BY AN INTERNAL COMBUSTION ENGINE.		
		Kilowatts.	Volts.	Amps.	Revs. per Min.		Fuel Used.	Flash Point of Fuel.	
MAIN ...	1	4	110	36.4	650	Compound steam engine			
AUXILIARY ...	✓								
EMERGENCY ...	✓								
ROTARY TRANSFORMER	✓								
LIGHTING AND HEATING CONDUCTORS.									
Ref. No.	DESCRIPTION.	No. of Conductors.	Effective Area of each Conductor. Sq. Ins.	COMPOSITION OF STRAND.		Total Maximum Current. Amperes.	Approximate Length. (Lead and Return.) Feet.	Insulated with	HOW PROTECTED.
				No.	Diameter.				
	MAIN GENERATOR...	1	0.46	✓ 19	17 SWG	36.4	30	P.V.I.R.	Lead covered.
	EQUALISER CONNECTIONS ...	✓							
	AUXILIARY GENERATOR ...	✓							
	EMERGENCY GENERATOR ...	✓							
	ROTARY TRANSFORMER...	✓							
	AUXILIARY SWITCHBOARDS ...	✓							
	ENGINE ROOM ...	✓							
	BOILER ROOM ...	✓							
	ACCOMMODATION ...	✓							
	NAVIGATION ...	1	0.0532	✓ 3	18 SWG	5.273	110	do	do
	GENERAL LIGHTING ...	1	0.125	✓ 7	18 SWG	11.45	30	do	do
	GANGWAY LIGHTS ...	1	0.19	✓ 19	20 SWG	18.2	32	do	do
	WIRELESS ...	✓							
	SEARCHLIGHT ...	✓							
	MASTHEAD LIGHT... EACH...	1	0.0246	✓ 1	17 SWG	9.1	60	do	do
	SIDE LIGHTS... EACH...	1	0.0246	✓ 1	17 SWG	9.1	41	do	do
	COMPASS LIGHTS ...	1	0.0246	✓ 1	17 SWG	2.73	24	do	do
	POOP LIGHTS ...	✓							
	CARGO LIGHTS ...	✓							
	ARC LAMPS ...	✓							
	HEATERS ...	✓							
MOTOR CONDUCTORS.									
Ref. No.	DESCRIPTION.	No. of Motors.	Effective Area of each Conductor. Sq. Ins.	COMPOSITION OF STRAND.		Total Maximum Current. Amperes.	Approximate Length. (Lead and Return.) Feet.	Insulated with	HOW PROTECTED.
				No.	Diameter.				
	BALLAST PUMP ...								
	MAIN BILGE LINE PUMPS ...								
	GENERAL SERVICE PUMP ...								
	EMERGENCY BILGE PUMP ...								
	SANITARY PUMP ...								
	CIRC. SEA WATER PUMPS ...								
	CIRC. FRESH WATER PUMPS ...								
	AIR COMPRESSOR ...								
	FRESH WATER PUMP ...								
	ENGINE TURNING GEAR ...								
	ENGINE REVERSING GEAR ...								
	LUBRICATING OIL PUMPS ...								
	OIL FUEL TRANSFER PUMP ...								
	WINDLASS ...								
	WINCHES, FORWARD ...								
	WINCHES, AFT ...								
	STEERING GEAR ...								
	(a) MOTOR GENERATOR ...								
	(b) MAIN MOTOR ...								
	WORKSHOP MOTOR ...								
	VENTILATING FANS ...								

All Conductors are of annealed copper conforming to British Standard Specification No. 7.
The Insulated Conductors are guaranteed to withstand the immersion and resistance tests specified in the Rules.
The foregoing is a correct description.

J. Charters

Electrical Engineers.

Date *6th December '27*

COMPASSES.

Distance between electric generators or motors and standard compass *40 feet*

Distance between electric generators or motors and steering compass ☒

The nearest cables to the compasses are as follows:—

A cable carrying *5.273* Amperes *5* feet from standard compass ☒ feet from steering compass.

A cable carrying *4.54* Amperes *17* feet from standard compass ☒ feet from steering compass.

A cable carrying *.273* Amperes *in* feet from standard compass ☒ feet from steering compass.

Have the compasses been adjusted with and without the electric installation at work at full power *Yes*

Has the effect of switching on and off circuits, motors and other electro-magnetic apparatus within the vicinity of the compasses been noted *Yes*

The maximum deviation due to electric currents was found to be *Nil* degrees on *any* course in the case of the standard compass, and ☒ degrees on ☒ course in the case of the steering compass.

FERGUSON BROTHERS (PORT GLASGOW) LTD.

Robert Ferguson

DIRECTOR.

Builder's Signature.

Date

Is this installation a duplicate of a previous case ☐ If so, state name of vessel

General Remarks (State quality of workmanship, opinions as to class, &c.)

This installation has been fitted on board under special survey. Tested under full working conditions and found satisfactory. The materials & workmanship were found to be good and sound.

It is submitted that

this vessel is eligible for
THE RECORD. Elec. light.

16/12/27

Total Capacity of Generators *4* Kilowatts.

The amount of Fee £ *5.0.0.*

When applied for,

9.12.27

When received,

4.1.28

Travelling Expenses (if any) £ *10/6*

J. S. Rankin
Surveyor to Lloyd's Register of Shipping.

Committee's Minute *GLASGOW 13 DEC 1927*

Assigned

Elec. Light.



© 2020

Lloyd's Register
Foundation