

SPARE PARTS

MAIN ENGINES (Type 6150-P)

Cylinder cover.

- 1 cylinder cover.
- 1 set of studs and nuts for one cylinder cover.

Fuel valve.

- 6 fuel valves complete.
- 3 push spindles.
- 3 loose bottom pieces.
- 1 overflow valve spindle.
- 1 roller with pin.
- 6 springs.
- 12 safety caps.

Inlet valve.

- 1 inlet valve complete.
- 1 roller with pin.
- 6 springs.

Exhaust valve.

- 12 exhaust valves complete.
- 3 loose spindles.
- 3 loose bottom pieces.
- 3 loose seats.
- 1 roller with pin.
- 6 springs.



© 2020

Lloyd's Register
Foundation

011120-011129-0147 1/4

Starting valve.

- 1 starting valve complete.
- 6 springs.
- 1 roller with pin.
- 6 safety caps.

Safety valves

- 1 safety valve complete.
- 6 springs.

Piston.

- 1 piston complete with rings.
- 2 sets of piston rings for one piston.
- 2 sets of scraper rings for one piston.
- 1 set telescopic pipe with packing.

Connecting rods.

- 1 pair of crank pin brasses.
- 2 bolts with nuts for crank pin brasses.
- 1 pair of cresshead brasses.
- 2 bolts with nuts for cresshead brasses.

Main bearing.

- 1 pair of main bearings brasses of each size.
- 2 studs with nuts.

Crank shaft.

- 1 set of coupling bolts for one flange.

Fuel oil pump.

- 1 piston.
- 1 suction valve.
- 1 delivery valve.
- 6 springs of each size.



© 2020

Lloyd's Register
Foundation

0147 214

3 packings complete for piston.

Compressor.

- 1 pair of crank pin brasses for connecting rod.
- 2 bolts with nuts for connecting rod.
- 1 pair of crosshead brasses.
- 1 set of piston rings for L.P.piston.
- 1 set of piston rings for I.P.piston.
- 1 set of piston rings for H.P.piston.
- $\frac{1}{2}$ set of L.P.suction valves.
- 1 set of I.P.suction valves.
- 1 set of H.P.suction valves.
- $\frac{1}{2}$ set of delivery valves.
- 1 set of I.P.delivery valves.
- 1 set of H.P.delivery valves.
- 1 set of springs of each size for compressor.
- 1 H.P. cooling coil.

Chain drive.


- 2 chain links for chain drive.

Bilge and sanitary pumps.

- 1 suction valve.
- 1 delivery valve.

Miscellaneous.

- 1 set of springs for indicator.
- rubber
- Assorted number of/rings.
- 1 length of pipe for injection air of each size with cone and union.
- 1 length of pipe for starting air with flanges, each size.



1 length of pipe for fuel oil of each size with cone and union from branch pipe to fuel valve.

6 glasses for lubricator.

Assorted number of nuts and packing.

1 spring of each size for motor, not mentioned above.

~~~~~



© 2020

Lloyd's Register  
Foundation

0197 414