

THE BRITISH CORPORATION FOR THE SURVEY AND REGISTRY OF SHIPPING.




PARTICULARS OF HATCH COAMINGS, WEBS, FORE AND AFTERS, &c.

S.S. "maiwava" ex "Schleswig"

NUMBER OF HATCHWAY, counting from Forward,		1	2	Raised Quarter 3 Decks		
DIMENSIONS OF HATCHWAY,		12'-11" x 9'-10"	23'-11" x 13'-1 1/2"	9'-5" x 11'-10"		
COAMINGS.	Height above Steel Deck,	31 1/2"	31 1/2"	31 1/2"	Sketch of No 3. Hatch F. & A. Section	
	Thickness—					
	Sides,	35"	45"	45"		
	Ends,	35"	35"	35"		
HATCH BEAMS.	Number,	1	3	1		
	Spacing,	6'-5 1/2"	5'-11 1/2"	5'-11 1/2"		
	Scantling and Sketch,					
	Bearing Surface of Carriers on Coaming,	2 1/4"	2 1/4"	2 1/4"		
FORE AND AFTERS	Number,					
	Spacing,					
	Unsupported Lengths,					
	Scantlings,*					
	Bearing Surface at Ends,					
* If of wood, state if iron shod at ends, and give dimensions below Hatches.						
HATCH COVERS	Thickness,	3"	3"	3"		
	How Fitted,	F. & A.	F. & A.	F. & A.		

* Surveyors are to note that it is recommended that all wood Fore and Afters be iron shod.



© 2021

Lloyd's Register Foundation