



DIMENSIONS:

LENGTH BETWEEN PP	L = 300'-0" = 91.440 METR.
BREADTH MOULDED	B = 44'-0" = 13.410 "
DEPTH LLOYDS	D = 27'-0" = 8.230 "
TO UPPER DECK	TO UPPER DECK = 27'-0" = 8.230 "
TO SECOND DECK	TO SECOND DECK = 19'-0" = 5.791 "

TO CLASS LLOYD'S 100A1 WITH FREEBOARD THE DRAFT CORRESPONDING TO A COMPLETE SUPERSTRUCTURE VESSEL HAVING A TONNAGE OPENING DOUBLE BOTTOM ARRANGED FOR OIL FUEL THE FLAM POINT TO BE ABOVE 580°C (50°F) AND THE REQUIREMENT OF SECTION 20 AND 50 OF THE RULES TO BE COMPLIED WITH STRENGTHENED FOR NAVIGATION IN ICE? ELECTRICALLY WELDED?

SEE LETTER RE BULKHEAD CRUSION

NUMERALS:

	FOOT	METRIC
D	= 27'-0"	= 8.230
L/D	= 300'-0" / 27'-0"	= 11.111
L/B	= 300'-0" / 44'-0"	= 6.818
L/D	= 300'-0" / 27'-0"	= 11.111
L/B	= 300'-0" / 44'-0"	= 6.818

D = 8.230 METR. IN MOTORROOM = 4.685 METR.



6

AS BUILT.

PART NO. 283-284-285

"Tina Portvorn" ★

PROFILE AND PLANS

SKALA 1:100

KOCKUMS MEK VERKSTADS A.B. MALMO SWEDEN

F 283 / 2

DATE 22-5-48

CORRECTED AS APPROVED BY LLOYD'S REGISTER 16/3 1948