

6 Rpt. 4b

Date of writing report L.R. 923d 7.5.63

Survey held at Köln-Deutz
B.N. 1.8369.0.7030

Received London

No. of visits In shops 4
On vessel

Port Köln

First date 21.1.63

Last date

No. 816

15.3.63

11 OCT 1963
20 MAY 1963

FIRST ENTRY REPORT ON INTERNAL COMBUSTION MACHINERY

No. in R.B. - Name - Gross tons -

Owners - Managers - Port of Registry - Year Month

Hull built at Elmshorn By D.W. Kremer Sohn Yard No. 1100 When -

Main Engines made at Köln-Deutz By Klöckner-Humboldt-Deutz Eng. No. 3529387-94 When 3.63

Gearing made at - By -

Donkey boilers made at - By -

Machinery installed at - By -

Particulars of restricted service of ship, if limited for classification -

Particulars of vegetable or similar cargo oil notation, if required -

Is ship to be classed for navigation in ice? - Is ship intended to carry petroleum in bulk? -

Is refrigerating machinery fitted? - If so, is it for cargo purposes? - Type of refrigerant -

Is the refrigerating machinery compartment isolated from the propelling machinery space? - Is the refrigerated cargo installation intended to be classed? -

The following particulars should be given as fully and as clearly as possible. Where the answer is "No" or "None", say so! Ticks and other signs of doubtful meaning are not to be used. Where the wording is not applicable to the installation, a black line may be inserted. If the main engines have been constructed at another port and are covered by a separate report, the particulars given in that report need not be repeated below, but the port and report number should be stated.

No. of main engines - No. of propellers - Brief description of propulsion system -

MAIN RECIPROCATING ENGINES. Licence Name and Type No. one airless injection heavy oil SBA8M 517

No. of cylinders per engine 8 Dia. of cylinders 130 mm stroke(s) 170 mm 2 or 4 stroke cycle 4 Single or double acting single

Maximum approved BHP per engine 230 at 1350 RPM of engine and - RPM of propeller.

Corresponding MIP 10.20 kg/cm² (For DA engines give MIP top & bottom) Maximum cylinder pressure 70 kg/cm² Machinery numeral 46

Are the cylinders arranged in Vee or other special formation? - If so, number of crankshafts per engine -

TWO STROKE ENGINES. Is the engine of opposed piston type? - If so, how are upper pistons connected to crankshaft? -

Is the exhaust discharged through ports in the cylinders or through valve(s) in the cylinder covers? - No. and type of mechanically driven scavenge pumps or blowers per engine and how driven -

No. of exhaust gas driven scavenge blowers per engine - Where exhaust gas driven blowers only are fitted, can the engine operate with one blower out of action? -

If a stand-by or emergency pump or blower is fitted, state how driven - No. of scavenge air coolers - Scavenge air pressure at full power -

Are scavenge manifold explosion relief valves fitted? -

FOUR STROKE ENGINES. Is the engine supercharged? yes Are the undersides of the pistons arranged as supercharge pumps? no No. of exhaust gas driven blowers per engine one No. of supercharge air coolers per engine none Supercharge air pressure at full load 0.33 kg/cm² Can engine operate without supercharger? yes

TWO & FOUR STROKE ENGINES-GENERAL. No. of valves per cylinder: Fuel 1 Inlet 1 Exhaust 1 Starting - Safety -

Material of cylinder covers cast iron Material of piston crowns aluminium Is the engine equipped to operate on heavy fuel oil? no

Cooling medium for: -Cylinders water Pistons - Fuel valves - Overall diameter of piston rod for double acting engines -

Is the rod fitted with a sleeve? no Is welded construction employed for: Bedplate? no Frames? no Entablature? no Is the crankcase separated from the underside of pistons? no

Is the engine of crosshead or trunk piston type? trunk Total internal volume of crankcase 240 litres. No. and total area of explosion relief devices none

Are flame guards or traps fitted to relief devices? - Is the crankcase readily accessible? no If not, must the engine be removed for overhaul of bearings, etc? yes

Is the engine secured directly to the tank top or to a built-up seating? - How is the engine started? electrically

Can the engine be directly reversed? no If not, how is reversing obtained? reversing reduction gear type WUö180/3,5:1

Has the engine been tested working in the shop? yes How long at full power? 6 hours

CRANK & FLYWHEEL SHAFTING. Date of approval of torsional vibration characteristics of the propelling machinery system 7/5/63 State barred speed range(s), if imposed for working propeller - For spare propeller - Is a governor fitted? yes Is a torsional vibration damper or detuner fitted to the shafting? yes

Where positioned? opposite flywheel Type friction damper No. of main bearings 9 Are main bearings of ball or roller type? no

Distance between inner edges of bearings in way of crank(s) 137 mm Distance between centre lines of side cranks or eccentrics of opposed piston engines -

Crankshaft type: Built, semi-built, solid. (State which) solid

Diameter of journals 90 mm Diameter of crankpins Centre 85 mm Side - Breadth of webs at mid-throw 130 mm Axial thickness of webs 32.5 mm

If shrunk, radial thickness around eyeholes - Are dowel pins fitted? no Crankshaft material Journals Cr. steel Minimum Y.P. 70 kg/mm² Approved 15.9.62

Webbs - Tensile strength 90 kg/mm² min.

Diameter of flywheel 520 mm Weight 85 kg Are balance weights fitted? no Total weight - Radius of gyration -

Diameter of flywheel shaft - Material - Minimum approved tensile strength -

Flywheel shaft: separate, integral with crankshaft, integral with thrustshaft. (State which) integral with crankshaft


PLEASE RETURN THIS REPORT WITH YOUR FIRST ENTRY.

My

10/7/63

563C

7/5/63



© 2021

Lloyd's Register Foundation

011544-011554-010512

GENERAL REMARKS

State if the machinery has been constructed and/or installed under special survey in accordance with the Rules, approved plans and Secretary's letters. State quality of materials and workmanship and give recommendations for classification, including any special notation to be assigned. Where existing machinery is submitted for classification the circumstances should be explained as fully as possible.

This engine has been constructed under special survey of tested materials and is in accordance with the Secretary's letters, approved plans and Rules Requirements. The materials and workmanship are good and the engine, when tested in the shops under full and overload conditions was found to function satisfactorily. The governor tests were also found satisfactory. This engine, in my opinion, is suitable for main propelling purposes and when satisfactorily installed and reported will be eligible to receive the notation * IMC (with date).

for H. Haremeister V. 1326 cm
K. Butcher
Engineer Surveyor to Lloyd's Register of Shipping.

PARTICULARS OF IDENTIFICATION MARKS (Including Port of origin) of important Forgings and Castings. (Copies of certificates should be forwarded with report.)

Conn. RODS LLOYD'S KLN. 181/9-16 H.D. 1.2.63

CRANKSHAFT OR ROTOR SHAFT LLOYD'S DSF 360 H.S. 11.12.62

FLYWHEEL SHAFT -

THRUST SHAFT -

GEARING -

INTERMEDIATE SHAFTS -

SCREW AND TUBE SHAFTS -

PROPELLERS -

OTHER IMPORTANT ITEMS turbo blowers: G.Fi. 28.9.60 LR T.P. 2,5 kg/cm²

Is the installation a duplicate of a previous case? no If so, state name of vessel -

Date of approval of plans for crankshaft 15.9.62 Straight shafting - Gearing - Clutch -

Separate oil fuel tanks - Pumping arrangements - Oil fuel arrangements -

Cargo oil pumping arrangements - Air receivers - Donkey boilers -

Dates of examination of principal parts: -

Fitting of stern tube - Fitting of propeller - Completion of sea connections - Alignment of crankshaft in main bearings -

Engine checks & bolts - Alignment of gearing - Alignment of straight shafting - Testing of pumping arrangements -

Oil fuel lines - Donkey boiler supports - Steering machinery - Windlass -

Date of Committee FRIDAY - 1 NOV 1963 Special Survey Fee DM 308.-

Decision See Ham 12986 Runn. Test DM 100.-

Expenses DM 40.-

Date when A/c rendered KLN. 6365, dd. 29.