

(ABS requirements approved)

302 lbs. with joining shackle)

(Received at London Office,.....)

seams,

Also spot

and minor

695 Port UDDEVALLIA Date March, 19 57.

We request that the Single Screw Turbine Tanker Building

Standard Oil Co. of California by Uddevallavarvet Aktiebolag

10,000 Tons. Length, 782'-0" breadth, 116'-0" depth, 56'-0"

Specially Surveyed while building (+100AL C.P.B. (Dual class A.B.)) If for a particular term or class, state the same

whereby engage to pay the established Special Survey Fees or any variation therefrom which has duly notified and, in addition, any travelling and other expenses which may be incurred by the owners in connection with the survey.

This request is made upon the terms of the Rules and Regulations of Lloyd's Register of Shipping provide that:—

Let the Committees of the Society use their best endeavours to ensure that the functions of the Society are properly executed, understood that neither the Society nor any Member of any of its Committees is under any circumstances whatever to be responsible for any inaccuracy in any report or certificate issued by the Society or its Surveyors, or in any entry in the Register or the publication of the Society, or for any error of judgment, default or negligence of any of its Committees or any Member of the Surveyors, or other Officers or Agents of the Society."

in Builder's Yard. Manufacturers of Engines De Laval Steam Turbine Co., Trenton.

of authorisation Oct. 12/4/57

Ditto of Boilers Babcock & Wilcox, USA

Signature

[Signature]

UDDEVALLAVARVET AKTIEBOLAG

Secretary, Lloyd's Register of Shipping, 71, Fenchurch Street, London, E.C.3.

To avoid misunderstanding, orders for materials requiring to be tested should be marked as follows:—"Inspection and Testing by Lloyd's Register Surveyors to the Society's requirements."

is strengthening for navigation in ice

is additional strengthening for heavy cargoes fitted? No

is the ship (if not a motorship) fitted for the carriage and burning of oil as fuel? Yes

DROP TEST

Weight (to include pins, etc.) kgs.

8565 ✓

8545 ✓

8460 ✓

Shaft

4350

4354

4362

Moulded

3'-2.3/4" ✓

floor 6" ✓

duct keel fitted ✓

© 2021

Lloyd's Register Foundation

011671-011677-0086-1