

Lloyd's Register of Shipping

2/3, Piazza Cavour

Genoa, 4th March, 1948

Ref. S.

Dear Sir,

M.V. " SERGIO LAGHI "RECEIVED
- 4 MAR 1948
ANSO.....

In reply to the enquiry of the 23rd Jan. regarding Genoa Report No. 16516 on the above Vessel we have been in communication with Mr. Binivento who confirms:

- 1) that 180 x 180 x 20 mm Stringer Angles have been fitted to the Upper Deck;
- 2) that the thickness of the Bridge Deck is 9mm.
- 3) that the thickness of the Strake G amidships is 18.5 mm.
- 4) that the 22 mm Diam. Rivets in the treble rivetted seams of the side shall plating and in the single rivetted seams of the bridge side plating are 88 mm apart.
- 5) that the 22 mm Diam. Rivets in the butts of the bridge side plating are 77 mm apart.
- 6) that the depth of the bottom longitudinal is 380 mm.
- 7) the spacing of the Stiffeners on the collision and Aft Peak Bulkheads
- 8) is 744 mm.
- 9) the spacing of the rivets connecting the lugs of the transverses to the bottom and side shell in the wing cargo tanks are 110 mm.
- 10) there are 22 lengths of chain cable (605 metres total length) of 67^{MM} Diam.
- 11) the butts of the bottom shell plating are welded and treble riveted straps are fitted.

The longitudinals are connected to the W.T. Bulkheads (on the opposite side of the stiffeners) by welded brackets.

Yours faithfully

The Secretary
London.

ATG/ag

© 2021
SENIOR SURVEYOR FOR ITALYLloyd's Register
Foundation

011800 - 011804 - 0457

Referred to Mr. Perrie

RP

For Skip Surveyors (F.E. Rpts.) to note.

RP



© 2021

Lloyd's Register
Foundation

RECEIVED

VE
Recei
F0010