

Rpt. 4c

Date of writing report 13th December, 1963

Received London

Port of Augsburg

No. 1734

Survey held at Augsburg

No. of visits 13

First date 20th Feb. 63 Last date 2nd December, 1963

## FIRST ENTRY REPORT ON AUXILIARY INTERNAL COMBUSTION ENGINES

Name of Ship - mT. "FEDOR POLETAEV"  
(Or Contract No. if name unknown).Owners. BLACKSEA STATE STEAMSHIP LINES, USSR.  
(Or Consignees)

Ship Built at Genoa/Italy

by Società Ansaldo SpA

when 1963

Yard No. 1594

Auxiliary Engines or Gas Turbines made at Augsburg

by M.A.N. A.G.

when 1963

Eng. Nos. 303 098

Total No. of sets and description (including type name) W 8 V 17.5/22A supercharged

## INTERNAL COMBUSTION RECIPROCATING ENGINES.

No. of cylinders per engine 8 ✓ Dia. of cylinders 175 mm ✓ Stroke 220 mm ✓

2 or 4 stroke cycle 4 ✓ Maximum approved BHP 305 ✓ at 750 ✓ RPM Corresponding MIP 10.35 kg/cm<sup>2</sup> ✓ Maximum pressure 7.5 kg/cm<sup>2</sup> ✓

Fuel gas oil Are cylinders arranged in Vee or other special formation? no If so, No. of

crankshafts per engine - Is engine of opposed piston type? - No. and type of mechanically driven scavenge pumps or blowers

per engine - No. of exhaust gas driven blowers or superchargers per engine one Is welded construction

used for: Bedplate? - Entablature? - Total internal volume of crankcase (if 20 cu. ft. or over) 0.665 m<sup>3</sup> ✓ No. and total area ofcrankcase explosion relief devices 2: 80 cm<sup>2</sup> ✓ Are flame guards or traps fitted? - Cooling medium for: Cylinders water

Pistons - No. of attached pumps: F.W. cooling 1 S.W. cooling 1 Lubricating oil 1 How is engine started? by air

## SHAFTING. Is a damper or detuner fitted? yes No. of main bearings 9 Are bearings of ball or roller type? - Distance between

inner edges of bearings in way of cranks 250 mm ✓ Crankshaft: ~~cast iron~~ solid. Material of crankshaft S.M. Steel, 34CrMo4 Approvedminimum tensile strength 80 kg/mm<sup>2</sup> Dia. of pins 105 mm ✓ Journals 105 mm ✓ Breadth of webs at mid throw 178 mm ✓ Axial

thickness 42 mm ✓ If shrunk, radial thickness around eyeholes - Dia. of flywheel 800 mm ✓ Weight 394 kgs. Are balance

weights fitted? yes Total weight 60 kgs. Rad. of gyration 110 mm Dia. of flywheel shaft -

Has each engine been tested in shop? yes How long at full power? 5 hrs. Was it tested with driven machinery attached? no Was the

governing tested and found satisfactory? yes Date of approval of torsional vibration characteristics (for engines of 150 BHP and over) 17.9.1963

Date of approval of shafting 10.2.1949 11.5.1951 Identification marks on shafting LLOYD'S AUG 4430 H.K.S. 8.1.63 C510698

Particulars of driven machinery -

Port and No. of Certificate for Starting Air Receivers none.

## AUXILIARY GAS TURBINES. BHP per set At RPM of output shaft. Open or closed cycle?

Arrangement of turbines. HP drives at RPM HP gas inlet temp. pressure

(A small diagram should be attached showing gas cycle) IP " at " IP " " " " " " " " " " " "

LP " at " LP " " " " " " " " " " " "

No. of air compressors per set Centrifugal or axial flow type? Material of turbine blades

Material of compressor blades No. of air coolers per set No. of heat exchangers per set How are

turbines started? Are the turbines operated in conjunction with free piston gas generators?

Total No. of free piston gas generators Dia. of working pistons Dia. of compressor pistons No. of double strokes

per minute at full power Gas delivery pressure Gas delivery temperature

Have the turbines and attached equipment been tested in shop? How long at full power? Were they tested with driven machinery

attached? Particulars of gearing

Date of approval of plans Identification marks Particulars of driven machinery

## ELECTRIC GENERATORS. Port and No. of Certificate for generators of 100 Kw. and over

For generators under 100 Kw., has Makers' Certificate been obtained? Are Certificates attached?

The foregoing description is correct and the particulars are as approved for torsional vibration characteristics (strike out words not applicable)

Maschinenfabrik Augsburg-Nürnberg A. G.  
Manufacturer

Is this machinery duplicate of a previous case? yes If so, which? Yard No. 1593

GENERAL REMARKS. State if the machinery has been constructed under special survey in accordance with the Rules, approved plans and Secretary's letters. State quality of materials and workmanship. Where existing machinery is submitted for classification the circumstances should be explained as fully as possible.

This auxiliary engine has been constructed under special survey in accordance with the requirements of the Rules and otherwise with the approved plans. The material used in the construction was tested and the workmanship was found satisfactory. The engine was tested running on maker's test bed under full-, over-, and partial loads with satisfactory results. In my opinion the engine can be recommended for the notation \* L.M.C. (with date) when the whole machinery has been satisfactorily fitted on board and tried under full working conditions.

und. frame 40.--  
Survey Fee DM 409.50  
Painting test DM 100.--  
Expenses 15.-- Total DM 564.50

Date when a/c rendered 20.12.1963

Engineer Surveyor to Lloyd's Register

Declaration to be signed by Surveyor at fitting-out Port:— The above described machinery has been fitted on board the "FEDOR POLETAEV" - Yard No. 1594.

at ANSALDO S.A. CANTIERE in a proper manner and found satisfactory when tested on the (date) 24/3/64 under full working conditions.

NAVALE, GENOVA/SESTRI

Engineer Surveyor to Lloyd's Register

011864011876-0100