

012193-012202-0235

THRIGE

ODENSE - DENMARK

Margit Gorthon
HELSINGBORG ~~FIRST ENTRY~~ REPORT No. 3350.

TEST-SHEET

Maskinfabriken Iron A/S, Søborg.

Order No.: 0704276 19 60 DC compound motor
date: 30.1.61 Rotor No.: 9-60809
Pressure: enclosed ventilated
Ings: SKF 6307-09
Type: CL14 No.: 3031715
Volts: 220 Amps.: 82
R. P. M.: 2300
Brush holders: KA19
HP/kW.: 220 Rating: cont.
Grade: EG16
Size: 16 x 30

Test voltage: 2000 volts for 1 min. Resistance: 100 megohms.

Time	Terminal Volts	Line Amps.	Shunt		R. P. M.	Air-temp. °C	Remarks
			Volts	Amps.			
00.00	220	82	220	1,52	2200	19	
01.00	-	-	-	1,36	2380	23	
02.00	-	-	-	1,33	2380	25	
03.00	-	-	-	-	-	26	
04.00	-	-	-	-	-	-	
05.00	-	-	-	-	-	-	
06.00	-	-	-	-	-	-	

Temperature rise: { Armature: 24 °C, Shunt: 27 °C, Commutator: 14 °C
Thermometer-method: { Series-winding: 18 °C, Interpoles: 14 °C

00.00	220	102,5	220	1,36	2330	26	
01.00	-	-	-	1,32	2360	27	
02.00	-	-	-	1,32	-	-	
	-	82	-	1,36	2360		
	-	123	-	1,32	2310		for 1 min.
	-	164	-	-	2230		- 15 sec.
	-	8	-	-	2450		

31.1.61 - C.S.N.

Manufactured and tested in accordance with
Odense, Denmark

Rules of Lloyd's Register
28.3.61

pr. Thomas B. Thrige