

Deck Drillings

SEL'S NAME S.S. "MECCA" REPORT No. 4812

THICKNESSES OF PLATING ascertained by drilling, and comparison of same with the original thicknesses.

The thicknesses are in hundredths of an inch.

| STRAKE. | AMIDSHIP. | | | | | FORWARD. | | | | | AFT. | | | | | REMARKS. | |
|---------------|--------------------|------------------------|------|--------------------|------|--------------------|------------------------|------|--------------------|------|--------------------|------------------------|------|--------------------|------|----------|-----------------|
| | Original Thickness | Thickness by drilling. | | Diminution if any. | | Original Thickness | Thickness by drilling. | | Diminution if any. | | Original Thickness | Thickness by drilling. | | Diminution if any. | | | |
| | | Port. | Std. | Port. | Std. | | Port. | Std. | Port. | Std. | | Port. | Std. | Port. | Std. | | |
| ESHEER AKE | O | .54 | .50 | .50 | .04 | .04 | .42 | .35 | .35 | .07 | .07 | .39 | .35 | .40 | .04 | - | |
| below | N | .54 | .45 | .54 | .09 | - | .42 | .40 | .35 | .02 | .07 | .39 | .35 | .40 | .04 | - | |
| STRAKE | M | .65 | .65 | .65 | - | - | .50 | .50 | .45 | - | .05 | .50 | .50 | .49 | - | .01 | |
| ake below | L | .65 | .65 | .65 | - | - | .50 | .50 | .50 | - | - | .46 | .45 | .45 | .01 | .01 | |
| " | K | .65 | .55 | .60 | 1.0 | .05 | .80 | .80 | .75 | - | .05 | .49 | .50 | .50 | - | - | doubled midship |
| " | J | .65 | .60 | .65 | .05 | - | .80 | .75 | .75 | .05 | .05 | .48 | .45 | .45 | .03 | .03 | doubled midship |
| " | H | .65 | .60 | .60 | .05 | .05 | .80 | .80 | .75 | - | .05 | .48 | .45 | .45 | .03 | .03 | doubled midship |
| " | G | .65 | .60 | .60 | .05 | .05 | outside area | | | | | .65 | .65 | .65 | - | - | |
| " | F | .65 | .65 | .65 | - | - | outside area | | | | | .65 | .65 | .65 | - | - | |
| " | E | .65 | .65 | .60 | - | .05 | .80 | .80 | .80 | - | - | .65 | .65 | .60 | - | .05 | |
| " | D | .65 | .65 | .65 | - | - | outside area | | | | | .73 | .70 | .70 | .03 | .03 | |
| " | C | .65 | .65 | .60 | - | .05 | .80 | .70 | .75 | 1.0 | .05 | .55 | .55 | .55 | - | - | Stealer aft |
| " | B | .65 | .65 | .60 | - | .05 | .60 | .56 | .60 | .04 | - | .50 | .45 | .50 | .05 | - | |
| " | A | .65 | .65 | .60 | - | .05 | .56 | .55 | .55 | .01 | .01 | .50 | .40 | .45 | 1.0 | .05 | |
| KEEL | | .75 | .75 | | | | .67 | .67 | | | | .70 | .70 | | | | |

Drillings at ends to be made in the vicinity of the peak bulkheads.

Port to

.50

.50

.50

--

--

012473-012430-0143

Port to

.50

.50