


# THE BRITISH CORPORATION FOR THE SURVEY AND REGISTRY OF SHIPPING.

## PARTICULARS OF HATCH COAMINGS, WEBS, FORE AND AFTERS, &c.

S.S.

NUMBER OF HATCHWAY, counting from Forward,	-	No. 2.	No. 1. ✓			
DIMENSIONS OF HATCHWAY,	- - - -	33'-2" x 12'-0"	14'-0" x 12'-0"			
COAMINGS.	{ Height above Steel Deck, - { Thickness— { Sides, - { Ends, -	{ 36 Rule { 30 Rule	{ 36 Rule { 30 Rule			
HATCH BEAMS.	{ Number, - - - - { Spacing, . - - - { Scantling and Sketch, - { Bearing Surface of Carriers on Coaming, - - - -	{ 3. 3. { 2 1/2" x 2 1/2" x 36 { 6 x 6 x 1 1/2" Iron ✓	{ 1. 1. { 2 1/2" x 2 1/2" x 36 { 9 x 9/20" full. { Plate 5/16" iron ✓			
FORE AND AFTERS.	{ Number, - - - - { Spacing, - - - - { Unsupported Lengths, - - { Scantlings,* - - - - { Bearing Surface at Ends, - { * If of wood, state if iron shod at ends, and give dimensions below Hatches.	{ 3. 3. { 6 x 6 - { wood ✓	{ 3. 3. { 6 x 6 - { wood			
HATCH COVERS.	{ Thickness, - - - - { How Fitted, - - - -	{ 3 3	{ 3. 3.			

\* Surveyors are to note that it is recommended that all wood Fore and Afters be iron shod.



© 2021

Lloyd's Register  
Foundation

012446 - 012459 - 0070