

Total 499.83
Gross Tonnage 499.83
Register Tonnage 318.48

Depth, at middle of length from top of keel to top of beam at side of uppermost continuous deck. See Sec. 3 (1c) to Bridge Deck: 6.05
1st Longitudinal Number (L x D)
2nd Numeral L x (B + D)

Owners N.V. Rotterdamse
Managers
(Where necessary to be entered in Reg. Book)

Terneuzensche Scheepsbouw.

Yard No.54.

3m.6.52

Received by Chief Ship Surveyor

Received from Chief Ship Surveyor

VESSEL'S NAME In.Sc. Motorship "GERRY S" REPORT Ant. No. 28246

The remarks of the Chief Ship Surveyor are desired on this case for the consideration of the Classing Committee.

("The endorsement to contain a succinct summary of any repairs that have been required and to show the cause or causes of such repairs, and also to bring out clearly any exceptional features in connection with the case, so that the Classing Committee may have all the salient points presented in the endorsement."—Extract from Sub-Committee's Report, 24/5/92.)

L. 177' B. 31.2' D. 13.22'

This is a single deck coaster with combined poop and bridge and longitudinally framed at bottom and deck.

The scantlings and arrangements, as reported, conform with the Society's Revised Rules and Regulations, and are in accordance with or equivalent to those shown on the approved plans.

IT IS THEREFORE SUBMITTED the ship is eligible to be classed:-

*100A1

1" Dk, "pt Elec. welded" Longitudinal framing at bottom & at dk"
Cell DB 112 pt W.B. 186t pt O.F.; FPT 58t; APTs pt W.B. 9t pt O.F. pt F.W.
FK, 3BH, Cem, Lloyd's A & CP
P & B 106' F 29'
Mchy Aft
O.L. 193.8'
ESD
"j"


REVISED CERTIFICATE

IT IS FURTHER SUBMITTED the Surveyors be requested to -

- (1) confirm that the steering gear, windlass and bilge pumps were tried under working conditions,
- (2) state the process of manufacture of the steel and if it has been tested as required by the Rules.

19.3.53.

no letter
20/3/53.



© 2021

Lloyd's Register

012620-012623-0031

spacing

Bridge Deck, Angle, [or]

Spacing

DOUBLE BOTTOM.

Solid Floors, thickness and spacing

" " Are Frame and Reversed Frame joggled?

longitudinal &

Longitudinal

see separate