

# Lloyd's Register of Shipping.

## SURVEYS FOR FREEBOARD.

(COMPUTATION FOR STEAMER, SAILING SHIP, TANKER.)

 Index No. \_\_\_\_\_  
 (For London Office only.)

Ship's Name <b>Howaldtswerke</b> <b>- 960</b>	Official Number	Nationality and Port of Registry	Gross Tonnage <b>42.98</b>	Date of Build	Port of Survey
Moulded Dimensions: Length <b>459.75</b> Breadth <b>62.99</b> Depth <b>31.69</b>					Date of Survey <b>27.4.57</b>
Moulded displacement at moulded draught = 85 per cent. of moulded depth					Surveyor's Signature
Coefficient of fineness for use with Tables <b>assumed .70</b>					Particulars of Classification <b>+ COAST</b> <b>(Contaminated)</b>

DEPTH FOR FREEBOARD (D).	DEPTH CORRECTION.	ROUND OF BEAM CORRECTION.
Moulded depth ... <b>31.69</b>	(a) Where D is greater than Table depth (D - Table depth) R = <b>(31.72 - 30.67) × 3 = + 3.15</b>	Moulded Breadth (B) <b>62.99</b>
Stringer plate ... <b>03</b>	(b) Where D is less than Table depth (if allowed) (Table depth - D) R = <b>1.05</b>	Standard Round of Beam = $\frac{B \times 12}{50} = \frac{62.99 \times 12}{50} = 15.12$
Sheathing on exposed deck $T \left( \frac{L-S}{L} \right) =$	If restricted by superstructures	Ship's Round of Beam = <b>11.8</b>
Depth for Freeboard (D) = <b>31.72</b>		Difference = <b>15.12</b>
		Restricted to
		Correction = $\frac{\text{Diff}^e}{4} \times \left( 1 - \frac{S_1}{L} \right) = \frac{15.12}{4} \times 0.123 = 4.54$

## DEDUCTION FOR SUPERSTRUCTURES.

	Mean Covered Length (S)	Equivalent Enclosed Length (S <sub>1</sub> )	Height	Height Correction	Effective Length (E)
Poop enclosed					
„ overhang					
R.Q.D. enclosed					
„ overhang					
Bridge enclosed					
„ overhang aft					
„ overhang forward					
Fore enclosed					
„ overhang					
Trunk aft					
„ forward					
Tonnage opening aft					
„ „ forward					
Total					

Standard Height of Superstructure **7.5**  
 „ „ R.Q.D. **42**  
 Deduction for complete superstructure  
 Percentage covered  $\frac{S}{L} =$   
 $\frac{S_1}{L} =$  } **assumed .990**  
 $\frac{E}{L} =$   
 Percentage from Table, Line A. **98.77**  
 (corrected for absence of forecastle (if required))  
 Percentage from Table, Line B.  
 (corrected for absence of forecastle (if required))  
 Interpolation for bridge less than .2L (if required)  
 Deduction = **42 × .9877 = - 41.50** ✓

## SHEER CORRECTION.

Station	Standard Ordinate	S	M	Product	Actual Ordinate	Effective Ordinate	S	M	Product
A.P.	<b>53.975</b>	1			<b>60</b>	<b>105.48</b>	1		<b>105.48</b>
$\frac{1}{4}$ L from A.P.		4			<b>28</b>	<b>46.94</b>	4		<b>187.76</b>
$\frac{2}{4}$ L „		2			<b>6</b>	<b>11.60</b>	2		<b>23.20</b>
Amidships		4			<b>-</b>	<b>-</b>	4		<b>-</b>
$\frac{3}{4}$ L from F.P.		2			<b>14</b>	<b>18.86</b>	2		<b>37.72</b>
$\frac{1}{4}$ L „		4			<b>60</b>	<b>76.30</b>	4		<b>305.20</b>
F.P.		1			<b>126</b>	<b>171.48</b>	1		<b>171.48</b>
Total				<b>503.78</b>	<b>+45.48</b>				<b>830.84</b>

 Correction =  $\frac{\text{Difference between sums of products}}{18} \left( \frac{.75 - S}{2L} \right) = \frac{327.06}{18} \times .25 = 4.54$  ✓  
 If limited on account of midship superstructure.

 Mean actual sheer aft =  
 Mean standard sheer aft =

 Mean actual sheer forward =  
 Mean standard sheer forward =

 Length of enclosed superstructure forward of amidships = **.5**  
 „ „ aft of „ =

 Actual height superstructure = **11.29**  
 Standard = **7.5**  
**3.79**  
**= 45.48** ✓

## Deduction for Tropical Freeboard.

Addition for Winter and Winter North Atlantic Freeboard.

 Depth to Freeboard Deck = **31.72**  
 Summer freeboard = **4.05**  
 Moulded draught (d) = **27.67**

Deduction for Tropical freeboard and addition for

Winter freeboard =  $\frac{d}{4}$  inches =

Addition for Winter North Atlantic Freeboard (if required) =

## Deduction for Fresh Water.

Displacement in salt water at summer load water line

 $\Delta =$ 

Tons per inch immersion at summer load water line

T =

Deduction =  $\frac{\Delta}{40 T}$  inches

## TABULAR FREEBOARD corrected for Flush Deck (if required)

Correction for coefficient

 Depth Correction ... **3.15**  
 Deduction for superstructures ... **41.50**  
 Sheer correction ... **4.54**  
 Round of Beam correction ... **.05**  
 Correction for Thickness of Deck amidships ...  
 Other corrections, scantlings, etc. ...
Summer Freeboard = **48.61** ✓

## SUMMER FREEBOARD amidships from Centre of Disc to top of Deck Line, Water, Steel, Deck:—

Tropical Fresh Water Line above Centre of Disc

Fresh Water Line

Tropical Line

Winter Line below

Winter North Atlantic Line

Tropical Fresh Water Freeboard

Fresh Water

Tropical

Winter

Winter North Atlantic

 Draught overboard = **29.33**  
**27.67**  
**1.66**



A new form should be prepared if any alterations that affect the freeboard have been made. If no such alterations have been made, the Surveyor should endorse the form on this side with his signature and the date.

53'-4"	10'-6"	-126
47'-10"	5'-0"	60
44'-0"	1'-2"	14
42'-10"	—	—
43'-4"	-6"	6
45'-2"	2'-4"	28
47'-10"	5'-0"	60

Trade of ship .....

Names of sister ships .....

Builder's name and yard number .....

Owners .....

Fee £.....



© 2021

Lloyd's Register  
Foundation