

Single
on the Twin
Triple
Quadruple

Screw vessel

Motor tanker "MADELEINE".

Tons
Net.

1 E

by Chief Engineer Surveyor


Received from Chief Engineer Surveyor

S NAME "MADELEINE" REPORT Mdb. 19821.
Hbg. No. 2368.
Ids. 824.
Got. 19686.

Remarks of the Chief Engineer Surveyor are desired on this case for the consideration of the Classing Committee.

("The endorsement to contain a succinct summary of any repairs that have been required and to show the cause or causes of such repairs, and also to bring out clearly any exceptional features in connection with the case, so that the Classing Committee may have all the salient points presented in the endorsement."—Extract from Sub-Committee's Report, 24/5/02.)

Type of Engine Oil Engine 2 SCSA.
9 cyl. 26 3/4" - 59. 1/16".
New MN 1300.



~~If Boilers fitted with forced draught~~

Tail Shaft. If fitted with a continuous liner Yes.

If fitted with an outside gland of approved type No.

The torsional vibration characteristics of the main propelling machinery were approved in the Secretary's letter of 26.9.52 for a service speed of 112 rpm. Similar calculations for the 165 KW generator sets were approved in the Secretary's letter of 7.5.52 for service speeds of 400 to 450 rpm.




This vessel's machinery appears to have been built in accordance with the Rules and the approved plans, and it is submitted she is eligible to be classed

IMC 6.53
2 DB 150 lb.
"Carrying petroleum in bulk"

The Helsingborg Surveyors should be informed that it is concluded that all essential pumps have been constructed under special survey (No certificates to hand).

X Yes. see 469.
C. 23/7/53

Note for S.R.L. Exhaust gas economiser to be examined at each DBS.



Lloyd's Register
Foundation
13.7.53.

013284-013292-0281

each fitted with a discharge valve always accessible on the plating of the vessel. Are the blow off cocks fitted with a spigot and brass How are they protected.