

REPORT ON ELECTRICAL EQUIPMENT.

(OTHER THAN FOR THE PROPULSION OF THE VESSEL)

5-NOV 1943

Received at London Office

Date of writing Report 12th Aug., 1943 When handed in at Local Office 12th Aug., 1943 Port of Vancouver, B. C.
 No. in Survey held at Vancouver, B. C. Date, First Survey 5th June, 1943 Last Survey 17th July, 1943
 Reg. Book. (Number of Visits 13)
 -- on the Steel Single Screw Steamer "FORT ASTORIA" Tons { Gross 7188.56
 Net 4291.30
 Built at Vancouver, B.C. By whom built West Coast Shipbuilders, Ltd. No. 123 When built 1943
 Owners Minister of Munitions & Supply of Canada. Port belonging to
 Electric Light Installation fitted by West Coast Shipbuilders, Ltd. Contract No. -- When fitted 1943
 Is the Vessel fitted for carrying Petroleum in bulk No

System of Distribution Constant Pressure Two-Wire Direct CurrentPressure of supply for Lighting 110 volts, Heating -- volts, Power 110 volts.Direct or Alternating Current, Lighting Direct Power Direct

If alternating current system, state frequency of periods per second --

Has the Automatic Governor been tested and found efficient when the whole load is suddenly thrown on or off YesGenerators, do they comply with the requirements regarding temperature rise Yes, are they compound wound Yesare they over compounded 5 per cent. No, if not compound wound state distance between each generator --Where more than one generator is fitted are they arranged to run in parallel Yes, is an adjustable regulating resistance fitted inseries with each shunt field Yes Have certificates of test results for machines under 100 kw. been submitted andapproved Attached. Also Have machines over 100 kw. been inspected by the Surveyors during manufacture and testing Under 100 K.W.Ship's Trial results attached. Are all terminals accessible, clearly marked, and furnished with sockets Yes, are they so spaced or shielded that they cannot be accidentally earthed,short circuited, or touched Yes Are the lubricating arrangements of the generators as per Rule YesPosition of Generators Engine Room/Generator platform on first grating level starboard aft, is the ventilationin way of the generators satisfactory Yes are they clear of all inflammable material Yes if situated near unprotected

woodwork or other combustible material, state distance of same horizontally from or vertically above the generators -- and --

are the generators protected from mechanical injury and damage from water, steam or oil Yes, are their axes of rotation fore and aft YesEarthing, are the bedplates and frames of the generating plant efficiently earthed Yes are the prime movers and their respective generatorsin metallic contact Yes Main Switch Boards, where placed Aft end of generator platform athwartships.

If the generators and main switchboard are not placed in the same compartment, is each generator provided with

a fuse on each insulated pole as near as possible to the terminals of the generator, additional to that provided on the main switchboard Same compartmentSwitchboards, are they placed in accessible positions, free from inflammable gases and acid fumes Yes, are they protected from mechanicalinjury and damage from water, steam or oil Yes, if situated near unprotected woodwork or other combustible material, state distance of same

horizontally from or vertically above the switchboards -- and --, are they constructed wholly of durable, non-ignitable non-absorbent

materials Ebony Asbestos, is all insulation of high dielectric strength and of permanently high insulation resistance Yesis it of an approved type Yes, if semi-insulating material is used, are all conducting parts insulated from the slab with mica or micanite or other


non-hygroscopic insulating material, and the slab similarly insulated from its framework --, is the non-hygroscopic insulating material of an approved

type --, and is the frame effectively earthed Yes Are the fittings as per Rule regarding:—spacing or shielding of live partsYes, accessibility of all parts Yes, absence of fuses on back of board Yes, temperature rise ofomnibus bars 4 C., individual fuses to voltmeter, pilot or earth lamp Yes, are moving parts of switches alive in the"off" position No are all screws and nuts securing connections effectively locked Yes are any fuses fitted on the live side ofswitches No Main Switchgear, description of switchgear for each generator and each outgoing circuit, and arrangement of equalizer switches150 Ampere D.P. circuit breakers on separate panels with overload and reverse current trips, and a three pole isolating switch for each generator. D.P. switches and fuses for eachoutgoing circuit.

Are turbine driven generators fitted with emergency trip switch as per rule -- Are cupboards or compartments containing switchboards composed of

fire-resisting material or lined with approved material Yes Instruments on main switchboard 3 ammeters 3 volt-meters Selector switch on No.2 Generator voltmeter

synchronising device for paralleling purposes. For compound machines is the ammeter connected on the opposite pole to equaliser connection

Yes Earth Testing, state what means are provided at the main switchboard for indicating the state of the insulation of the systemNo.2 Generator voltmeter selector switch wired to give ground readings in addition toGenerator and Bus Bar readings. Also earth lamps and switch switches, Circuit Breakers and Fusible Cut-outs,do these comply with the requirements of the Rules Yes are the fusible cutouts of an approved type Yes have the reversedLloyd's Register
Foundation

013390-013396-0033 1/2

current protection devices been tested under working conditions. **Yes** Joint Boxes, Section and Distribution Boards, is the construction, protection, insulation, material, and position of these as per rule **Yes**
Single and twin on high pressure multicore on telephones
 Cables: Single, twin, concentric, or multicore are the cables insulated and protected as per Tables IV, V, X or XI of the Rules. **Yes**

If the cables are insulated otherwise than as per Rule, are they of an approved type **Yes** Fall of Pressure, state maximum between bus bars and any point of the installation under maximum load. **5.5**

Cable Sockets, are the ends of all cables having a sectional area of 0.04 square inch and above provided with soldering sockets. **Yes** Paper Insulated and Varnished Cambric Insulated Cables.

If conductors are paper or varnished cambric insulated, is the dielectric at the exposed ends of the conductor protected from moisture by being suitably sealed with insulating compound **--**, or waterproof insulating tape **Yes (Degaussing)**

Cable Runs, are the cables fixed as far as possible in accessible positions not exposed to drip or accumulation of water or oil, or to high temperature from boilers, steam pipes, uptakes or other hot objects, or to avoidable risk of mechanical damage **Yes** Are cables in machinery spaces, galleys, laundries, bathrooms and lavatories lead covered or run in conduit **Lead covered and Conduit**

Support and Protection of Cables, state how the cables are supported and protected **Clipped to woodwork in accommodation by brass clips spaced as per Rule and run in wood casings, elsewhere run in conduit, all cables protected by metal guards where liable to damage.**

If cables are run in wood casings, are the casings and caps secured by screws. **Yes**, are the cap screws of brass **Yes**, are the cables run in separate grooves **--**. If armoured and lead covered cables are secured by metal clips, are the clips spaced as per Table VIII **Yes**

Refrigerated Chambers, are the cables and fittings in accordance with the special requirements **Yes**

Joints in Cables, state if any, and how made, insulated, and protected **None except at Junction Boxes**

Watertight Glands and Deck Tubes, are all cables passing through decks and watertight bulkheads provided with deck tubes or watertight glands **Yes**

Bushes in Beams and Non-watertight Partitions, where unarmoured cables pass through beams and non-watertight partitions, are the holes efficiently bushed **Yes** state the material of which the bushes are made **Lead and hardwood collars**

Earthing Connections, state what earthing connections are fitted and their respective sectional areas **Lead covered cables, conduit, and metal trays effectively earthed.**

are their connections made as per Rule **Yes**

Alternative Lighting, are the groups of lights in the propelling machinery space arranged as per Rule **Yes** Emergency Supply, state position and method of control of the emergency supply and how the generator is driven **12 in number 4.5 volt Bulst emergency hand lamps fitted throughout the vessel.**

Navigation Lamps, are these separately wired **Yes**, controlled by separate switch and separate fuses **Yes**, are the fuses double pole **Yes**, are the switches and fuses grouped in a position accessible only to the officers on watch **Wheelhouse**

has each navigation lamp an automatic indicator as per Rule **Yes** Secondary Batteries, are they constructed and fitted as per Rule **Yes**

Fittings, are all fittings on weather decks, in stokeholds and engine rooms and wherever exposed to drip or condensed moisture, watertight **Yes**, are any fittings placed in spaces in which goods are liable to be stacked in close proximity to them; if so, how are they protected **Cast metal guards**

are any fittings placed in spaces where inflammable or explosive dust or gases are liable to be present, if so, how are they protected **Yes in magazines. Russell Stoll No. 4521 Explosion Proof Fittings.** how are the cables led

Cables run in conduit

where are the controlling switches situated **Outside compartments**

are all fittings suitably ventilated **Yes**, are all switches and lampholders constructed wholly of non-ignitable, non-absorbent materials **Yes**

Heating and Cooking Appliances, are they constructed and fitted as per Rule **None**, are air heaters constructed and fitted as per Rule **None**

Searchlight Lamps, No. of **1-12" -1000 Watt metal filament lamp.** are they fixed or portable **Spigot on either side of flying bridge** are their fittings as per Rule **Yes**

Are Lamps, other than searchlight lamps, No. of **--**, are their live parts insulated from the frame or case **--**, are their fittings as per Rule **--**

Motors, are their working parts readily accessible **Yes**, are the coils self-contained and readily removable for replacement **Yes**

are the brushes, brush holders, terminals and lubricating arrangements as per Rule **Yes**, are the motors placed in well-ventilated compartments in which inflammable gases cannot accumulate and clear of all inflammable material **Yes**, are they protected from mechanical injury and damage from water, steam or oil **Yes** are their axes of rotation fore and aft **Where possible**, if situated near unprotected woodwork or other combustible material, are the motors of the totally enclosed, pipe ventilated, forced draught, drip or flame proof type **Drip Proof**

if not of this type, state distance of the combustible material horizontally or vertically above the motors **--** and **--** have machines of over 100 BHP been inspected by the Surveyors during manufacture and testing **100** Control Gear and Resistances, are the generator field and motor speed regulators, starters and controllers constructed and fitted as per Rule **Yes** Lightning Conductors, where lightning conductors are required, are these fitted as per Rule **--** Ships carrying Oil having a Flash Point less than 150°F. Have the special requirements of the Rules been complied with regarding switches, joint boxes, section and distribution boards, protection of cables, method of distribution, lead of cables, lights and fittings **--** are all fuses of the filled cartridge type **--** are they of an approved type **--**

If portable lamps for use in dangerous spaces are supplied, are they of a self-contained, battery-fed type approved by the Home Office **--**

Spare Gear, if the vessel is for open sea service have spares been supplied as per Rule **Yes**

PARTICULARS OF GENERATING PLANT.

DESCRIPTION OF GENERATOR.	No. of	RATED AT				DRIVEN BY	WHERE DRIVEN BY AN INTERNAL COMBUSTION ENGINE.	
		Kilowatts.	Volts.	Amperes.	Revs. per Min.		Fuel Used.	Flash Point of Fuel.
MAIN ...	3	15	110	136	575	Steam Reciprocating	--	--
AUXILIARY ...								
EMERGENCY ...								
ROTARY TRANSFORMER								

GENERATOR, LIGHTING AND HEATING CONDUCTORS.

DESCRIPTION.	No. of	CONDUCTORS.		COMPOSITION OF STRAND.		TOTAL MAXIMUM CURRENT. AMPERES.		Approximate Length. (Lead and Return.) Feet.	Insulated with	HOW PROTECTED
		No. per Pole.	Total Nominal Area per Pole Sq. Ins.	No.	Diameter.	Circuit.	Rule.			
MAIN GENERATOR Nos. 1, 2, 3	1	1	.166	19	.105	136	162	22	Rubber	In Conduit
EQUALISER CONNECTIONS	1	1	.0828	19	.074	--	102	18	"	"
AUXILIARY GENERATOR										
EMERGENCY GENERATOR										
ROTARY TRANSFORMER MOTOR										
ENGINE ROOM	1	1	.052	7	.097	50.5	75	30	"	"
BOILER ROOM										
Low Power	1	1	.008	7	.038	20	27	6	"	Switchboard wiring
AUXILIARY SWITCHBOARDS	1	1	.082	19	.074	75	102	200	"	In conduit
Refrigerator	1	1	.131	19	.094	65	138	30	"	"
Degaussing Panel	1	1	.032	7	.077	13	55	40	"	"
Power Panel P1	1	1	.052	7	.097	17	75	336	"	"
Accommodation	1	1	.082	19	.074	43.2	102	390	"	"
Crew	1	1	.052	7	.097	43.5	75	86	"	"
Aft Deck House	1	1	.052	7	.097	39	75	116	"	"
Engr. House Star	1	1	.052	7	.097	39.5	75	288	"	"
Accommodation	1	1	.032	7	.077	22	55	300	"	"
Saloon	1	1	.032	7	.077	17.5	55	300	"	"
Port	1	1	.052	7	.097	30	75	450	"	"
House	1	1	.032	7	.077	10	27	450	"	"
Navigation	1	1	.003	7	.024	.45	10	300	"	"
WIRELESS	1	1	.003	7	.024	.45	10	100	"	Lead covered
SEARCHLIGHT	1	1	.003	7	.024	.3	10	22	"	In Conduit
MASTHEAD LIGHT	1	1	.052	7	.097	30.5	75	450	"	"
SIDE LIGHTS	1	1	.032	7	.077	14	55	230	"	"
COMPASS LIGHTS	1	1	.020	7	.061	10	43	295	"	"
POOP LIGHTS										
CARGO LIGHT										
For'd. L7	1	1	.052	7	.097	30.5	75	450	"	"
Aft L8	1	1	.032	7	.077	14	55	230	"	"
Gyro Compass	1	1	.020	7	.061	10	43	295	"	"

MOTOR CONDUCTORS.

DESCRIPTION.	No. of Motors.	CONDUCTORS.		COMPOSITION OF STRAND.		TOTAL MAXIMUM CURRENT. AMPERES.		Approximate Length. (Lead and Return.) Feet.	Insulated with	HOW PROTECTED
		No. per Pole.	Total Nominal Area per Pole Sq. Ins.	No.	Diameter.	In Circuit.	Rule.			
BALLAST PUMP										
MAIN BILGE LINE PUMPS										
GENERAL SERVICE PUMP										
EMERGENCY BILGE PUMP										
SANITARY PUMP										
CIRC. SEA WATER PUMPS										
CIRC. FRESH WATER PUMPS										
AIR COMPRESSOR										
FRESH WATER PUMP	1	1	.005	7	.030	6.5	16	36	Rubber	In Conduit
ENGINE TURNING GEAR										
ENGINE REVERSING GEAR										
LUBRICATING OIL PUMPS										
OIL FUEL TRANSFER PUMP										
WINDLASS										
WINCHES, FORWARD										
WINCHES, AFT										
STEERING GEAR										
(a) MOTOR GENERATOR										
(b) MAIN MOTOR										
WORKSHOP MOTOR										
Eng. Room	1	1	.005	7	.030	6.5	16	112	"	"
VENTILATING FAN										



© 2021

Lloyd's Register Foundation

0033 2/2

All Conductors are of annealed copper conforming to British Standard Specification No. 7 (or International Electro-technical Commission Publication No. 28).

The Insulated Conductors are guaranteed to withstand the immersion and resistance tests specified in the Rules.

The foregoing is a correct description

WEST COAST SHIPBUILDERS LTD.

W. M. Larn
General Manager

Electrical Engineers.

Date 12th Aug., 1943

COMPASSES.

Distance between electric generators or motors and standard compass 19 feet (Gyro Compass)

Distance between electric generators or motors and steering compass 10 feet (Gyro Compass)

The nearest cables to the compasses are as follows:—

A cable carrying .3 Ampères 9 inches from standard compass 9 inches from steering compass. (Compass lights)

A cable carrying .3 Ampères 1'-4" feet from standard compass 1'-4" feet from steering compass. (Compass correction coils)

A cable carrying .3 Ampères 5 feet from standard compass 3 feet from steering compass. (Wheelhouse light)

Have the compasses been adjusted with and without the electric installation at work at full power Yes

Has the effect of switching on and off circuits, motors and other electro-magnetic apparatus within the vicinity of the compasses been noted Yes

The maximum deviation due to electric currents was found to be Nil degrees on All course in the case of the standard

compass, and Nil degrees on All course in the case of the steering compass.

WEST COAST SHIPBUILDERS LTD.

W. M. Larn
General Manager

Builder's Signature.

Date 12th Aug., 1943

Is this installation a duplicate of a previous case Yes, with so, state name of vessel S.S. "FORT COLUMBIA"
points of difference. (Ver. Report No. 5942)

General Remarks (State quality of workmanship, opinions as to class, &c. The electrical equipment of this ship

has been installed under Special Survey in accordance with the approved plans, New York
letters and Society's Rules. The material and workmanship are good. The installation

has been examined under full working conditions, tested as per Rule and found satisfactory

and in our opinion is eligible to have the Society's Classification without Special

Notation. Copies of particulars of ship's trials on generators attached. Maker's

Certificates covering steam auxiliary engines (driving generators) and generators attached.

As fitted plan of electrical wiring attached. The electrical equipment has also been

surveyed during construction and installation on behalf of Wartime Merchant Shipping, Ltd.,

to ensure that the terms of the specification have been fully complied with and this work

has been satisfactorily carried out.

Total Capacity of Generators 45 Kilowatts.

The amount of Fee ... £\$125.00 : 30th Aug. 1943

Travelling Expenses (if any) £\$ 10.00 : When received. 19

Committee's Minute TUES. 7 DEC 1943

Assigned

See for machinery etc

W. G. Donald
Surveyor to Lloyd's Register of Shipping.