

Lloyd's Register of Shipping.

SURVEYS FOR FREEBOARD.

(COMPUTATION FOR STEAMER, ~~SAILING SHIP, TANKER.~~)

Ship's Name <i>No. 1689</i>	Official Number	Nationality and Port of Registry	Gross Tonnage	Date of Build	Port of Survey
Moulded Dimensions: Length <i>551</i> Breadth <i>70</i> Depth 40.5 <i>40.5</i>					Date of Survey
Moulded displacement at moulded draught = 85 per cent. of moulded depth _____ tons					Surveyor's Signature
Coefficient of fineness for use with Tables <i>78 assumed.</i>					Particulars of Classification <i>100 A1 (Contemplated)</i>

Depth for Freeboard (D).	Depth correction.	Round of Beam correction.
Moulded depth <i>40.02</i>	(a) Where D is greater than Table depth (D-Table depth) R = <i>(40.10-36.73)3 = 10.11</i>	Moulded Breadth (B)
Stringer plate <i>1" .08</i>	(b) Where D is less than Table depth (if allowed) (Table depth-D) R = <i>3.37</i>	Standard Round of Beam = $\frac{B \times 12}{50} =$
Sheathing on exposed deck $T \left(\frac{L-S}{L} \right) =$	If restricted by superstructures	Ship's Round of Beam = <i>Standard.</i>
Depth for Freeboard (D) = <i>40.10</i>		Difference
		Restricted to
		Correction = $\frac{\text{Diff}^*}{4} \times \left(1 - \frac{S_1}{L} \right) = \text{NIL.}$

DEDUCTION FOR SUPERSTRUCTURES.

Mean Covered Length (S)	Equivalent Enclosed Length (S _i)	Height	Height Correction	Effective Length (E)	Standard Height of Superstructure
Poop enclosed					" " R.Q.D.
" overhang					Deduction for complete superstructure
R.Q.D. enclosed					Percentage covered $\frac{S}{L} =$
" overhang					" " $\frac{S_i}{L} =$
Bridge enclosed					" " $\frac{E}{L} =$
" overhang aft					Percentage from Table, Line A. (corrected for absence of forecastle (if required))
" overhang forward					Percentage from Table, Line B. (corrected for absence of forecastle (if required))
F'cle enclosed					Interpolation for bridge less than 2L (if required)
" overhang					Deduction = <i>-12.04</i>
Trunk aft					
" forward					
Tonnage opening aft					
" " forward					
Total					

SHEER CORRECTION.

Station	Standard Ordinate	S M	Product	Actual Ordinate	Effective Ordinate	S M	Product	Mean actual shear aft = /
A.P.		1				1		Mean actual shear forward = /
$\frac{1}{2}L$ from A.P.		4				4		Mean standard shear aft = /
$\frac{3}{8}L$ "		2				2		Mean actual shear forward = /
Amidships		4				4		Mean standard shear forward = /
$\frac{3}{8}L$ from F.P.		2				2		Length of enclosed superstructure forward of amidships =
$\frac{1}{2}L$ "		4				4		" " aft of " =
F.P.		1				1		
Total								

Correction = $\frac{\text{Difference between sums of products}}{18} \left(75 - \frac{S}{2L} \right) = \text{NIL.}$
If limited on account of midship superstructure.

If limited to maximum allowance of 1 1/2 ins. per 100 ft. ✓

Deduction for Tropical Freeboard. Addition for Winter and Winter North Atlantic Freeboard. Depth to Freeboard Deck = <i>40.10</i> Ft. Summer freeboard = <i>10.27</i> Moulded draught (d) = <i>29.83</i> Deduction for Tropical freeboard and addition for Winter freeboard = $\frac{d}{4}$ inches = Addition for Winter North Atlantic Freeboard (if required) =	Deduction for Fresh Water. Displacement in salt water at summer load water line $\Delta =$ Tons per inch immersion at summer load water line T = Deduction = $\frac{\Delta}{40T}$ inches =	TABULAR FREEBOARD corrected for Flush Deck (if required) Correction for coefficient $\frac{.78+.68}{1.36} = 1.46/1.36$ <table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 50%;"></td> <td style="width: 50%; text-align: right;">+ -</td> </tr> <tr> <td>Depth Correction</td> <td style="text-align: right;"><i>10.11</i> -</td> </tr> <tr> <td>Deduction for superstructures</td> <td style="text-align: right;">- <i>12.04</i></td> </tr> <tr> <td>Sheer correction</td> <td style="text-align: right;">- -</td> </tr> <tr> <td>Round of Beam correction</td> <td style="text-align: right;">- -</td> </tr> <tr> <td>Correction for Thickness of Deck amidships</td> <td style="text-align: right;">- -</td> </tr> <tr> <td>Other corrections, scantlings, etc.</td> <td style="text-align: right;">- -</td> </tr> <tr> <td></td> <td style="text-align: right;"><i>10.11</i> <i>12.04</i> <i>-1.93</i></td> </tr> <tr> <td></td> <td style="text-align: right;">Summer Freeboard = <i>123.29</i></td> </tr> </table>		+ -	Depth Correction	<i>10.11</i> -	Deduction for superstructures	- <i>12.04</i>	Sheer correction	- -	Round of Beam correction	- -	Correction for Thickness of Deck amidships	- -	Other corrections, scantlings, etc.	- -		<i>10.11</i> <i>12.04</i> <i>-1.93</i>		Summer Freeboard = <i>123.29</i>
	+ -																			
Depth Correction	<i>10.11</i> -																			
Deduction for superstructures	- <i>12.04</i>																			
Sheer correction	- -																			
Round of Beam correction	- -																			
Correction for Thickness of Deck amidships	- -																			
Other corrections, scantlings, etc.	- -																			
	<i>10.11</i> <i>12.04</i> <i>-1.93</i>																			
	Summer Freeboard = <i>123.29</i>																			

SUMMER FREEBOARD amidships from Centre of Disc to top of Deck Line, ~~Wood~~, Steel, Deck: *10' 3/4"*

Tropical Fresh Water Line above Centre of Disc	Tropical Fresh Water Freeboard
Fresh Water Line " "	Fresh Water " "
Tropical Line " "	Tropical " "
Winter Line below " "	Winter " "
Winter North Atlantic Line " "	Winter North Atlantic " "

③: Equi. moulded depth of ② draught having erection as shown on plans, but standard shear & camber, B = 78