


# THE BRITISH CORPORATION FOR THE SURVEY AND REGISTRY OF SHIPPING.

## PARTICULARS OF HATCH COAMINGS, WEBS, FORE AND AFTERS, &c.

S.S. M.S. "Immisshannon".

NUMBER OF HATCHWAY, counting from Forward,	-	Fore 1	Upper Deck 2			
DIMENSIONS OF HATCHWAY,	- - - -	8' x 10'	43' x 14'-6"			
COAMINGS.	Height above <del>Steel</del> Wood Deck,	8 3/4	36"			
	Thickness—{ Sides, - - { Ends, - -	11 1/2 x 3 1/2 x 75 B.A.	4 4			
HATCH BEAMS.	Number, - - - -		6 at at	1 at Centre		
	Spacing, - - - -		7 1/2 x 12 x 12	7 1/2 x 12 x 12		
	Scantling and Sketch, - -		Angles 3 x 3 x 4	3		
	Bearing Surface of Carriers on Coaming, - - - -					
FORE AND AFTERS	Number, - - - -	1				
	Spacing, - - - -	4'-0"				
	Unsupported Lengths, -	10'-0"				
	Scantlings,* - - - -	5 x 4 1/2 x 5				
	Bearing Surface at Ends, -	12 x 10 x 5	3			
	* If of wood, state if iron shod at ends, and give dimensions below Hatches.					
HATCH COVERS	Thickness, - - - -	2 1/2	2 1/2			
	How Fitted, - - - -	Atthwartship	F + A.			

\* Surveyors are to note that it is recommended that all wood Fore and Afters be iron shod.



© 2021

Lloyd's Register Foundation

015020-015225-0008