

... of Frames from moulding edge ...  
... bulding edge, all fore and aft ...

(Class *100A* *Steel*)  
Inches | Inches | *10ths*

... of d'blng at Sh'stk. & lnc. applied  
... Sheerstrake, breadth and thickness..... *48* *13 1/10* *13*

# PARTICULARS for RECORD OF DOUBLE BOTTOMS, &c., in LLOYD'S REGISTER.

(Received at London Office, ..... 188.....)

of Report *3543* Port *Belfast* Date *18<sup>th</sup> March 1889*

in Register Book *46 Sup.* On the *Steel Screw Steamer "Star of England"*

ble bottom, aft, length ..... and water capacity in tons ..... Double bottom, forward, length ..... and water capacity in tons .....

ble bottom, under engines and boilers, length ..... and water capacity in tons ..... If under Engines only, or Boilers only, state which .....

ble bottom, constructed on the cellular system, length *276* and water capacity in tons *400*

peak tank, water capacity in tons ..... After ~~peak~~ <sup>deep</sup> tank, water capacity in tons *120 and 20ft long*

ship deep tank, length ..... and water capacity in tons ..... Other tanks, if fitted, length ..... and water capacity in tons .....

(If necessary, furnish further information by sketch.)

*James Maxton*  
Surveyor to Lloyd's Register of British and Foreign Shipping.

0-4 12/82.)

*BELLS-0270*

Rider Plate	<i>12</i>	<i>10</i>	<i>10</i>						
-------------	-----------	-----------	-----------	--	--	--	--	--	--