

height extended at the Bilges...

15 kts.

69

69

69

69

69

69

69

69

69

69

69

69

69

69

69

69

69

69

69

69

69

69

69

69

Angle ~~iron~~ on ditto

Tie Plates fore and aft, outside Hatchways

Diagonal Tie Plates on Beams No. of Pairs

42 x 42 x 12

4 x 4 x 9

4 x 4 x 9

4 x 4 x 9

4 x 4 x 9

4 x 4 x 9

4 x 4 x 9

4 x 4 x 9

clearly

PARTICULARS for RECORD OF DOUBLE BOTTOMS, &c., in LLOYD'S REGISTER.

(Received at London Office, 1889.)

No. of Report 3553

Port

Belfast

Date

April 13th 1889

No. in Register Book Sup-35

On the

S. S. British Empire

Double bottom, aft, length

—

and water capacity in tons

—

Double bottom, forward, length

—

and water capacity in tons

—

Double bottom, under engines and boilers, length

—

and water capacity in tons

—

If under Engines only, or Boilers only, state which

—

Double bottom, constructed on the cellular system, length

264

and water capacity in tons

545

Fore peak tank, water capacity in tons

—

After peak tank, water capacity in tons

40

Midship deep tank, length

—

and water capacity in tons

—

Other tanks, if fitted, length

—

and water capacity in tons

—

(If necessary, furnish further information by sketch.)

James Simpson
Surveyor to Lloyd's Register of British and Foreign Shipping.

plating for

length

Height up

5 to upper deck and 1 to main deck

BELSS-0320