3 Decks.

~~IRON OR~~ STEEL STEAMER.

Received at London Office FRI 23 JUN 1899

State if Report is also sent on the Machinery of the Vessel yes

Date of completion of report June 21st 1899 Port of Belfast No. 5014

Survey held at Belfast Date First Survey March 23rd 99 Last Survey June 20th 1899

the Steel Screw Steamer "Ping Suey" Rig Schooner, 2 masts

THREE DECKED VESSEL.

CLASS 100 A

		FEET.
TONNAGE under Tonnage Deck...		
between Tonnage Dk. and 3rd and 4th Dk.		
Total under Upper Dk.	5886.91	
Do. of Poop	98.45	
Do. of Bridge House	250.49	
Do. of Forecastle	—	
Do. of Houses on Dk.	133.13	
Do. of excess of Hatchways	28.~~28~~88	
Do. above Crown of Engine Room ..	59.70	
Gross Tonnage	6456.~~26~~88	
Less Crew Space	144.35	
Less above Crown of Engine Room ..	59.70	
TONNAGE FOR FEES..	6226.~~21~~81	
Less Engine Room	2066.32 +2	
Less Navigation Spaces	40.23	
Register Tonnage cut on Beam ..	4149.~~36~~ 76	

		FEET.
Half Breadth (moulded)		26.5
Depth from upper part of Keel to top of Upper Deck Beams (with the normal round up of beam)		34.95
Girth of Half Midship Frame (as per Rule)		57.45
		118.90
deduct 7 feet		7.
1st Number		111.9
Length on deck from after part of stem to fore part of stern post		447.96
2nd Number		50126
Proportions—Breadth to Length		8.45
Depth to Length—Upper Deck to top of Keel		12.98
Main Deck ditto		16.5

Destined Voyage China

Master C. L. M. de la Perrelle

Year of appointment (1) As Master in service of owner of present vessel: 18 91 (2) As Master of this vessel 18 99

Built at Belfast

When built 1899 Launched March 30th

By whom built Workman, Clark & Co. Ltd

Owners China Mutual Steam N. Co. Ltd

Managers — (Where necessary to be entered in Hull Book.)

Residence London

Port belonging to London

If Surveyed while Building, Afloat, or in Dry Dock Whilst Building

	Feet.	Inches.		Feet.	Inches.		Feet.	Inches.	
LENGTH on Deck as per Rule	447	11½	BREADTH—Moulded	58	0	DEPTH, ACTUAL—Top of Floors to top of Upper Dk. Beams	30	11½	No. of Decks with flat laid Two
						Do. do. do. do. Main Dk. Beams	22	4½	No. of Tiers of Beams Two

Dimensions of Ship per Register, Length 450 breadth 58.2 depth 30.9 Moulded depth, ft. 33 ins. 10½ To Upper Dk. Round of Upper Dk. Beam, Actual 13 ins.

FRAMING.	Inches in Ship	Inches in Ship.	16ths or 20ths in Ship.	Inches per Rule Or as	Inches per Rule as Approved	16ths or 20ths per Rule
FRAME, Angles, ~~Z, T, or L Bars~~ for ¾ length amidships	7	3½	10	7	3½	10
Do. for ⅛ at each end	7	3½	9	7	3½	9
Do. in way of Double Bottoms at Solid Floors	3½	3½	10	3½	3½	10
,, ,, at intermdt. Bkts.	—			—		
Distance of Frames from moulding edge to moulding edge, all fore and aft	26			26		
REVERSED FRAME, Angles	7	3½	10	7	3½	10
DEEP FRAMING, depth of girder	10½			10½		
FLOORS, depth and thickness of Floor Plate at mid-line for ¾ length amidships						
,, in way of Engines and Boilers						
,, thickness at the ends of vessel						
,, depth at ¾ the half breadth, as per Rule						
,, height extended at the Bilges						
DOORS & BRACKETS in Cell Dble Bottoms	48		9	48		9
,, ,, Distance apart	26			26		
CENTRE GIRDER, in Double bottom, depth and thickness	48		11	48		11
,, ,, Angles, Top	4	4	10	4	4	10
,, ,, ,, Bottom	5	5	12	5	5	12
SIDE GIRDERS, number on each side & thickness	Two		9	Two		9
,, ,, Angles	3½	3½	10	3½	3½	10
MARGIN PLATE, depth (exclusive of flange) and thickness	42		10	34		10
,, ,, Angles to Outside Plating	4	4	10	4	4	10
INNER BOTTOM PLATING, breadth and thickness of Middle Line Strake	48		11	36		11
,, ,, ,, in Engine and Boiler space		11 & 12			11 & 12	
,, ,, ,, Remainder in Holds			9			9
BEAMS, Upper Deck, ~~Single Angle, Bulb Angle, Plate or~~ Tee Bulb	11		10	11		10
,, ~~Angles on upper edge~~	T. Bulb			T. bulb		
,, Average space	52			52		
BEAMS, Middle Deck, ~~Single Angle, Bulb Angle, Plate or~~ Tee Bulb	12		12	12		12
,, ~~Angles on upper edge~~	T. bulb			T. Bulb		
,, Average space	52			52		
BEAMS, Lower Deck, Single Angle, Bulb Angle, Plate or Tee Bulb						
,, Angles on upper edge						
,, Average space						
BEAMS, Hold, or Orlop, Plate or Tee Bulb						
,, Angles on upper edge						
,, Average space						
BEAMS, Poop Deck, ~~Angle~~, Bulb Angle, ~~Plate or Tee Bulb~~	9½	3½	11	9	3	11
,, ~~Angles on upper edge~~	Bulb angle			Bulb angle		
,, Average space	52			52		
BEAMS, Bridge Deck, ~~Angle~~, Bulb Angle, ~~Plate or Tee Bulb~~ Hatch beams	7½	3	9	9	3	11
	9½	3½	11			
,, ~~Angles on upper edge~~	Bulb angle			Bulb angle		
,, Average space	26			52		
BEAMS, Forecastle Deck, ~~Angle, Bulb Angle, Plate or~~ Tee Bulb	10		10	10	3½	13
,, ~~Angles on upper edge~~	T. Bulb			Bulb angle		
,, Average space	52			52		
PILLARS, In 'tween Deck, size and spacing	3½		52	3½		52
,, ,, Hold ,, ,,	4½		52	4½		52
,, Quarter 'tween Dks., ,, ,,	3½		104	3½		104
,, ,, in Hold ,, ,,	4½		104	4½		104
WEB-FRAMES, In Fore Body, No. and spacing	9 as pr. plan			9 as pr. plan		
,, ,, ,, brdth. & thickness	36		10	36		10
,, No. of Side Stringers ,, ,,	2	36	11	2	36	11
WEB-FRAMES, In E. & B. Space, No. & spacing	4 as pr. plan			4 as pr. plan		
,, ,, ,, brdth. & thickness	36		10	36		10
WEB-FRAMES, In After Body, No. and spacing	7 as pr. plan			7 as pr. plan		
,, ,, ,, brdth. & thickness	36		10	36		10
,, No. of Side Stringers ,, ,,	2	36	11	2	36	11
,, Size of Angles or Tee Bars to Web-Frames	4½	4	10	4½	4	10
BRACKET PLATES to Stringers between Web Frames, depth and thickness	52	24	10	30	24	10

FORGINGS or CASTINGS.	Inches in Ship.	Inches per Rule. Or as Approved.
KEEL, Bar or Side Plates, depth and thickness	—	12 × 3¼
STEM, moulding and thickness	12 × 3¼	12½ × 4¾
STERN-POST for Rudder do. do.	12½ × 4¾	12½ × 4¾
,, for Propeller	12½ × 4¼	11
MAIN PIECE of Rudder, diameter at head	11	
,, ,, do. at heel	9 × 7	8½ × 5½

RUDDER, how constructed Cast steel frame single plate 22/20

Can the Rudder be unshipped afloat? yes.

KEELSONS & STRINGERS.	Inches in Ship.	Inches in Ship.	16ths or 20ths in Ship.	Inches per Rule Or as	Inches per Rule as Approved	16ths or 20ths per Rule
CENTRE LINE KEELSON, Vertical Plate above floors, Through Plate, or Intercostal Plate						
,, Rider Plate						
,, Bulb Plate to Intercostal Keelson						
,, Horizontal Plates on Floors						
,, Angles						
SIDE KEELSON, Angles						
,, Bulb or Plate above floors, for lng.						
,, Intercostal Plate, for length						
,, Attached to outside Plating with Angle						
BILGE KEELSON, Angles						
,, Bulb or Plate above floors, for lng.						
,, Intercostal Plate for length						
,, Attached to outside Plating with Angle						
BILGE STRINGER Angles						
,, Bulb Plate for length						
,, Intercostal Plate for length						
,, Attached to outside Plating with Angle						
SIDE STRINGER Angles						
,, Bulb or Intercostal Plate, for lng.						
,, Attached to outside plating with Angle						
Upper Deck Stringer Plates, br'dth & thickness	72	14		72		14
,, Angle on ditto	5 × 3 × ¼			5 × 3 ×		14
,, Tie Plates fore and aft, outside Hatchways	—			—		
,, Deck.* ~~Iron or~~ Steel, for Entire lng.		9				9
,, Wood Deck. Material & thickness	—			—		
Middle Deck Stringer Plate, br'dth & thickness	72	11		72		11
,, Angles on ditto, No. 2	4 × 4 ×	9		4 × 4 ×		9
,, Tie Plates outside Hatchways						
,, Diagonal Tie Plates on Bms., No. of prs.	1			1		
,, Deck.* ~~Iron or~~ Steel, for Entire lng.		9				9
,, Wood Deck. Material & thickness	—			—		
Lower Deck Stringer Plate, br'dth & thickness	36	11		36		11
,, Angles on ditto, No. 2	4 × 4 ×	10		4 × 4 ×		10
,, ~~Tie Plates, outside Hatchways~~ Face plate	12	11		12		11
,, ~~Deck.* Material and thickness~~ angles to d.	3½ × 3½ ×	10		3½ × 3½		10
Hold, or Orlop Stringer Plate, br'dth & thckn's	36	11		36		11
,, Angles on ditto, No. 2	4 × 4 ×	10		4 × 4 ×		10
,, ~~Tie Plates outside Hatchways~~ Face plate	12	11		12		11
,, ~~Deck. Material and thickness~~ angles to d.	3½ × 3½ ×	10		3½ × 3½		10
Poop Deck Stringer Plate, breadth & thickness	40	8		40		8
,, Angle on ditto	3½ × 3½ ×	8		3½ × 3½		8
,, Tie Plates	—			—		
,, Deck. Material and thickness Teak	3	5		3		5
Bridge Deck Stringer Plate, br'dth & thickness	40	9		40		9
,, Angle on ditto	3½ × 3½ ×	10		3½ × 3½ ×		10
,, Tie Plates	—			—		
,, Deck. Material and thickness Teak	3	7-6-5		3		5
Forecastle Deck Stringer Plate, b'dth & th'kns	40	8		40		8
,, Angle on ditto	3½ × 3½ ×	8		3½ × 3½ ×		8
,, Tie Plates	—					
,, Deck. Material and thickness Teak	3	6		3		5

* If Iron or Steel Deck, state if whole or part, and if Wood Deck is laid thereon.

BULKHEADS.	Number. In Vessel.	Number. Per Rule.	Thickness.	STIFFENERS. Horizontal. Size.	Horizontal. Spacing	Vertical. Size.	Vertical. Spacing	Single or Double Frames.	Height up.
			~~Plates~~ 20ths.	Inches.	Inches.	Inches.	Inches.		
W. T. BULKHEADS	2	6	2 - 7 9	3 × 12	48	6½ × 3½	10 - 36	Double	To Upr. Dk.
PARTITION ,,			Bulb angle						
LONGITUDINAL ,,	—								

Are the outside Plates doubled two spaces of Frames in length No diamond plates

Are the Sluice Valves and Watertight Doors in efficient working order? yes.

Form No. 1B. 9-96

BEL69A-0001 (1 OF 2)

PLATING.

STRAKES.	AS IN SHIP. Amidship. Breadth.	Amidship. Thickness.	Forward. Thickness.	Aft. Thickness.	PER RULE OR AS APPROVED. Amidship. Breadth.	Amidship. Thickness.
	Inches.	10ths or 20ths	10ths or 20ths	10ths or 20ths	Inches.	10ths or 20ths
Flat Plate Keel (If Bar Keel, state Riveting)	48	23	16	16	46	23
Garboard or A Strake	48	17	14	15	36	17
B "		12	11	13		12
C "		13	11	16		13
D "		12	10	16		12
E "		13	12	16		13
F "		13	10	16		13
G "		14	11	16		14
H "		13	10	15		13
J "		14	11	14		14
K "		13	10	13		13
L "		14	11	12		14
M "		13	10	14		13
N "		14	11	13		14
O "		18	10	10		18
Sheer P "	46	20	12	12	46	20
Q "						
R "						
Doubling of Flat Plate Keel						
Length and thickness of Bilges	At back end of Bridge		7/8 26	× 18		13
Length and thickness of Sheerstrakes						
Length and thickness of Strake below						
Poop Sides			7			7
Bridge Sides		10-9-13 & 12	at ends			10-9
Forecastle Sides			7			7

Write 'Sheer Strake' opposite its corresponding letter.

RIVETING.

	Edges. Single or Double.	Edges. Breadth of Lap.	Edges. Rivets. Diam.	Edges. Rivets. Spacing cr. to cr.	Butts. Double or Treble and for what Length.	Butts. Rivets. Diam.	Butts. Rivets. Spacing cr. to cr.	Butts. Straps. Breadth.	Butts. Straps. Thickness.	If Lapped. Breadth.	If Lapped. For what Length.
		Inches.	Inches.	Inches.		Inches.	Inches.	Inches.	Double for	Inches.	Feet.
Flat Plate Keel	Double	6 3/4	1 5/8	4 1/2	Treble	1 5/8	3 1/2	22	16 3/8	—	—
Garboard or A Strake	"	6	1	—	Entire	1	—	—	—	10 1/2	Entire
B "	"	5 1/4	1	3 5/8	length	1	3 5/8	—	—	9	length
C "	"	"	"	"	"	"	"	—	—	"	"
D "	"	"	"	"	"	"	"	—	—	"	"
E "	"	"	"	"	"	"	"	—	—	"	"
F "	"	"	"	"	"	"	"	—	—	"	"
G "	"	"	"	"	"	1	3 1/2	—	—	10 1/2	"
H "	"	"	"	"	"	7/8	3 1/8	—	—	9	"
J "	"	"	"	"	"	1	3 1/2	—	—	10 1/2	"
K "	"	"	"	"	"	7/8	3 1/8	—	—	9	"
L "	"	"	"	"	"	1	3 1/2	—	—	10 1/2	"
M "	"	"	"	"	"	7/8	3 1/8	—	—	9	"
N "	"	"	"	"	"	1	3 1/2	—	—	10 1/2	"
O "	"	"	"	"	"	"	"	—	—	15 1/4	"
Sheer P "	"	6 3/4	1 5/8	"	Treble	1 5/8	3 1/2	22	14 3/8	—	—
Q "											
R "											
Doubling of Flat Plate Keel											
Length and thickness of Bilges											
Length and thickness of Sheerstrakes											
Length and thickness of Strake below											
Poop Sides	Single	2 1/2	3/4	3 1/4	Double	3/4	2 5/8	—	—	5	Entire
Bridge Sides	Double	4 3/4	7/8	3 1/4	Treble	7/8	3 5/8	—	—	9	"
Forecastle Sides	Single	2 1/2	3/4	3 1/4	Double	3/4	2 5/8	—	—	5	"

Quadruple

Manufacturer's name or trade mark of the Iron or Steel (state process of manufacture of Steel) used for Frames, Floors, Beams, Keelsons, Tie and Stringer Plates, Plating, &c.? Siemens Martin Steel; Frames & Rev. frames Lanarkshire; Floors Barrow; L. Beams Cleveland & Sons; Keelsons Lanarkshire; & Steel Co. of Scotland; Stringers and Outside plating Barrow Ham. S. Co.

Has the Steel been tested as required by the Rules? Yes.

Upper Deck Stringer Plate Butts, ~~treble~~ riveted for Half, length amidship. Straps, ~~single, double or~~ overlapped for Entire, length ~~amidship~~.

Middle Deck Stringer Plate Butts, treble riveted for entire, length ~~amidship~~. Straps, ~~single, double or~~ overlapped for Entire, length ~~amidship~~.

Butts of Bilge & Side Stringers and Tie Plates, treble or double riveted? Treble

Inner Bottom Plating, riveting of **Edges** Double **Butts** Double

Centre Girder Butts, Treble riveted **Keelson Butts,** Treble riveted.

Frames, riveted through Plates with 1 and 7/8 in. Rivets, about 7 and 6 apart.

Rivets, state whether Iron or Steel Iron

FRAMES extend in one length from Margin Plate to Gunwale.

REVERSED FRAMES on floors and frames extend from Margin plate to lower deck for 2/5 length, and abaft After pea bulkhead, remainder to M. & U. decks alternately, Alternate ~~vertical~~ bars to Forecastle deck.

MASTS, SPARS, &c.

No Square Sails

	Material.	Total Length.	Diameter and Thickness. At Partners.	Heel.	Hounds.	Head.	No. of Plates in round.	Angles. Number.	Angles. Size.	Riveting. Seams.	Riveting. Butts.
Lower Masts. Fore	Steel	80 × 9	24 × 7/20	18 × 6/20	22 5/8 × 7/20	20 × 5/20	2	3	3 1/2 × 3 × 9/20	Single	Treble & Double
Lower Masts. Main		84 × 10	25 × 7/20	24 × 6/20	21 × 6/20	19 × 6/20	2	3	3 × 3 × 5/20	—	—
~~Mizen~~		~~& M. Pk~~									
~~Derrick~~											

Masts doubled at partners and at heels.

Topmasts, ~~Lower~~ and Remainder of **Spars** of Pitch pine

Rigging, Material and Size, **Shrouds** Galvd steel, wire 4" and 3 3/4". **Stays** 5" and 4" respectively

Sails. One Complete Suit of fidheaded Sails, and the following spare sails —

EQUIPMENT No. 56620 LETTER G.T.

ANCHORS.

Number of Certificate.	Anchors.	Weight, Ex. Stock. Cwts.	qrs.	lbs.	Weight of Stock. Cwts.	qrs.	lbs.	Test, per Certificate. Tons.	cwts.	qrs.	lbs.	Weight Required by Table 22. Cwts.	qrs.	lbs.	Description of Anchor.	Makers.	Where and when tested and Superintendent.
41910	1st Bower	74	1	11	—			56	"	"	"	73	"	"	Hall's Stockless	Kingley Sons	Netherton 31 Mar. 99
41840	2nd "	72	1	7	—			55	"	"	"	73	"	"	Cast steel Head	" "	" 22 " "
41839	3rd "	61	2	"	—			49	3	3	"	62	"	"	" "	" "	" 22 " "
	4th "																H. Green Superin.
	Collective weight	208	10	"								208	"	"			
41794	Stream	18	3	24	4	3	6	19	7	2	"	18	3	"	Rodgers J. S.	" "	13 Mar. 99
41793	Kedge	9	2	16	2	0	26	11	15	2	14	9	"	"	" "	" "	13 " "

CHAIN CABLES.

Number of Certificate.	Fathoms.	Size.	Test per Certificate. Tons.	Weight of Chain Cable. Supplied.	Per Table 22.	Fathoms and Size per Table 22.	Description.	Makers of Cables.	When and where tested, and Superintendent.
25818	150	2 3/20	142-2-0	123-0-27	144-1-0	300 × 2 3/20	Stud link	Kingley & Sons	Netherton 3 Mar. 99
25819	150	"	101-10-0	122-3-27				" "	13 " "
			246-0-26						
~~Iron Stream Cable~~ or Steel Wire	120	5	89			120 × 5			

HAWSERS AND WARPS.

Material.	Fathoms.	Size.	Breaking Test of Steel Wire Towline.	Fathoms and Size per Table 22.
TOWLINE	130	6 1/2	71	130 × 5 1/2
HAWSER	2 × 90	2 3/4	2 × 44	4 × 90 × 2 3/4
WARP	2 × 100	5	Manila	
	2 90	7	4 & 90	3 1/2

Boats 4 Life Boats, 2 Cutters, and 1 Dingy

Pumps, Number 9 Diameter of Barrel 2 × 5 1/2 × 4 State whether they are in efficient working order Yes.

Windlass is Emerson & Walkers Patent steam **Capstan** Good

Engine Room Skylights.—How constructed? of plates and angles.

What arrangements for deadlights in bad weather? Solid top with bulls eyes.

Coal Bunker Openings.—How constructed? plates & angles How are lids secured? with hatch bars Height above deck? 15 ins.

Number of **Scuppers,** and numbers and dimensions of **Freeing Ports, &c.** 8 Scuppers, 4 freeing ports 33 × 24 and 8 × 33 × 12 ea. side.

Ceiling in Holds, thickness and material 2 1/2 Red pine **Ceiling 'tween Decks,** thickness and material 6 × 2 spruce.

Cargo Hatchways.—How formed? of plates and angles. **Hatches,** If strong and efficient? Yes

State size **No. 1 Hatch** (Forward) 21.0 × 15.0 **No. 2 Hatch** 20.4 × 16.3 **No. 3 Hatch** 19.6 × 16.3 **No. 4 Hatch** 22.6 × 15.0.

Number of **Web Plates, Shifting Beams** and **Fore** and **Afters** to each Hatch Two web plates in No. 1, 2 & 3; 3 in No 4; 1 in No 3, and 3 fore and afters in all. **No. of Breasthooks** 8 **No. of Crutches** 4 & deep floors.

Bulwarks, height above deck and description 4 - 3 × 5/16 steel Main Rail, material and size 6 × 3 Bulb angle & Moulding combined

The above is a correct description. For WORKMAN, CLARK & CO., LIMITED. Secretary

Builder's Signature (if any) —

Surveyor's Signature James Turpin

Surveyor to Lloyd's Register of British and Foreign Shipping.

Form No. 1B.

Correspondence.—State dates and initials of letters respecting this case (*Reference should be made to any correspondence connected with this case*) M.

March 9th and 25th; April 4th and 18th; and Sept. 13th 1898.

Workmanship. Are the butts of plating planed or otherwise fitted? Planed where butted, but mostly overlapped.

Is the riveted work properly closed? Yes.

Are the liners between the frames and plates solid single pieces? Yes. Do the holes for riveting plate to frames, butt straps, or plate to plate, &c., conform well to each other? Yes. Are the rivet holes well and sufficiently countersunk in the plate and punched from the faying surfaces? Yes. Do any rivets break into or through the seams or butts of plating? very few.

Are the butts of Plating, Stringers, &c., properly shifted and strapped? Yes.

Have all the upper and weather decks been tested as required by the Rules (Sec. 23, par. 24)? Yes State results of tests Good

Have all the gutterways been tested as required by the Rules (Sec. 23, par. 25)? — State results of tests —

General Remarks (State quality of workmanship, &c.) This vessel has been built in accordance with the approved tracings of Midships and Longitudinal sections forwarded with the 1st Entry Report No 4976 on the S.S. Yangtze, a Sister vessel; the Secretary's letters dated as above, so far as they apply, have been complied with, and the Rules in other respects adhered to.

All pumps and watertight doors have been tested and found efficient, and the weather decks flooded with a hose and found tight and satisfactory.

The materials used in her construction and the workmanship are very good.

A duplicate tracing of Midship section was forwarded on the 19th instant.

The Surveyor should state the Number of Report and Name of any Sister Vessel.

PARTICULARS FOR RECORD in the REGISTER BOOK.—Length of Poop 36 ft., R.Q.D. or Break — ft., Bridge Dk. 145 ft., F'castle 45 ft. (in feet and tenths). When the Poop is joined to the B.D., this should be distinctly stated —

No. and Material of Decks (if Iron or Steel) and whether wholly or partially covered with wood, and No. of tiers of Beams (this information is to be given as it should appear in the Register Book) 2 Dks (Stl) 2 to 83.

Official No. ; Signal Letters

How are the surfaces preserved from oxidation? Inside Portland Cement & paint Outside paint.

PARTICULARS OF WATER BALLAST.—State whether the Double bottom is constructed on the cellular system or with girders on floors Cellular system.

Where fitted.	*Length. Feet.	Water Capacity. Tons.	Where fitted.	*Length. Feet.	Water Capacity. Tons.
Double bottom, aft,	134.25	455	Fore peak tank,		105
Double bottom, under Engines and Boilers,	52.5	265	After peak tank,		70
Double bottom, if under Engines only,	—		Midship deep tank,	30.4	460
Double bottom, if under Boilers only,	—		Other tanks, if fitted,	—	
Double bottom, forward,	171.16	645	(If necessary, furnish further information by sketch.)	—	

* The wells are not to be included in the lengths of the tanks.

State whether the above have been tested as required by the Rules Yes.

Order for Special Survey No. 426

Date Mar. 7 1899

No. 156 in builder's yard.

Dates of Surveys held while building: Mar. 23, May 16; June 1, 8, 13, 21, 24, 28; July 7, 18, 21, 27; Aug. 2, 12, 17, 22, 27; Sep. 2, 7, 26; Oct. 3, 7, 12, 17, 20, 24, 26, 28; Nov. 2, 4, 9, 11, 18, 23, 28; Dec. 6, 9, 13, 16, 19, 23; 1898. Jan. 4, 5, 6, 12, 19, 25; Feb. 8, 20, 23, 28; Mar. 3, 13, 14, 16, 23, 29, 30; April 7, 11, 13, 21, 27; May 2, 11, 15, 17, 29, 31; June 5, 7, 8, 12, 13, 15, 19, 20; 1899.

Total No. of Visits 44

The amount of Entry Fee £ 5 : 0 : 0

Special Survey Fee 100 : 13 : 0

Travelling Expenses, if any £ : :

Fees applied for, 21. 6. 1899

Received by me, 20. 6. 1899

Certificate to be sent to this Office

State whether the Vessel has been built under Special Survey Yes.

I am of opinion this Vessel should be Classed + 100 A1. 2 Dks (Stl) 2 to 83.

With, or without Freeboard, as condition of Class without.

James Turpin

Surveyor to Lloyd's Register of British and Foreign Shipping.

Committee's Minute TUES. 27 JUN 1899

Character assigned 100 A1 Steel

Laid + Launched 99

Water Bal.

The Surveyors are requested not to write on or below the Committee's Minute.

Hull Certificate Written

© 2019 Lloyd's Register Foundation