IRON OR STEEL STEAMER.

Received at London Office SAT. 8 SEP 1900

State if Report is also sent on the Machinery of the Vessel Yes. No. 5164

Date of completion of report September 7th 1900 Port of Belfast

Diver held at Belfast Date First Survey Jan.y 9th 1899 Last Survey Sept.r 6th 1900

the Steel Screw Steamer "Devonian" Rig Schooner, 4 masts

THREE DECKED VESSEL.

CLASS 100 A

Master G. W. Muir.

Year of appointment (1) As Master in service of owner of present vessel:—18 (2) As Master of this vessel 1900

Built at Belfast

When built 1900 Launched June 28. 1900

By whom built Harland & Wolff Ltd.

Owners Fred.k Leyland & Co. Ltd.

Managers — (Where necessary to be entered in Reg. Book.)

Residence Liverpool

Port belonging to Liverpool.

Destined Voyage Boston If Surveyed while Building, Afloat, or in Dry Dock while Building

	FEET.
Half Breadth (moulded)	29.5
Depth from upper part of Keel to top of Upper Deck Beams (with the normal round up of beam)	41.52
Girth of Half Midship Frame (as per Rule)	64.46
	135.47
deduct 7 feet	7.
	128.47
1st Number	550
Length on deck from after part of stem to fore part of stern post	706.58
2nd Number	9.3
Proportions—Breadth to Length	13.2
Depth to Length—Upper Deck to top of Keel	16.3
Main Deck ditto	

Decks.	
...te of completion of report	
...ver held at	Belfast
...the	Steel Screw Steamer
...NNAGE under ...nnage Deck...	7237.38
...between Tonnage Dk. ...nd 3rd and 4th Dk.	2151.64
...tal under Upper Dk	9389.02
...of Poop	26.92
...of Bridge House (Upper	431.64
...of Forecastle	134.72
...of Houses on Dk.	292.52
...of excess of Hatchways ...above Crown of ...Engine Room ..	140.03
...oss Tonnage	10417.87
...s Crew Space	219.04
...s above Crown of ...Engine Room ..	146.03
...NNAGE FOR FEES..	10058.79
...s Engine Room	3333.72
...Navigation Spaces	41.90
...gister Tonnage ...s cut on Beam ..	6823.20

	Feet.	Inches.		Feet.	Inches.
...NGTH on Deck ...s per Rule	550	0	BREADTH— Moulded	59	0

DEPTH, ACTUAL—Top of Floors to top of Upper Dk. Beams: Feet. 37 Inches. 0; Main Dk. Beams: Feet. 24 Inches. 0½

No. of Decks with flat laid 3

No. of Tiers of Beams 3

Round of Upper Dk. Beam, Actual 11½ ins.

...ensions of Ship per Register, Length 552.5 breadth 59.35 depth 28.95 / 26.85 Moulded depth, ft. 40 ins. 3½ To Upper Dk.

FRAMING.

	Inches in Ship	Inches in Ship.	16ths or 20ths in Ship.	Inches per Rule Or as	Inches per Rule as Appro	16ths or 20ths per Rule ved.
...AME, ~~Angles, or~~ ┐, ┌ ~~or L~~ Bars for ⅜ length amidships	8 - 3 13/20 × 3 13/20 × 11-13			8 - 3 13/20 × 3 13/20 × 11-13		
	4	3½	11	Channels 4	3½	11
Do. for ⅓ at each end	3½	3½	11	3½	3½	11
Do. in way of Double Bottoms at Solid Floors .. at intermdt. Bkts.	-			-		
,, ,,	30½			30½		
...tance of Frames from moulding edge to ...moulding edge, all fore and aft						
...VERSED FRAME, Angles .... ~~Deep Framing, depth of girder~~	at ends 4	4	10	4	4	10
	2 - ┌ Channels 3½ × 3½ × 11			3½	3½	11
...OORS, depth and thickness of Floor Plate at mid-line for ¾ length amidships						
,, in way of Engines and Boilers						
,, thickness at the ends of vessel						
,, depth at ¾ the half breadth, as per Rule ..						
,, height extended at the Bilges	1	Flgd	11	1	Flgd	11
...OORS & BRACKETS in Cell Dble Bottoms	30½			30½		
,, ,, Distance apart	1		15	51		15
...NTRE GIRDER, in Double bottom, depth and thickness						
,, ,, Angles, Top	4	4	13	4	4	13
,, ,, ,, Bottom	4½	4½	15	4½	4½	15
,, ,, ,,	Two	Flgd	11	Two	Flgd	11
...DE GIRDERS, number on each side & thickness	3½	3½	10	3½	3½	10
,, ,, Angles	42		12	40		12
...RGIN PLATE, depth (exclusive of flange) and thickness						
,, ,, Angles to Outside Plating	4	4	12	4	4	12
,, ,,	42		13	36		13
...NER BOTTOM PLATING, breadth and thickness of Middle Line Strake		12/20	& 5/8		12/20	& 5/8
,, ,, ,, in Engine and Boiler space						
,, ,, ,, Remainder in Holds			11			11
...AMS, Upper Deck, ~~Single Angle, Bulb Angle, Plate or Tee Bulb~~	8 - 3 13/20 × 3 13/20 × 11-13			8 - 3 13/20 × 3 13/20 × 11-13		
	Channels			Channels		
~~Angles on upper edge~~						
,, Average space	30½			30½		
...AMS, Middle Deck, ~~Single Angle, Bulb Angle, Plate or Tee Bulb~~	9 - 3 13/20 × 3 13/20 × 11-13			9 - 3 13/20 × 3 13/20 × 11-13		
	Channels			Channels		
~~Angles on upper edge~~						
,, Average space	30½			30½		
...AMS, Lower Deck, ~~Single Angle, Bulb Angle, Plate or Tee Bulb~~	9 - 3 13/20 × 3 13/20 × 11-13			9 - 3 13/20 × 3 13/20 × 11-13		
	Channels			Channels		
~~Angles on upper edge~~						
,, Average space	30½			30½		
...AMS, Hold, or Orlop, Plate or Tee Bulb ..						
,, Angles on upper edge						
,, Average space						
...AMS, Poop Deck, ~~Angle~~, Bulb Angle, ~~Plate or Tee Bulb~~	8	3½	10	8	3½	10
	Bulb angles			Bulb angles		
~~Angles on upper edge~~						
,, Average space	30½			30½		
...AMS, Bridge Deck, ~~Angle~~, Bulb Angle, ~~Plate or Tee Bulb~~	8	3½	10	8	3½	10
	Bulb angles			Bulb angles		
~~Angles on upper edge~~						
,, Average space	30½			30½		
...AMS, Forecastle Deck, ~~Angle~~, Bulb Angle, ~~Plate or Tee Bulb~~	8	3½	10	8	3½	10
	Bulb angles			Bulb angles		
Channels under middle line ~~Angles on upper edge~~	8 - 3 13/20 × 3 13/20 × 11-13			30½		
,, Average space	30½					
...LLARS, In 'tween Deck, size and spacing	4 & 3½		61	4 & 3½		61
,, ,, Hold ,, ,,	3¼		61	3¼		61
,, ,, Quarter 'tween Dks., ,, ,,	4 & 3½		122	4 & 3½		122
,, ,, in Hold ,, ,,	3¼		122	3¼		122
...EB-FRAMES, In Fore Body, No. and spacing	4 as pr. plan			4 as pr. plan		
,, ,, ,, brdth. & thickness	26		12	26		12
,, ,, No. of Side Stringers ,, ,,	2 × 26 × 16			2 × 26 × 16		
...EB-FRAMES, I. E. & P. Space, No. & spacing	4		122	4		122
,, ,, ,, brdth. & thickness	26		12	26		12
...EB-FRAMES, In After Body, No. and spacing	3 as pr. plan			3 as pr. plan		
,, ,, ,, brdth. & thickness	26		12	26		12
,, ,, No. of Side Stringers ,, ,,	2 × 26 × 16			2 × 26 × 16		
,, Size of Angles or Tee Bars to Web-Frames	4	4	12	4	4	12
...RACKET PLATES to Stringers between Web Frames, depth and thickness	30	24	11	30	24	11

FORGINGS or CASTINGS.

	Inches in Ship.	Inches per Rule. Or as Approved.
KEEL, Bar ~~or Side Plates~~, depth and thickness	10 × 3	10 × 3
STEM, moulding and thickness	12 × 3 7/8	12 × 3 7/8
STERN-POST for Rudder do. do.	13 × 10	13 × 10
,, for Propeller	13 × 10	13 × 10
MAIN PIECE of Rudder, diameter at head ..	12½	11½
,, ,, do. at heel	9¾ × 8.P 5¼	5¾

RUDDER, how constructed Cast steel frame, Single plate 22/20

Can the Rudder be unshipped afloat? yes

KEELSONS & STRINGERS.

	Inches in Ship.	Inches in Ship.	16ths or 20ths in Ship.	Inches per Rule Or a	Inches per Rule < Appro	16ths or 20ths per Rule ved.
CENTRE LINE KEELSON, Vertical Plate above floors, Through Plate, or Intercostal Plate						
,, Rider Plate						
,, Bulb Plate to Intercostal Keelson						
,, Horizontal Plates on Floors						
,, Angles						
SIDE KEELSON, Angles						
,, Bulb or Plate above floors, for lng.						
,, Intercostal Plate, for length						
,, Attached to outside Plating with Angle						
BILGE KEELSON, Angles						
,, Bulb or Plate above floors, for lng.						
,, Intercostal Plate for length						
,, Attached to outside Plating with Angle	3/ 6½	4½	12	3/ 6½	4½	12
BILGE STRINGER Angles	2/ 6½	4½	15	2/ 6½	4½	15
,, ~~Bulb Plate for length~~	26		16	26		16
,, Intercostal Plate for Entire length	4	4	13	4	4	13
,, Attached to outside Plating with Angle	3/ 6½	4½	12	3/ 6½	4½	12
SIDE STRINGER Angles	2/ 6½	4½	13	2/ 6½	4½	13
,, ~~Bulb or~~ Intercostal Plate, for Entire lng.	26		16	26		16
,, Attached to outside plating with Angle	4	4	13	4	4	13

Upper Deck Stringer Plates, br'dth & thickness	42		20	42		20
	42		18	42		18
,, Angle on ditto	L - Double			L - Double		
,, ~~Tie Plates fore and aft, outside Hatchways~~						
,, Deck.* ~~Iron or~~ Steel, for Entire lng.			10			10
,, Wood Deck. Material & thickness						
Middle Deck Stringer Plate, br'dth & thickness	42		14	42		14
	42		12	42		12
,, Angles on ditto, No. 2	4 × 4 ×		13	4 × 4 ×		13
,, ~~Tie Plates outside Hatchways~~				T		
,, Diagonal Tie Plates on Bms., No. of prs.						
,, Deck.* ~~Iron or~~ Steel, for Entire lng.			10			10
,, Wood Deck. Material & thickness 2						
Lower Deck Stringer Plate, br'dth & thickness	40		12	40		12
	40		11	40		11
,, Angles on ditto, No.	4 × 4 ×		13	4 × 4 ×		13
,, ~~Tie Plates, outside Hatchways~~						
,, Deck.* Material and thickness	Steel		7			7
Hold, or Orlop Stringer Plate, br'dth & thckn's						
,, Angles on ditto, No.						
,, Tie Plates outside Hatchways						
,, Deck. Material and thickness						
Poop Deck Stringer Plate, breadth & thickness	44½		8	44		8
,, Angle on ditto	3½ × 3½ ×		8	3½ × 3½ ×		8
,, Tie Plates	2 7½		8	2 4½		8
,, Deck. Material and thickness	Y.P.		3	3		
Bridge Deck Stringer Plate, br'dth & thickness	48		10	48		10
,, Angle on ditto	3½ × 3½ ×		10	3½ × 3½ ×		10
,, Tie Plates						
,, Deck. Material and thickness	Y.P.	3	Steel 7			7
Forecastle Deck Stringer Plate, b'dth & th'kns	46		9	46		9
,, Angle on ditto	3½ × 3½ ×		9	3½ × 3½ ×		9
,, Tie Plates	2 7½		8	2 7½		8
,, Deck. Material and thickness	Y.P.	3	Wd 1/3 Lgd 6/16	3		

* If Iron or Steel Deck, state if whole or part, and if Wood Deck is laid thereon.

BULKHEADS.

	Number. In Vessel.	Number. Per Rule.	Thickness.	STIFFENERS. Horizontal. Size.	Horizontal. Spacing	Vertical. Size.	Vertical. Spacing	Single or Double Frames.	Height up.
			16ths or 20ths.	Inches.	Inches.	Inches.	Inches.		
W. T. BULKHEADS	10	6	8 - 7 9/20 - 3 3/20	4 Bulb angles		7 - 3½ - 5/20	30	Double	9 & 11.9
PARTITION ,,									1½ I.B.
LONGITUDINAL ,,									

Are the outside Plates doubled two spaces of Frames in length? No diamond plates

Are the Sluice Valves and Watertight Doors in efficient working order? Yes

Lloyd's Register Foundation

PLATING.

STRAKES.	AS IN SHIP. AMIDSHIP. Breadth.	AMIDSHIP. Thickness.	FORWARD. Thickness.	APT. Thickness.	PER RULE OR AS APPROVED. AMIDSHIP. Breadth.	AMIDSHIP. Thickness.
	Inches.	~~inches.~~ 20ths	~~inches~~ or 20ths	~~inches~~ or 20ths	Inches.	~~inches~~ or 20ths
FLAT PLATE KEEL (If Bar Keel, state Riveting)	54	20	18	18	41	20
GARBOARD or A Strake	54	16	14	16	36	16
State actual thickness in way of Double Bottom. B "		15	14	16		15
C "		15	14	16		15
D "		15	13	15		15
E "		14	12	15		14
F "		13	12	13		13
G "		13	12	13		13
H "		16	12	15		16
J "		16	12	15		16
K "		16	12	15		16
L "		16	12	15		16
M "		16	12	15		16
N "		18	12	15		18
O "		19	12	12		19
Write 'Sheer Strake' opposite its corresponding letter. Sheer P "	41	24	13	13	41	21
Q "						
R "						
DOUBLING of Flat Plate Keel						
Length and thickness of Bilges	3	16ths	18			18
of Sheerstrakes	3	16ths	18			18
of Strake below	5	"				7
POOP SIDES				7		14-8
BRIDGE SIDES	15, 14, 12.10					7
FORECASTLE SIDES			7			

RIVETING.

EDGES.

Single or Double.	Breadth of Lap.	Rivets. Diam.	Rivets. Spacing cr. to cr.	
	Inches.	Inches.	Inches.	
Double	4	1 5/8	5 f	
"	6 3/4	1	4 4/4 f	
"	"	"	"	
"	"	"	"	
"	"	"	"