

# PARTICULARS for RECORD OF DOUBLE BOTTOMS, &c., in LLOYD'S REGISTER.

(Received at London Office, 8/7/87 188...)

No. of Report 4425

Port Dundee

Date 7<sup>th</sup> September 1881

No. in Register Book

On the S.S. "Waverley"

~~Double bottom, aft, length~~

~~and water capacity in tons~~

~~Double bottom, forward, length~~

~~and water capacity in tons~~

~~Double bottom, under engines and boilers, length~~

~~and water capacity in tons~~

~~If under Engines only, or Boilers only, state which~~

Double bottom, constructed on the cellular system, length

278 ft

and water capacity in tons

480

2 right divisions

Fore peak tank, water capacity in tons

44

~~After peak tank, water capacity in tons~~

~~Ship deep tank, length~~

~~and water capacity in tons~~

~~Other tanks, if fitted, length~~

~~and water capacity in tons~~

(If necessary, furnish further information by sketch.)

Geo. V. Cooper

Surveyor to Lloyd's Register of British and Foreign Shipping.

" Butts of 3 Strakes at Bilge for 2 length, treble riveted with Butt Straps 7/16 thicker than the plates they connect.

Edges from Bilge to Main Sheerstrake, worked clencher, double or single riveted; with rivets 7/8 in. diameter, averaging 3 1/2 ins from or to or