

Distance of Frames from moulding edge to
moulding edge, all fore and aft.

23

23

From up. prt of Bilge to lr. edge of Sh'rstrake...

164/5

164/5

PARTICULARS for RECORD OF DOUBLE BOTTOMS, &c., in LLOYD'S REGISTER.

(Received at London Office,

1885)

No. of Report 4050

Port Dundee

Date 10th October 1885

No. in Register Book

On the S.S. "Shieldrake"

Double bottom, aft, length 7.3 and water capacity in tons 10. Double bottom, forward, length 18.10 and water capacity in tons 174

Double bottom, under engines and boilers, length and water capacity in tons. If under Engines only, or Boilers only, state which

Double bottom, constructed on the cellular system, length 188 ft and water capacity in tons

only the parts detailed
above are to be used for
water ballast

Fore peak tank, water capacity in tons. After peak tank, water capacity in tons

Midship deep tank, length and water capacity in tons. Other tanks, if fitted, length and water capacity in tons

The above have *hmv* been tested as required by the Rules.

(If necessary, furnish further information by sketch.)

Surveyor to Lloyd's Register of British and Foreign Shipping.

(1000-4/11/84-Transfer ink.)

DUN110-0299

KEELSONS Centre line, *through* plate,

44 16

16

Stringer or Tie Plates, outside Hatchways
Flat of Lower Deck*

4x4x13 4x4x13

12 16 12 16