

Her Masts, Bowsprit, Yards, &c., are in 3986 condition, and sufficient in size and length. If they are of Iron or Steel give the Scantlings of Plating, Angle Irons, &c., and further explain by a Sketch showing how the lower Masts and Bowsprit are constructed, showing the number of Plates and Angle Irons, mode of rivetting, quality of Materials, and if stamped with Maker's name.

State also Length and Diameter of Lower Masts and Bowsprit

S.S. EGERON Equipment Compressed air Pump under the
Length inside of stem and stem post 170.5 - Deck breadth 12.6
Port 24.4
Number 8900
Depth - 15.2
1/10 added - 890 9790 for number.
52.2 x 170.5 = 8900
Number system 3

N ^o .	She has SAILS.	CABLES, &c.	Fathoms.	Inches.	Test as per Certificate.	In. req'd per Rule.	Test req'd per Rule.	ANCHORS, &c.	N ^o .	Weight. Ex. Stock.	Test as per Certificate.	W'ght req'd per Rule.	Test req'd per Rule.
	Fore Sails,	Chain	195	12/16	22 3/4	195	22 13/20	Bowers	3	10.0.5	12 3/20	10	12
	Fore Top Sails,	(State Machine where Tested, and name of Superintendent).	Breaking strain 34 2/20 ton.			12/16		(State Machine where Tested, and name of Superintendent).		9.2.25	11 15/20	10	12
	Fore Topmast Stay Sails,	Hemp or Stream Cable	90	12/16	—	90. 12/16	—	Stream S. & L.	1	9.0.16	11 5/20	8.2.0	10 13/20
	Main Sails,	Hawser	90	6 1/2	—	90. 6 1/2	—			4.3.0	—	4 3/4	—
	Main Top Sails,	Towlines								2.0.26	—	2 1/4	—
and		Warp						Kedges	2	1.0.5	—	1	—
		All of ___ quality											

Her standing and Running Rigging _____ sufficient in size and _____ in quality. She has _____ Long Boat and _____

GLS 145-0056

Gross Tonnage _____
 Crew Space, as per Rule _____
 Register Tonnage, cut on Beam _____
 Engine Room _____
 Register Tonnage, as a Steamer;
 cut on the Beam

Port belonging to North American Destined Voyage _____

If Surveyed while Building, Afloat, or in Dry Dock _____

Length aloft (Dimensions of Ship per Register, length)	Feet. Inches.	Extreme Breadth	Feet. Inches.	Depth from top of Upper Deck Beam to top of Floor	Feet. Inches.	Power of Engines	Horse.	N ^o . of Decks
				Inches in Ship.		Inches required by Rule.		
Keel, siding and moulding				Inches for	Inches required per Rule. tons Scale.	Outside Plank.		
„ plate, breadth and thickness						Garboard Strakes, thickness		
Stem, siding and moulding						Garboard to Topsides ditto		
Fore deadwood plate, breadth and thickness ..						Topsides ditto		
Stern-post, siding and moulding						Sheerstrakes ditto		
After deadwood plate, breadth and thickness ..						Planksheers ditto		
Distance of Frames from moulding edge to moulding edge, all fore and aft						Water-Upper Deck		
						Ways Lower Deck		
Frames, Size of Angle Iron, single or double ..	Inches. In Ship.	Inches. In Ship.	16ths. In Ship.	In. req'd per Rule for	In. req'd per Rule tons Scale.	Iron Sheerstrake, breadth and thickness		
„ „ Reversed Iron, if to every frame or every frame						„ Bilge Plate ditto ditto		
						Diagonal Plates on Frames		
						Gunwale Plate or Stringer on ends of Upper		

© 2019

Lloyd's Register
Foundation