

Awning or Shelter Deck, or Pt. Awning Deck.

STEEL STEAMER.

No. 16954

Port of Greenock Date of completion of Report 22nd Dec. 1915 Received at London Office THU. 30 DEC 1915
 Survey held at Port Glasgow & Glasgow Date, First Survey, 5th November 1913 Last Survey 19th December 1915
 On the 5th twin screw (geared turbine) steamer "CUMBERLAND" Rig 4 Mast. Fore & aft Schooner
 TONNAGE under Tonnage Deck 3317.91 CLASS 100A1 Shelter deck with fore and aft Master A. S. McGibbon
 Do. between Tonnage Dk. and 3rd, 4th, or Aft Deck 14.09 Breadth (greatest moulded) 59.75 Year of Appointment 1894
 Total under Upper Dk. 67.79 Depth at middle of length from top of keel to top of uppermost Continuous Deck 31.45 Built at Port Glasgow
 Do. of Poop 46.545 Deduct height of 'tween deck when this does not exceed 8ft. 91.20 When built 1915 Launched 1st March 1915
 Do. of Bridge House 117.27 Transverse Number 473 By whom built Wm. Hamilton & Co. Ltd.
 Do. of Houses on Deck 43.34 Length on deck from fore part of stem to after part of sternpost 431.34 Owners Federal Steam Navigation Co. Ltd.
 Do. above Crown of Engine Room 43.34 Longitudinal Number 431.34

COPY.

Lloyd's Register of Shipping,

71, Fenchurch Street, E.C.

2 Enclosures.

2nd December 1915.

Dear Sirs,

I send herewith for your information a copy of a letter received from the Owners of the new steamer "CUMBERLAND", Messrs. W. Hamilton & Co's No. 298 vessel, together with a copy of my reply thereto, respecting their proposal to dispense with cargo battens in the upper tween decks of this vessel.

I am, Dear Sirs,

Yours faithfully,

Assistant to the Secretary.

The Surveyors,
GREENOCK.

Book.)			
ndow.			
ndow			
Dry Dock Yes			
No. of Decks with flat laid	3		
No. of Tiers of Beams	3		
Round up of Uppermost Dk. Beam, Actual ..	15 in		
Inches. in Ship.	Inches. Spacing in Ship.	Inches. per Rule. Or as Approved.	Inches. per Rule. Or as Approved.
Side spaced pillars and girders fitted in accordance with approved plans.			
Inches in Ship.	Inches in Ship.	Inches per Rule.	Inches per Rule.

4	50	7	3 1/2	52
7	44			46
4	48	4	4	46
6 1/2	62	6 1/2		62
5	64	5 x 5		64
	40			40
	46			
2 1/2	5 x 2 1/2			
5 1/2	50	49		50
4 x 4	50	4 x 4		50
	40			40
52	44	49		44
4 x 4	50	4 x 4		50
	30			30

GLS184-0014

GLS184-0013

Spacing	27 1/2		27 1/2	
BEAMS, Poop Deck, Angle, Bulb Angle, Plate, Tee Bulb or Channel				
Angles on upper edge				
Spacing	8 1/2	3	46	8 1/2 3 46
BEAMS, Bridge Deck, Angle, Bulb Angle, Plate, Tee Bulb or Channel				
Angles on upper edge				
Spacing	27 1/2		27 1/2	
BEAMS, Forecastle Deck, Angle, Bulb Angle, Plate, Tee Bulb or Channel				
Angles on upper edge	7 1/2	3	42	7 1/2 3 42
Spacing	27 1/2		27 1/2	

Angles on ditto				
Tie Plates				
Deck. Material and thickness				
Bridge Deck Stringer Plate, br'dth & thickness	6 1/2	54	60	54
Angle on ditto	5 x 5	64	5 x 5	64
Tie Plates	Steel 8"	42		42
Deck. Material and thickness	P.Pine	5 x 2 1/2	5 x 2 1/2	
Forecastle Deck Stringer Plate, br'dth & thickness	46	36	38	36
Angle on ditto	3 1/2 x 3 1/2	36	3 1/2 x 3 1/2	36
Tie Plates	Steel deck	30	3 1/2	36
Deck. Material and thickness	P.Pine	5 x 3	5 x 3	