Main Deck ditto

BREADTH— Moulded... 10

Power of Engines 35

Dimensions of Ship per Register, length, 95

Iron

do.

do.

moulding edge to

and aft

length amidships

Angle Iron

thickness of Floor Plate

amidships

per Rule

Awning Deck

Upper edge

Mess Neilson & Maxwell 88 Cadogan St

28th Jany 86

THE STEEL COMPANY OF SCOTLAND, LTD
HALLSIDE WORKS

PARTICULARS for RECORD OF DOUBLE BOTTOMS, &c., in LLOYD'S REGIS

Received at London Office

Port Greenock

35368	8	Rounds	1⅛ diar	3 1 21
	1		1¼	2 7
	17	9. 5	1¾	12 2 7
	2	6. 8	1⅜	2 2 .
	4	6. 0½	2¼	1 1 21
	2			1 . 2 .
	34		R 5/11	

Test Nos 50. 41. 48. 45. 52. 49. 51. 50. 53. 49. 51. 168. 167. 166. 60. 61. 47

been tested as required by the Rules

further information by sketch.)

Carr paid to J & T Mc Gregor

Angle Irons

length from middle line

ANGLE IRONS on floors and frames extend

the various lengths of Plates and Angle Irons

double riveted to Keel, with rivets

and to upper part of Bilge

Keel to turn of Bilge, worked carvel

Bilge to Main Sheerstrake, worked

Bilge to Main Sheerstrake, worked carvel

or single riveted

Breadth of laps of plating in double riveting

Breadth of laps of plating in single riveting 2¼

No. of Breasthooks, 3

Crutch

Upper or Spar Stringer Plate, treble riveted for

© 2019 Lloyd's Register Foundation