

# PARTICULARS for RECORD OF DOUBLE BOTTOMS, &c., in LLOYD'S REGISTER.

(Received at London Office, 1886)

No. of Report 9113 Port Greenock Date 5<sup>th</sup> May 1886  
 No. in Register Book \_\_\_\_\_ On the Steel S.S. "Isabella"

Double bottom, aft, length ✓ and water capacity in tons ✓. Double bottom, forward, length ✓ and water capacity in tons ✓.

Double bottom, under engines and boilers, length ✓ and water capacity in tons ✓. If under Engines only, or Boilers only, state which ✓.

Double bottom, constructed on the cellular system, length ✓ and water capacity in tons ✓.

Fore peak tank, water capacity in tons 14. After peak tank, water capacity in tons ✓.

Ship deep tank, length ✓ and water capacity in tons ✓. Other tanks, if fitted, length ✓ and water capacity in tons ✓.

The above have ✓ been tested as required by the Rules.

(If necessary, furnish further information by sketch.)

Surveyor to Lloyd's Register of British and Foreign Shipping.

100-4/11/84-Transfer ink.)

CE STRINGER Angle Irons

How secured to sides of ship As shown on both angles  
 Size of Vertical Angle Irons 2 1/2 x 7 1/2 and distance apart 30 ins.