

PARTICULARS for RECORD OF DOUBLE BOTTOMS, &c., in LLOYD'S REGISTER.

(Received at London Office, 1886.)

of Report 9223

Port Greenock

Date 20th Nov: 1886

in Register Book

On the

S.S. Australand

Double bottom, aft, length \_\_\_\_\_ and water capacity in tons \_\_\_\_\_. Double bottom, forward, length \_\_\_\_\_ and water capacity in tons \_\_\_\_\_

Double bottom, under engines and boilers, length 19 ft and water capacity in tons 42 If under Engines only, or Boilers only, state which Engines

Double bottom, constructed on the cellular system, length \_\_\_\_\_ and water capacity in tons \_\_\_\_\_

Peak tank, water capacity in tons 24. After peak tank, water capacity in tons 20.

Hip deep tank, length \_\_\_\_\_ and water capacity in tons \_\_\_\_\_. Other tanks, if fitted, length \_\_\_\_\_ and water capacity in tons \_\_\_\_\_

The above have \_\_\_\_\_ been tested as required by the Rules.

(If necessary, furnish further information by sketch.)

Surveyor to Lloyd's Register of British and Foreign Shipping.

(See & Son - 1000 - 4/12/85 - Transfer ink.)

GRK 306 - 0170