

Awning Dk.

IRON OR STEEL STEAMER.

No. 11329

State of Report is also sent on the Machinery of the Vessel.

Date of completion of Report 11th October  
Glasgow & Gls. Date, First Survey Dec. 11th 1894  
On the "Langbank"

Received at London Office MON. 14 OCT 1895

Last Survey 7th October, 1895  
Rig Schooner

NAME of Vessel  
Tonnage  
Gross Tonnage  
Net Tonnage  
Crew Space  
Tonnage for Fees  
Engine Room  
Navigation Spaces  
Master Tonnage

SPAR, ~~AWNING OR PART AWNING-DECKED VESSEL,~~  
or a Vessel having a continuous Shade Deck.

CLASS 100A1.

FEET.

Half Breadth (moulded) 23.54  
Depth from upper part of keel to top of Main Deck Beams 25.39  
Girth of Half Midship Frame (as per Rule) 45.25  
1st Number 94.18  
Length 380.16  
2nd Number 35803  
Proportions—Breadths to Length 8.04  
Depths to Length—Main Deck to top of Keel 14.94

Master William J. Roul

Year of Appointment

Built at Port Glasgow

When built 1895 Launched 23rd August

By whom built Russell & Co.

Owners

Managers

Residence 23, Old Hall St. Liverpool

Port belonging to Liverpool

Destined Voyage Colombia Barry. If Surveyed while Building, Afloat, or in Dry Dock Building Afloat and in Dry Dock.

LENGTH on Deck as per Rule 380 2  
BREADTH Moulded 47 1  
DEPTH, top of Floors to Spar or Awn. Dk. Beams 28 85  
Do. do. Main Deck Beams 21 85  
Power of Engines 329  
No. of Decks with flat laid 2  
No. of Tiers of Beams 2

Dimensions of Ship per Register, Length 382'2 breadth 47'1 depth 28'85 Spar or Awn. Dk. Moulded depth, ft. 24 ins. 5 To Main Dk. Round up of Beam, Main Dk. 11 3/4 ins.

FRAMING.				FORGINGS AND CASTINGS.			
	Inches in Ship	Inches in Ship	20ths in Ship		Inches in Ship	Inches per Rule Or as Approved	
ME, Angles, or Bars, for length amidships	5 1/2	3 1/2	9	KEEL, Bar or Side Plates, depth and thickness	11 x 3	11 x 3	
Do. for 1/2 at each end	5 1/2	3 1/2	8	STEM, moulding and thickness	11 x 4	11 x 4	
Do. in way of Double Bottoms at Solid Floors	3 1/2	3 1/2	9	STERN-POST for Rudder do. do.	11 x 4	11 x 4	
" " at intermdt. Plats.				" " for Propeller	11 x 4	11 x 4	
Distance of Frames from moulding edge to moulding edge, all fore and aft	24		24	MAIN PIECE of Rudder, diameter at head	9 1/2	9 1/2	
EVERSED FRAME, Angles	6 1/2	3 1/2	9	do. at heel	8 1/4 x 5 1/4	8 1/4 x 5 1/4	
DEEP FRAMING, depth of girder	9		9	RUDDER, how constructed	Solid cast steel frame single plate		
FLOORS, depth and thickness of Floor Plate at mid line for 1/2 length amidships				Can the Rudder be unshipped afloat?	Yes.		
" " in way of Engines and Boilers				KEELSONS AND STRINGERS.			
" " thickness at the ends of vessel				CENTRE LINE KEELSON, Vertical Plate above floor, Through Plate, or Intercoastal Plate			
" " depth at 1/2 the half bth. as per Rule				" Rides Plate			
" " height extended at the Bilges	40		40	" Bulb Plate to Intercoastal Keelson			
FLOORS & BRACKETS, in Cell Dble Bottoms	44 1/4	8	44 1/4	" Horizontal Plates on Floors			
" " Distance apart	24		24	" Angles			
CENTRE GIRDER, in Double bottom, depth and thickness	44 1/4	10	44 1/4	SIDE KEELSON, Angles			
" " Angles, Top	4	4	9	" Bulb or Plate above floors, for length			
" " Bottom	6 1/2	4 1/2	10	" Intercoastal Plate, for length			
DE GIRDERS, number and thickness	3 1/2	3 1/2	8	" Attached to outside plating with Angle			
MARGIN PLATE, depth (exclusive of flange) and thickness	36	9	36	BILGE KEELSON, Angles			
" " Angles	4	4	9	" Bulb or Plate above floors, for length			
VER BOTTOM PLATING, breadth and thickness of Middle Line Strake	60	10	60	" Intercoastal Plate, for length			
" " thickness in Engine and Boiler space		10	10	" Attached to outside plating with Angle			
BEAMS, Spar or Awning Deck, Single Angle, Bulb Angle, Plate or Tee Bulb	9 1/2	9	9 1/2	BILGE STRINGER Angles			
" " Angles on upper edge	3 1/2	3 1/2	4	" Bulb Plate, for length	9	3 1/2	11
" " Average space	48		48	" Intercoastal Plate, for whole length	3 1/2	3 1/2	9
BEAMS, Main Deck, Single Angle, Bulb Angle, Plate or Tee Bulb	9	3	12	" Attached to outside plating with Angle			
" " Angles on upper edge				SIDE STRINGER Angles			
" " Average space	24		24	" Bulb or Intercoastal Plate, for length			
AMS, Lower Deck, Single Angle, Bulb Angle, Plate or Tee Bulb				" Attached to outside plating with Angle			
" " Angles on upper edge				Spar, or Awning Deck Stringer Plates, breadth and thickness	56	12	56
" " Average space				" Angle on ditto	4 x 4	9	4 x 4
AMS, Hold, or Orlop, Plate or Tee Bulb				" Tie Plates, fore and aft, outside Hatchways			
" " Angles on upper edge				" Diagonal Tie Plates, No. of p's			
" " Average space				" Deck, Iron or Steel, for whole length			
AMS, Poop Deck, Angle, Bulb Angle, Plate or Tee Bulb	8	3	12	" Wood Deck, Material and thickness			
" " Angles on upper edge				Main Deck Stringer Plate, breadth & thickness	58	10	58
" " Average space				" Angles on ditto, No. 2	4 x 4	9	4 x 4
AMS, Bridge Deck, Angle, Bulb Angle, Plate or Tee Bulb	8	3	12	" Tie Plates, outside Hatchways			
" " Angles on upper edge				" Diagonal Tie Plates, No. of p's			
" " Average space				" Deck, Iron or Steel, for whole length			
AMS, Forecastle Deck, Angle, Bulb Angle, Plate or Tee Bulb	4 1/2	3	8	" Wood Deck, Material and thickness			
" " Angles on upper edge	3	3	4	Lower Deck Stringer Plates, br'dth & thckn's	34	11	34
" " Average space	24		24	" Angles on ditto, No. 2	4 x 4	9	4 x 4
LLARS, In Fore Deck, size and spacing	2 1/2	48	2 1/2	" Tie Plates, outside Hatchways			
" " Hold	4 1/2	48	4 1/2	" Diagonal Tie Plates, No. of p's			
" " Quarter, 'tween Dks., "	2 1/2	96	2 1/2	" Deck, Iron or Steel, for whole length			
" " in Hold	4 1/2	96	4 1/2	" Wood Deck, Material and thickness			
WEB FRAMES, In Fore Body, No. and spacing				Upper Deck Stringer Plates, br'dth & thckn's	34	11	34
" " br'dth & thickness				" Angles on ditto, No. 2	4 x 4	9	4 x 4
" " No. of Side Stringers				" Tie Plates, outside Hatchways			
WEB FRAMES, In E. & B. Space, No. & spacing				" Diagonal Tie Plates, No. of p's			
" " br'dth & thickness				" Deck, Iron or Steel, for whole length			
WEB FRAMES, In After Body, No. and spacing				" Wood Deck, Material and thickness			
" " br'dth & thickness				Bridge Deck Stringer Plate, br'dth & thickness	40	8	40
" " No. of Side Stringers				" Angles on ditto	3 x 3	8	3 x 3
" " Size of Angles or Tee Bars to Web Frames				" Tie Plates	12	4	12
BRACKET PLATES to Stringers between Web Frames, depth and thickness				" Deck, Material and thickness	3	3	3



[illegible]