



# CERTIFICATE FOR STEEL WIRE RIGGING.

We hereby Certify that the 288 fathoms of  
 $2\frac{1}{4}$  inch circumference galvanized Steel Wire Rigging  
 applied to Messrs. Russell & Co.  
 of the Ship "Fairport" is  
 composed of 5 strands, each containing 7 wires of .086 inch  
 diameter, and that the several wires, after being galvanized, have  
 been subjected to, and have successfully withstood, the following  
 tests, viz.:

Each wire has withstood a tensile stress at least equivalent to that  
 set forth in Table No. 11 of the Rules of Lloyd's Register  
 of Shipping, and the aggregate strength of the wires is not less  
 than 10 per cent. in excess of that stress.

Each wire has been twisted eight times round itself as a core, and  
 untwisted again and straightened without fracture.

No hemp has been used in the strands, a hemp core only being fitted.

We guarantee that the Steel Wire Rigging of  
 $2\frac{1}{4}$  inches in circumference above described will bear a strain  
 of 9 tons without breaking.

Liverpool.

THE WARRINGTON WIRE ROPE WORKS

Clifford Temple

Manufacturer

20<sup>th</sup> April 1896.

Lloyd's Register  
 Foundation  
 1821  
 Wm 333-0210