


Gen Report No 1288 S. S. Alberta

CERTIFICATE FOR STEEL WIRE RIGGING.



We hereby Certify that the _____ fathoms of
 $3\frac{1}{4}$ inch circumference galvanized Steel Wire Rigging
 supplied to Messrs. Russell & Co. for Glasgow
 for the Ship No 468. is
 composed of six strands, each containing seven wires of .115 inch
 diameter, and that the several wires, after being galvanized, have
 been subjected to, and have successfully withstood, the following
 tests, viz.:

Each wire has withstood a tensile stress at least equivalent to that
 set forth in Table No. 11 of the Rules of Lloyd's Register
 of Shipping, and the aggregate strength of the wires is not less
 than 10 per cent. in excess of that stress.

Each wire has been twisted eight times round itself as a core, and
 untwisted again and straightened without fracture.

No hemp has been used in the strands, a hemp core only being fitted.

We guarantee that the Steel Wire Rigging of
 $3\frac{1}{4}$ inches in circumference above described will bear a strain
 of Twelve tons without breaking.

WARRINGTON

THE WHITECROSS CO LIMITED

Manufacturer.

Nov. 9th 1900

© 2019

Lloyd's Register
Foundation

GRK354-0077

89468

Wine Reggung



© 2019

Lloyd's Register
Foundation.