3 Decks.

~~IRON OR~~ STEEL STEAMER.

State if Report is also sent on the Machinery of the Vessel Yes

Received at London Office FRI. MAY 25 1900

Date of completion of report 22nd Mar 1900. Port of WEST HARTLEPOOL No. 111833.

Survey held at W. Hpl. Date, First Survey 22nd August 1899 Last Survey 15th May, 1900

on the Steel S.S. "MARBURG" Rig Schooner

THREE DECKED VESSEL.

CLASS +100A1 Steel

		FEET.
Half Breadth (moulded)	Well deck	25.86
Depth from upper part of Keel to top of Upper Deck Beams (with the normal round up of beam)		33.20
Girth of Half Midship Frame (as per Rule)		54.33
		113.38
	deduct 7 feet	7.0
1st Number		106.38
Length on deck from after part of stem to fore part of stern post		398.1
2nd Number		42360
Proportions—Breadth to Length		7.69
Depth to Length—Upper Deck to top of Keel		11.99
~~Main Deck~~ ditto		

Destined Voyage Bremen.

Master F. Ton Binzer

Year of appointment (1) As Master in service of owner of present vessel:—18 (2) As Master of this vessel 1900

Built at West Hartlepool.

When built 1899-1900 Launched 31st Jan 1900.

By whom built Furness Withy & Co Ltd

Owners Norddeutscher Lloyd.

Managers (Where necessary to be entered in Reg. Book.)

Residence Bremen.

Port belonging to Bremen.

LENGTH, on Deck as per Rule	Feet. 398	Inches. 1	**BREADTH**— Moulded	Feet. 51	Inches. 9	**DEPTH, ACTUAL**—Top of Floors to top of Upper Dk. Beams / Do. do. do. do. Main Dk. Beams	Feet. 29 / Inches. 4½

No. of Decks with flat laid 2. No. of Tiers of Beams 3.

Dimensions of Ship per Register, Length 400.4 breadth 52.0 depth 29.2 Moulded depth, ft. 32 ins. 1½ To Upper Dk. Round of Upper Dk. Beam, Actual -13. ins.

FRAMING.

	Inches in Ship	Inches in Ship.	16ths or 20ths in Ship.	Inches per Rule Or as	Inches per Rule As Appro	16ths or 20ths per Rule ved.
~~FRAME~~, ~~Angles or L, T or~~ [Bars for ⅜ length amidships	7½	3½	14/15	7½	3½	14/15
Do. for ¼ at each end	7½	3½	12	7½	3½	12.
Do. in way of Double Bottoms at Solid Floors	Floors flanged.					
,, ,, ~~Intermds. Plts~~						
Distance of Frames from moulding edge to moulding edge, all fore and aft	-	25	-	-	25	-
REVERSED FRAME, Angles	Bulb angle frames					
~~BRD FRAMES~~, depth of girder						
~~FLOORS~~, depth and thickness of Floor Plate at mid line for ⅜ length amidships						
,, in way of Engines and Boilers						
,, thickness at the ends of vessel						
,, depth at ¼ the half breadth, as per Rule						
,, height extended at the Bilges						
~~DOORS & BRACKETS~~ in **Cell Dble Bottoms**	46 - 11.10.9			46 - 11.10.9		
,, Distance apart	-	25	-	-	25	-
~~CENTRE~~ GIRDER, in Double bottom, depth and thickness	46 -	12		46 -	12.	
,, ,, Angles, Top	4	4	10	4	4	10
,, ,, ,, Bottom	6½	4½	11	6½	4½	11.
~~SIDE~~ GIRDERS, number on each side & thickness	Two on side.					
,, Angles	3½	3½	9	3½	3½	9.
~~GIRDER~~ PLATE, depth (exclusive of flange) and thickness	35	-	10	35	-	10.
,, Angles to Outside Plating	4	4	10	4	4	10
~~CENTRE~~ BOTTOM PLATING, breadth and thickness of **Middle Line Strake**	60	-	10	60	-	10
,, ,, in Engine and Boiler space	E.R.		3/4	-	-	3/16
,, ,, Remainder in Holds	B.R.		7/16	-	-	7/16
	-	-	8	-	-	8.
~~BEAMS~~, Upper Deck, ~~Single Angle~~, Bulb Angle, ~~Plate or Tee Bulb~~	9	3	12	9	3	12
~~Angles on upper edge~~	-	-	-	-	-	-
Average space	-	25	-	-	25	-
~~BEAMS~~, Middle Deck, ~~Single Angle~~, Bulb Angle, ~~Plate or Tee Bulb~~	9	3	13	9	3	13
~~Angles on upper edge~~	-	-	-	-	-	-
Average space	-	25	-	-	25	-
~~BEAMS~~, Lower Deck, ~~Single Angle, Bulb Angle, Plate or~~ Tee Bulb	12	6	11	12	6	11
~~Angles on upper edge~~	-	-	-	-	-	-
Average space	-	50	-	-	50	-
~~BEAMS, Hold, or Orlop,~~ ~~Plate or Tee Bulb~~	-	-	-	-	-	-
~~Angles on upper edge~~	-	-	-	-	-	-
~~Average space~~	-	-	-	-	-	-
BEAMS, Poop Deck, ~~Angle~~, Bulb Angle, ~~Plate or Tee Bulb~~	7	3	9	7	3	9
~~Angles on upper edge~~	-	-	-	-	-	-
Average space	-	25	-	-	25	-
BEAMS, Bridge Deck, ~~Angle~~, Bulb Angle, ~~Plate or Tee Bulb~~	7	3	9	7	3	9
~~Angles on upper edge~~	-	-	-	-	-	-
Average space	-	25	-	-	25	-
BEAMS, Forecastle Deck, ~~Angle~~, Bulb Angle, ~~Plate or Tee Bulb~~	7	3	9	7	3	9
~~Angles on upper edge~~	-	-	-	-	-	-
Average space	-	25	-	-	25	-
PILLARS, In 'tween Deck, size and spacing	3½3½	-	50	3½3½	-	50
,, Hold ,, ,,	4	-	50	4	-	50
Quarter 'tween Dks., ,, ,,	3½3½	-	100	3½3½	-	100
,, in Hold ,, ,,	4	-	100	4	-	100
~~HALF-FRAMES, In Fore Body,~~ ~~No. and spacing~~	-	-	-	-	-	-
,, ,, ~~brdth. & thickness~~	-	-	-	-	-	-
~~No. of Side Stringers~~ ,, ,,	-	-	-	-	-	-
HALF-FRAMES, In E. & B. Space, No. & spacing	5 each side.					
,, ,, brdth. & thickness	12	-	8	12	-	8
~~HALF-FRAMES, In After Body,~~ ~~No. and spacing~~	-	-	-	-	-	-
,, ,, ~~brdth. & thickness~~	-	-	-	-	-	-
~~No. of Side Stringers~~ ,, ,,	-	-	-	-	-	-
Size of Angles ~~or Tee Bars~~ to **Web-Frames**	4½	3½	10	4½	3½	10
~~BRACKET PLATES to Stringers between Frames~~, depth and thickness	-	-	-	-	-	-

FORGINGS or CASTINGS.

	Inches in Ship.	Inches per Rule. Or as Approved.
~~KEEL, Bar or Side Plates~~, depth and thickness		
STEM, moulding and thickness	11½ 3⅛	11½ 3⅛
STERN-POST for Rudder do. do.	11½ + 7½	11½ + 7½
,, for Propeller	11½ + 7½	11½ + 7½
MAIN PIECE of **Rudder,** diameter at head	10	10
,, ,, do. at heel	~~Pintles~~ 5	5

RUDDER, how constructed Cast Steel frame - plated

Can the Rudder be unshipped afloat? Yes

KEELSONS & STRINGERS.

	Inches in Ship.	Inches in Ship.	16ths or 20ths in Ship.	Inches per Rule Or as	Inches per Rule As Appro	16ths or 20ths per Rule ved.
~~CENTRE LINE KEELSON,~~ Vertical Plate above ~~floors, Through Plate, or Intercostal Plate~~						
,, ~~Rider Plate~~						
,, ~~Bulb Plate to Intercostal Keelson~~						
,, ~~Horizontal Plates on Floors~~	Cellular					
,, ~~Angles~~						
~~SIDE KEELSON,~~ ~~Angles~~	double					
,, ~~Bulb or Plate above floors, for lng.~~						
,, ~~Intercostal Plate, for length~~	bottom					
,, ~~Attached to outside Plating with Angle~~						
~~BILGE KEELSON,~~ ~~Angles~~						
,, ~~Bulb or Plate above floors, for lng.~~						
,, ~~Intercostal Plate for length~~						
,, ~~Attached to outside Plating with Angle~~						
BILGE STRINGER Angles ~~Bulb~~	9	3	11	9	3	11
,, ~~Bulb Plate for length~~	-	-	-	-	-	-
,, Intercostal Plate for whole length	-	16½	10	-	16½	10
,, Attached to outside Plating with Angle	3½	3½	10	3½	3½	10
SIDE STRINGER Angles ~~bulb~~	9	3	11	9	3	11
,, ~~Bulb or~~ Intercostal Plate, for whole lng.	-	16½	10	-	16½	10
,, Attached to outside plating with Angle	3½	3½	10	3½	3½	10

Upper Deck Stringer Plates, br'dth & thickness	62	13	62	13	
,, Angle on ditto ~~dbl. in. creases~~	4½×4×9		4½×4×9		
,, Tie Plates fore and aft, outside Hatchways	increased 2/20				
,, Deck.* ~~Iron or~~ Steel, for whole lng.	8.7½		-	8.7½	
,, ~~Wood Deck, Material & thickness~~	~~Y.P.~~				
Middle Deck Stringer Plate, br'dth & thickness	62	11	62	11	
,, Angles on ditto, No. ~~double~~	4×4×9		4×4×9		
,, ~~Tie~~ Plates outside Hatchways	increased 2/20				
,, ~~Diagonal Tie Plates on Bms., No. of pcs.~~	-	-	-	-	
,, Deck.* ~~Iron or~~ Steel, for whole lng.	-	8.7½	-	8.7½	
,, ~~Wood Deck. Material & thickness~~	-	-	-	-	
Lower Deck Stringer Plate, br'dth & thickness	54	10½	54	10.	
,, Angles on ditto, No. double	4×4×9		4×4×9		
,, ~~Tie Plates, outside Hatchways~~					
,, ~~Deck.* Material and thickness~~					
~~Hold, or Orlop Stringer Plate,~~ br'dth & thckn's					
,, ~~Angles on ditto, No.~~					
,, ~~Tie Plates outside Hatchways~~					
,, ~~Deck. Material and thickness~~					
Poop Deck Stringer Plate, breadth & thickness	Poop & Bridge				
,, Angle on ditto	combined forming				
,, ~~Tie Plates~~	long Poop.				
,, Deck. Material and thickness ~~Iron or Steel~~					
Bridge Deck Stringer Plate, br'dth & thickness	60		60		
,, Angle on ditto	3½×3½×7/8		3½×3½×7/8		
,, ~~Tie~~ Plates ~~iron deck~~	-	5/16	-	5/16	
,, Deck. Material and thickness Sheathed Y.P.	-	3"	-	3"	
Forecastle Deck Stringer Plate, b'dth & th'kns	Iron	5/16	-	5/16	
,, Angle on ditto	3½×3½×7/8		3½×3½×7/8		
,, ~~Tie~~ Plates ~~iron deck~~	iron	5/16	-	5/16	
,, Deck. Material and thickness	Y.P.	3"			

* If Iron or Steel Deck, state if whole or part, and if Wood Deck is laid thereon.

BULKHEADS.

	Number. In Vessel.	Number. Per Rule.	Thickness.	STIFFENERS. Horizontal. Size.	Horizontal. Spacing	Vertical Size.	Vertical Spacing	Single or Double Frames.	Height up.
			16ths or 20ths.	Inches.	Inches.	Inches.	Inches.		
W. T. BULKHEADS	6	6	8.7½	7½×3×½	48	dbl	web		
PARTITION ,,	1	-	-	-	-	-	-		
LONGITUDINAL ,,									

Are the outside Plates doubled two spaces of Frames in length? Diamond Lap

Are the Sliding Watertight Doors in efficient working order? Yes

HM 388-0268 (112)

© 2020 Lloyd's Register Foundation

FRI. MAY 25 1900

PLATING.

STRAKES.	AS IN SHIP. Amidship. Breadth. Inches.	Amidship. Thickness. Millms. 20ths	Forward. Thickness. Millms. 20ths	Aft. Thickness. Millms. 20ths	PER RULE OR AS APPROVED. Amidship. Breadth. Inches.	Amidship. Thickness. Millms. 20ths
Flat Plate Keel (If Bar Keel, state Breadth)						
Gairboard or A Strake	48	20	14	14	48	20.
Garboard B "	51	15	13	13	51	15
C "		12	10	10	—	12
D "		12	10	10	—	12
E "		12	10	10	—	12
F "		13	10	10	—	13
G "		13	10	10	—	13
H "		13	10	10	—	13
J "		13	10	10	—	13
K "		13	10	10	—	13
L "		13	10	10	—	13
M "		13	10	10	—	13
N "		13	10	10	—	13
O "		13	10	10	—	15
P "		15	10	10	—	15
Sheer Q "	44	16	11	11	44	16
R "						

Write 'Sheer Strake' opposite its corresponding letter.

State actual thickness in way of Double Bottom.

Doubling of Flat Plate Keel: F.K. gart.ds & centre keelson increased in thickness.

Length and thickness: of Bilges — Doubled at Poop ends. of Sheerstrakes. increased abt Rule thickness. of Strake below

Poop Sides: — — — 7 — 8x7

Bridge Sides: — 8x7 — — — —

Forecastle Sides: — — 7 — — —

Stringers in Rule thickness

RIVETING.

EDGES.

Single or Double.	Breadth Lap. Inches.	Rivets Diameter. Inches.	Rivets Pitch. Inches.
double	6	1	4 1/2
—	—	—	—
—	—	—	—
—	5 1/4	7/8	3 1/2
—	—	—	—
—	—	—	—
—	—	—	—
—	—	—	—
—	—	—	—
—	—	—	—
—	—	—	—
—	—	—	—
—	—	—	—
—	—	—	—
—	6	1	4 1/8
—	—	—	—
—	—	—	—

BUTTS.

Double or Treble Riveted Butt. Length.	Rivets Diam. Inches.	Rivets Spacing (or, if Zigzag, Pitch of Outer Rivets). Inches.	Straps Breadth. Inches.	Straps Thickness. 16ths.	If Lapped Breadth. Inches.	If Lapped For what Length. Feet.
treble	1	3 1/2	19	14 & 13	(Double & Strake	
—	—	—	—	—	10 1/2	whole
—	7/8	3 1/16	—	—	9	—
—	—	—	—	—	—	—
—	—	—	—	—	—	—
—	—	—	—	—	—	—
—	—	—	—	—	—	—
—	—	—	—	—	—	—
—	—	—	—	—	—	—
—	—	—	—	—	—	—
—	—	—	—	—	—	—
—	—	—	—	—	—	—
—	—	—	—	—	—	—
—	—	—	—	—	—	—
—	—	—	—	—	10 1/2	—
Quadruple	—	4	—	—	13 1/2	—

Manufacturer's name or trade mark of the Iron or Steel (state process of manufacture of Steel) used for Frames, Floors, Beams, Keelsons, Tie and Stringer Plates, Plating, &c.? Mild Steel:- South Durham "Dorman Long & Co" Iron. Jno Hall & Co

Has the Steel been tested as required by the Rules? Yes.

Upper Deck Stringer Plate (Butts, ~~treble~~ riveted ~~or~~ quadruple & length amidship. Straps, ~~single, double or~~ overlapped for all length amidship.

Middle Deck Stringer Plate (Butts, treble riveted for whole length amidship. Straps, ~~single, double or~~ overlapped for whole length amidship.

Butts of Bilge & Side Stringers and Tie Plates, treble or double riveted? treble

Inner Bottom Plating, riveting of Edges 2 rows - 2 pitch. Butts double.

Centre Girder Butts, treble riveted **Keelson Butts**, ~~riveted~~

Frames, riveted through Plates with 7/8 in. Rivets, about 6 apart.

Rivets, state whether Iron or Steel Iron rivets.

FRAMES extend in one length from tank sides to bunwall.

REVERSED FRAMES on floors and ~~frames extend from~~ are double in engine & boiler space; floors flanged at other parts. Bulb angle framing at tank sides.

MASTS, SPARS, &c.

	Material.	Total Length.	Diameter and Thickness. At Partners.	Heel.	Hounds.	Head.	No. of Plates in round.	Angles. Number.	Angles. Size.	Riveting. Seams.	Riveting. Butts.
Lower Masts. Fore	Mild	50.0	21 x 7/20	19 x 4/20	17 1/2 x 4/20	16 1/2 x 4/20	2	—	—	Single	Treble above deck
Main	Steel	51.4	21 x 7/20	19 x 4/20	17 1/2 x 4/20	16 1/2 x 4/20	2	—	—	— " —	
Mizen											
~~Bowsprit~~											

Topmasts, Yards and Remainder of **Spars** Topmasts of Pitch Pine. Yards.

Rigging, Material and Size, **Shrouds** Galvanized Iron rope 4". **Stays** 5" 4 1/2"

Sails. One Suit of fore and aft Sails, ~~and the following spare sails~~

EQUIPMENT No. 49495 LETTER Z

ANCHORS.

Number of Certificate.	Anchors.	Weight, Ex. Stock. Cwts.	qrs.	lbs.	Weight of Stock. Cwts.	qrs.	lbs.	Test, per Certificate. Tons.	cwts.	qrs.	lbs.	Weight required by Table 22. Cwts.	qrs.	lbs.	Description of Anchor.	Makers.	Where and when tested and Superintendent.
37486	1st Bower	65	1	0	—	—	—	51	2	2	0	63	2	0	Baliance Patent	Byers & Co	20.11.99
37211	2nd "	63	3	0	—	—	—	50	7	2	0	63	2	0	" "	"	14.10.99
37341	3rd "	54	0	0	—	—	—	44	15	0	0	54	0	0	" "	"	31.10.99
-	4th "	—	—	—	—	—	—	—	—	—	—	—	—	—			
	Collective weight	183	0	0								181	0	0			
37687	Stream	15	1	0	3	3	7	16	14	1	14	15	1	0	Common	J.P. Jones & Co	14.12.99
42747	Kedge	7	2	5	1	3	11	9	15	3	21	7	2	0	" "	Rowley, Dudley	24.10.99. Dudley

Both Cert. anchors for stockless anchors supplied. H. Green: Sunderland 4 T. tested.

If Trident state name of Patentee. If Stockless, state Mechanical Trots.

CHAIN CABLES.

Number of Certificate.	Fathoms.	Size.	Test per Certificate. Tons.	Weight of Chain Cable. Supplied.	Per Table 22.	Fathoms and Size per Table 22.	Description.	Makers of Cables.	When and where tested, and Superintendent.
14905	135	2 1/4	127 1/4	343-3-21	682-1-11	270 - 2 1/4	Stud Link	J.P. Jones	15.12.99 Sund'd
14915	135 1/2	"	91 1/2	344-2-0				Rowley, Dudley.	18.12.99 H.T. Hartlepool
	271			688-1-21					
Stream (Sheer) or Steel Wire	90	4 1/2	47	-	-	90 - 4 1/2	Steel wire.	Craven & Speeding Bros	Sunderland. 7.12.99

HAWSERS AND WARPS.

Material	Fathoms.	Size.	Breaking Test of Steel Wire Towline.	Fathoms and Size per Table 22.
Towline	120	5"	59	120 - 5
Hawser Two	90	8"	(manila)	(2) 90 - 8
Warp Two	90	7"	"	(2) 90 - 7
	90	6"	"	

Boats Two life boats and two others ~~mounted~~ to main line of suction pipe

Pumps, Number One flex wheel hand pump Diameter of Barrel 6" State whether they are in efficient working order Yes.

Windlass is Iron. Clarke Chapman & Co's Patent. ~~Capstan~~ Four steam winches forward

Engine Room Skylights.—How constructed? Teak on iron examings

What arrangements for deadlights in bad weather? Thick glass bullseyes in hinged teak covers port

Coal Bunker Openings.—How constructed? Iron examings How are lids secured? Hatches battens Height above deck? 12 ins

Number of **Scuppers**, and numbers and dimensions of **Freeing Ports, &c.** Three scuppers & 5" ports in well on each side 36" x 15"

Ceiling in Holds, thickness and material H.P. 2 1/2 **Ceiling 'tween Decks**, thickness and material 6 x 2 1/2 H.P battens

Cargo Hatchways.—How formed? Plate examings 33" above deck in well 32" a Poop **Hatches**, If strong and efficient? Yes.

State size **No. 1 Hatch** (Forward) 22'-11" x 16'-0" **No. 2 Hatch** 25'-0" x 16'-0" **No. 3 Hatch** 14'-7 x 16'-0" **No. 4 Hatch** 8'-4" x 16'-0" &.

Number of **Web Plates, Shifting Beams** and **Fore** and **Afters** to each Hatch Two deck web plates & 3 iron fore and afters in No. 1.2.5.6 1 & in No. 3 & 4; 3 iron fore and afters in each. **No. of Breasthooks** 5 & deck plates **No. of Crutches** 2 & deck plates

Bulwarks, height above deck and description 38" 1/2" iron plates Main Rail, material and size Steel bulb angle 6 x 3

The above is a correct description. FURNESS, WITHY & CO. LIMITED. *Surveyor's Signature* C.E. Burnley. Eb Champness.

Builder's Signature (here only) John L. Mills *Surveyors to Lloyd's Register of British and Foreign Shipping.*

Form No. 18.

"5 and 6 Hatchways 25'-0" x 16'-0"

Correspondence.—State dates and initials of letters respecting this case (*Reference should be made to any correspondence connected with this case*) 21/12/98 M: 5/1/99 M: 27/1/99 M: 1/2/99 M: 7/6/99 M: 5/7/99 C.

Workmanship. Are the butts of plating planed or otherwise fitted? Planed.

Is the riveted work properly closed? Yes.

Are the liners between the frames and plates solid single pieces? Yes Do the holes for riveting plate to frames, butt straps, or plate to plate, &c., conform well to each other? Yes Are the rivet holes well and sufficiently countersunk in the plate and punched from the faying surfaces? Yes Do any rivets break into or through the seams or butts of plating? No

Are the butts of Plating, Stringers, &c., properly shifted and strapped? Yes

Have all the upper and weather decks been tested as required by the Rules (Sec. 23, par. 24)? Yes. State results of tests Good.

Have all the gutterways been tested as required by the Rules (Sec. 23, par. 25)? Yes. State results of tests Good.

General Remarks (State quality of workmanship, &c.) The workmanship is good: & the vessel has been constructed in accordance with the approved plans, seven in number, which, together with the Reports on the forgings & Castings, are attached hereto.

The upper deck in the well is sheathed with 3 1/2" Y.P.

This is a sister vessel to No. 246. S.S. "Freiburg" H. Hpl. Report No. 11140

The Surveyor should state the Number of Report and Name of any Sister Vessel.

PARTICULARS FOR RECORD in the REGISTER BOOK.—Length of Poop 268 ft., ~~R.Q.D. or Break~~ ft., ~~Bridge Dk.~~ ft., F'castle 40 ft. (in feet and tenths). When the Poop is joined to the B.D., this should be distinctly stated. Poop & Bridge combined forming "Well Deck" vessel.

No. and Material of Decks (if Iron or Steel) and whether wholly or partially covered with wood, and No. of tiers of Beams (this information is to be given as it should appear in the Register Book) 2 D.Ks (Stl) (Upr. W.S) 3 tr Bms.

Official No. ; Signal Letters

How are the surfaces preserved from oxidation? Inside Portland cement Paint Outside Paint

PARTICULARS OF WATER BALLAST.—State whether the Double bottom is constructed on the cellular system or with girders on floors cellular

Where fitted.	*Length. Feet.	Water Capacity. Tons.
Double bottom, aft, and under Engines and Boilers	165	426
~~Double bottom, under Engines and Boilers~~		
~~Double bottom, if under Engines only~~	open well under	
~~Double bottom, if under Boilers only~~	boilers for 23 feet.	
Double bottom, forward,	160	462
		888

* The wells are not to be included in the lengths of the tanks.

Where fitted.	*Length. Feet.	Water Capacity. Tons.
Fore peak tank,	-	89
After peak tank,	-	64
~~Midship deep tank~~,	-	-
~~Other tanks, if fitted~~,	-	-

(If necessary, furnish further information by sketch.) See pumping plan

State whether the above have been tested as required by the Rules Yes.

Order for Special Survey No. 1773

Date 16th June 1899

No. 248 in builder's yard.

Dates of Surveys held while building: 1899 Aug. 22. 23. 25. 28. Sept. 1. 11. 13. 15. 19. 22. 26. 29. Oct. 6. 9. 12. 16. 19. 23. 27. 30. Nov. 1. 3. 6. 14. 17. 20. 21. 23. 28. 29. Dec. 11. 7. 18. 22. 1900 Jan. 3. 5. 8. 10. 12. 13. 15. 16. 18. 19. 25. 29. 31. Feb. 6. 7. 15. 16. Mar. 5. 30. Apr. 11. 18. 24. May 2. 14. 9. 10. 11. 15.

Total No. of Visits 63

The amount of Entry Fee £ : :

Special Survey Fee £142 : 10 :

Travelling Expenses, if any £ : :

Fees applied for, 23. 5. 1900

Received by me, 24. 5. 1900 HH

Certificate to be sent to W. Hartlepool

State whether the Vessel has been built under Special Survey Yes.

I am of opinion this Vessel should be Classed 100A1 3 D.K. rule

~~With, or~~ without Freeboard, as condition of Class

E.b Champness C.E. Burnley

Surveyors to Lloyd's Register of British and Foreign Shipping.

Committee's Minute TUES. MAY 29 1900

Character assigned 100A1 (Stl)

a1 6 P.W.

+LMC 6.00 Elect light

The Surveyors are requested not to write on or below the Committee's Minute.

Hull Certificate Written

© 2020 Lloyd's Register Foundation HPL388-0268 (2/2)