

FRAMES, Angle Iron, for  $\frac{2}{3}$  length amidships ...

Inches. In Ship.	Inches. In Ship.	16ths. In Ship.	Inches per Rule	Inches per Rule	16ths per Rule
3 1/2	3	6	3 1/2	3	6
3 1/2	3	5	3 1/2	3	5

Of a bing at Sh. strake to ing. applied  
From M'n. to Upr. or Spar Dk. Sh'rstrake....  
Up. or Spar Dk Sh'rstrake, brdth & thicken'ss...

# PARTICULARS for RECORD OF DOUBLE BOTTOMS, &c., in LLOYD'S REGISTER.

No. of Report 5324 Port Hull Date June 20<sup>th</sup> 1883  
No. in Register Book          On the Screw Steamer "Bolama"

Double bottom, aft, length 40 and water capacity in tons 45. Double bottom, forward, length 42 and water capacity in tons 60

Double bottom, under engines and boilers, length ✓ and water capacity in tons ✓. If under Engines only, or Boilers only, state which ✓

Double bottom, constructed on the cellular system, length ✓ and water capacity in tons ✓

Fore peak tank, water capacity in tons ✓. After peak tank, water capacity in tons ✓

Midship deep tank, length ✓ and water capacity in tons ✓. Other tanks, if fitted, length ✓ and water capacity in tons ✓

(If necessary, furnish further information by sketch.)

Surveyor to Lloyd's Register of British and Foreign Shipping.

HUL396-6023

(000-22/5/80.)

Angle Irons ...

4 3 6 4 3 6

Ceiling betwixt Decks, thickness and material ..

" in hold

do.

do.

Batten & Gao  
2 1/2 6 6 2 1/2