

BEAMS, IRON, or STEEL
Single or d'ble Ang. Iron, Plate or Tee Bull Iron
Single or double Angle Iron on Upper Edge ...

Is the Stringer Plate attached to the outside plating?
41

Yes

PARTICULARS for RECORD OF DOUBLE BOTTOMS, &c., in LLOYD'S REGISTER.

(Received at London Office, 1886.)

No. of Report 5926 Port Hull Date 4th May 1886

No. in Register Book ✓ On the Iron S.S. "Pia"

Double bottom, aft, length ✓ and water capacity in tons ✓. Double bottom, forward, length ✓ and water capacity in tons ✓

Double bottom, under engines and boilers, length ✓ and water capacity in tons ✓. If under Engines only, or Boilers only, state which ✓

Double bottom, constructed on the cellular system, length 248' and water capacity in tons 523

Fore peak tank, water capacity in tons 35. After peak tank, water capacity in tons ✓

Midship deep tank, length ✓ and water capacity in tons ✓. Other tanks, if fitted, length ✓ and water capacity in tons ✓

The above have not been tested as required by the Rules.
(If necessary, furnish further information by sketch.)

James McNeil
Surveyor to Lloyd's Register of British and Foreign Shipping.

(2000—28/11/83.)

Butts from Keel to turn of Bilge, worked carvel, double riveted; with rivets 7/16 thicker than the plates they connect.
Butts of 4 Strakes at Bilge for 1/2 length, treble riveted with Butt Straps 7/16 in diameter, averaging 3 1/2 ins. from cr. to cr.

HVL 398-0183