

N^o 129

Scale 1/2" to the foot

Length between perpendiculars 230'-0"

Breadth 29'-6"

Depth under main deck 15'-0"

" " spar " 22'-0"

Tonnage under main deck 690

Gross 1050

Doubly rivetted throughout.

Rec 15/12/64 & 28/12/64

JH

Frames 4x3x7/16

Reverse Bars 3x2 3/4 x 9/16

Clapnet. 10' 6" 5"

Angle Iron 2 3/4 x 2 3/4 x 9/16

Bulb Iron 7 x 8/16

4x3 1/2 x 7/16

25 x 9/16

all members to be

7x1/6 5x4 1/2 x 9/16

4x3 1/2 x 7/16 4x2 3/4 x 9/16

7x1/6 5x4 1/2 x 9/16

4x3 1/2 x 7/16 4x2 3/4 x 9/16

Plate 7x5/16

20x9/16

10/16

9/16

9/16

9/16

9/16

9/16

8/16

8/16

8/16

7/16 8/16

3/8 depth

7/16

7/16

7/16

7/16

8/16

4 1/2 x 3 1/2 x 7/16

25 x 9/16

Angle Iron 2 3/4 x 2 3/4 x 9/16

Bulb Iron 6 1/2 x 7/16

8x9/16

Reverse Bar to here &

Spar deck alternately

their strake doubled with

7/16 plate for 3/4 length

7/16

7/16

7/16

7/16

7/16

7/16

7/16

7/16

7/16

7/16



© 2021

Lloyd's Register Foundation

IRON 499-0230