

# D. Antonia to lengthen 45 feet Amidships

Length to Bulkhead in nose of vessel 248 ft increase to 290 ft

Breadth 30 ft

Depth 19 ft 5 ins

No. 64 and 19430 No. for Equipment 21,373

over 14 depths + 9 3/4 breadths

Rec. 26/6/72

22/7/72

Again 19/11/72

Diagonals 12 x 10/16 - 14 x 10/16  
12 x 9/16 - 14 x 10/16

Doubled for 3/4 x 11/16 + 10/16

36 x 12/16 + 9/16

Sheerstrake to be doubled for length with 10/16 plate

180 ft wide 1 3/16 plate in new portion new 11/16

10/16 10/16 8/16

8 x 8/16 Patent Bulbs + 5 1/2 x 5/8 top flange and 1/2 x 10/16 Bulb + 3 x 3 x 6/16 Angles 3 ft apart

Beams 1/2 x 7/16 Bulb + 3 x 2 1/2 x 5/16 Angles

Frames spaced 18" apart - 24" apart

4 1/2 x 3 x 8/16

4 x 3 x 7/16 + 6/16

Reversed

3 x 3 x 7/16

3 x 3 x 6/16

Floors

20 x 10/16

19 x 8/16 + 7/16

All Seams and Bulbs double rivetted

5 x 4 x 5/8 4 x 4 x 9/16 4 3/4 x 9/16 3 3/4 x 7/16 3 3/4 x 7/16 3 3/4 x 7/16 3 3/4 x 7/16

14 x 9/16 12 x 10/16

8 x 8/16 Patent Bulbs, top flange 5 1/2 x 5/8 and 1/2 x 10/16 Bulb + 3 x 3 x 6/16 Angles 3 ft apart

1/2 x 7/16 Bulb + 3 x 2 1/2 x 5/16 Angles

To class 100 A

Bulbs 3 Shakes to be made for length

This shake to be doubled with 10/16 for 180 ft + 11/16 thick

13/16 9/16 11/16

1/2 x 7/16 for 3/5 length 1/2 x 7/16 for 180 feet length 5 x 4 x 5/8 5 1/2 x 4 x 9/16 5 1/2 x 4 x 9/16

5 1/2 x 4 x 9/16 5 x 4 x 5/8

Intersect 8/16 thick connected to shell

5 x 4 x 5/8 for 110 ft amidships

12 x 9/16

5 x 4 x 5/8 5 1/2 x 4 x 9/16 2 5/8 x 10/16 - 2 3/8 x 10/16 place 12 x 9/16

Three Shakes at new part round Bulbs to be rivetted

Doubled for 3/5 length 11/16 9/16 11/16

28/6/72 26/7/72

20/11/72



Lloyd's Register Foundation

12010500-0092