

## MIDSHIP SECTION

*Screw Steamer N<sup>o</sup> 46*

Scale  $\frac{3}{4}$ " to the foot

*Virgo*

*Dimensions*

Length Keel and Foreake 250' 0"

Breadth Moulded 30' 0"

Depth D. 17' 10"

D: in hold 16' 10"

14.8 depths in length

8.5 breadths

Dec 30/31/70

Coaming: 18" above deck  
1/2" thick

# Numbers

Depth 18' 5½

Half Girth of Section 29'2"

D<sup>o</sup> Breadth moulded 15" 0"

$$\begin{array}{r} \text{Summation } 62.7\frac{1}{2} \\ \times \text{Length } \underline{250.0} \\ \hline = 15,675 \end{array}$$

Sheer Strake  $30'' \times \frac{3}{4}''$   
Doubling  $\frac{9}{16}''$   
Rivets  $\frac{1}{2}''$

Short Reverse Frame  
height

12/16 You have fitted the vessels  
with the same dip net and basket  
as for the Rule No 20 of an  
vessel above 14 and under  
18 depths in length

London  
April 2/40

These Vertical angles are  
to extend as now marked  
with dotted lines in Red  
as per Rule Section D  
Done April 2/70

26

26<sup>th</sup> March/70

Thos<sup>3</sup> Gouley Esq<sup>r</sup>  
Dundee

IRON 503 - 0143