

Single or double Angle 2 in on Upper edge every frame
Average space... ..

How fastened to Beams Riveted
Stringer Plate on ends of Main or Middle Deck } 40 10 40
Length and thickness

PARTICULARS for RECORD OF DOUBLE BOTTOMS, &c., in LLOYD'S REGISTER.

No. of Report 23134 Port Newcastle (Received at London Office, 188...)
No. in Register Book ... Date 12th August 1889
On the S.S. Neuquay
Double bottom, aft, length 80.0 and water capacity in tons 149. Double bottom, forward, length 114 and water capacity in tons 147.65
Double bottom, under engines and boilers, length 36 and water capacity in tons 76 If under Engines only, or Boilers only, state which -
Double bottom, constructed on the cellular system, length 234 and water capacity in tons 437.
Fore peak tank, water capacity in tons -. After peak tank, water capacity in tons 30.
Midship deep tank, length - and water capacity in tons -. Other tanks, if fitted, length - and water capacity in tons -.

The above have been tested as required by the Rules.
(If necessary, furnish further information by sketch.)

C. Montebey Lloyd's Register
Surveyor to Lloyd's Register of British and Foreign Shipping.

& S. - 1000 - 20 2/88 - Transfer ink.)

NWC809-0062

length)
SIDE STRINGER Angle Irons Are the outside Plates doubled two spaces of Frames in length? 3