S/S "Fonar" Inv. 1st Entry Report No 23543

Wrightson Pile Hardware Co.

No 230 [illegible]

CAST STEEL [illegible]

Scale [illegible]

10"×2¾"

NOTE
ROW OF HOLES 2½" FROM BACK OF POST AND 8" APART 1⅛" DIA

SECTION

½" CHECK 10"×6"

STOPPER 8½" 9"

6" 8½"

A WEB 2" THICK B

5'-6"

10½"×6"

8½"

6" ½" DIA

SECTIONS

6" 10½" 6" 10"

ROUNDED

2'-3" rad

10"×6"

5'-6" from base line to keel 34'-9"

5'-6" from base line to stem 3'-4"

Top radius 28'-0"

11'-9"

19'-9"

9'-6"

9'-6"

8'-3"

6'-1½"

17"

5'-6"

8½"

6"

STOPPER

Bottom radius 20'-0"

10"×6"

5'-0" radius

12" rad

2'-2"

1'-3"

10½" 6½" 7"

1'-0" 1'-0" 1'-0" 1'-0" 1'-0"

10'-0 post made square

16'-0"

5 frame 6 frame 7 frame 8 frame

section 7"×10½" about

(the area here (sole piece) to be about 15% greater than main post

10½"

NOTE
HOLES 1⅞" DIA. spaced 5¾" apart (3 rows)
2½" from back of post + 2½" between rows
front row of holes 11½" apart
holes drilled per red dotted lines
holes in keel 3" from bottom + 3" between rows (2 rows)

Section through A.B.

2"

SECTION AT STOPPER
SCALE 1½" = 1FT

45°

STERN POST

10"

PLAN of BOTTOM PINTLE

CHECK PIN IN HALL PINTLES

10½"

3"

3½"

5½"

2"

6"

8½"

STERN POST

PLAN of STERN POST GUDGEONS
SCALE 1½=1FT

10½"

3½"

½" DIA

PLAN OF BOSS
SCALE 1½" = 1FT

10"×6"

10"

5½" 5½" 11½"

2½" 2½" 2½"

5"

2"

BACK ROW of Holes

6"

10" pads

5½"

4½"

Rough bored 6" 19⅜"

3½"

10" pads

© 2021 Lloyd's Register Foundation
NMC811-0224