

Empire Leben.

NEWCASTLE-ON-TYNE, No ^C21994

PARTICULARS OF PROTECTION TO OPENINGS, ETC.

Description of Hatchways		HATCHWAYS ON FREEBOARD AND SUPERSTRUCTURE DECK ⁸								
		N° 4	N° 5	N° 6						
Dimensions of Hatchway ...		11'-10" x 8'-6"	11'-9" x 17'-0"	10'-6" x 17'-0"						
COAMINGS	Height above Deck ...	33"	36"	36"						
	Thickness { Sides38	.50	.50						
	{ Ends ...									
	Stiffeners ...	HOR. 7" BA	11" BA	9" BA						
	Brackets, Stays ...	NONE	NONE	NONE						
HATCH BEAMS	Number ...	1 BULKHEAD	1	1						
	Spacing ...	4'-0" FROM FORE END	1/2 LENGTH	7'-0" FROM AFT END						
	Scantling and Sketch ...	4x3x50	4x3x50	Do						
	Bearing Surface ...	—	3x50 7/8x34-50	3"						
FORE AND AFTERS	Number ...	NONE	NONE	NONE						
	Spacing ...									
	Unsupported Lengths ...									
	Scantling* and Sketch ...									
	Bearing Surface ...									
HATCH COVERS	Material ...	WOOD								
	Thickness ...	2 3/4"	Do.	Do.						
	How fitted (material) ...	FVA								
	Bearing Surface ...	3"								
Spacing of Cleats ...		24"	Do.	Do.						
Number of Tarpaulins ...		2								

*Are wood fore and afters steel shod at all bearing surfaces? ☒ YES

Are battens and wedges efficient and in good condition? ☒ YES

Are tarpaulins in good condition and in accordance with rule requirements? ☒ YES

Are lashings provided in accordance with rule requirements? ☒ YES

Vertical distance of Sill of lowest Side Scuttle below top of freeboard deck at side amidships 4'-0"