

Moulded depth	33.50	(a) When D is greater than $\frac{15}{15}$	✓	Standard
Stringer plate05	$(D - \frac{L}{15}) \times R = (33.55 - \frac{29.00}{15}) \times 3.3$	+13.65	Ship ...
							Difference
							Restricted
							Allowance

Name of Vessel ss. Acme.

No. in Register Book

	FEET.	INCHES.
Moulded Depth	33	6
Stringer Plate		$\frac{5}{8}$
Thickness of wood sheathing if required		✓
Statutory deck line above intersection of <u>actual</u> deck at side		✓
Total depth from top of statutory deck line to top of keel	33	$6\frac{5}{8}$
Freeboard recorded	6	$10\frac{1}{4}$
Moulded Draft	26	$8\frac{3}{8}$
Add for keel—Flat or Bar		$2\frac{1}{8}$
Draught	26	$10\frac{1}{2}$
Draught for record		

2m,12,32.



© 2021

Lloyd's Register Foundation

Moulded draught	26	$8\frac{1}{2}$		Sheer	2	58
Addition for keel below base line	2		$\frac{15050}{40 \times 5095} = 7.38$	Camber	...	22
Extreme draught				Thickness of deck	...	-
				Scantlings, etc.	...	-