

# Lloyd's Register of Shipping.

## SURVEYS FOR FREEBOARD.—STEAM SHIPS.

29714  
Index No. 1427  
(For London Office only.)

37501 dup  
WRITTEN

Amended Certification Subsid report  
due to vessel having been re-measured for Survey

PARTICULARS RELATING TO ALL STEAM SHIPS EITHER FLUSH DECKED, OR WITH  
POP FORECASTLES, SHORT POOPS AND BRIDGE HOUSES DISCONNECTED, OR  
WITH TOP GALLANT FORECASTLES HAVING LONG POOPS OR RAISED QUARTER DECKS  
CONNECTED WITH BRIDGE HOUSES OR OTHERWISE.

Port of Survey San Francisco Calif.  
Date of Survey While building  
Name of Surveyor Ld. (W. Smith)

Ship's Name. <u>GARBOYLE</u>	Port of Registry and Nationality. <u>New York</u>	Official Number. <u>221040</u>	Gross Tonnage. <u>4002.64</u>	Date of Build. <u>91</u>	Particulars of Classification. <u>+ 100 H. buoyed in Bulk (also contemplated)</u>
Number in Register Book <u>10523</u>					

REGISTERED DIMENSIONS.	LENGTH.	BREADTH.	DEPTH.	UNDER DECK TONNAGE.
	<u>425.0</u>	<u>14.2</u>	<u>11.1</u>	<u>6433.25</u>
Frame Depth	<u>9.2</u>			
Rule	<u>6.5</u>			
Peak				<u>11.0</u>
Tanks				<u>11.0</u>

Moulded Depth as measured..... 12ft.  
Addition for Keel below base line for draught record... 2 1/4 inches.

NOTE.— If the depth is measured when vessel is afloat, the details of measurement should be reported.

Efficient of fineness..... .44  
Modification necessary [Para. 4 (a) to (e)]\*  
Efficient as corrected..... .44

CORRECTION FOR LENGTH.  
Length of Ship on Loadline..... 425ft.  
Length in Table..... 396  
Difference..... 29  
Correction for 10ft., Table A..... 16 Table C..... 16  
× Difference divided by 10..... 4.64 (if required.) 2.92  
If 1/10ths length covered divide by 2 + 4.64 + 2.92

Sheer at Stem..... 12 1/16  
at Sternpost..... 18 1/2  
Mean..... 9 1/2  
Standard mean Sheer [Table, Para. 18]..... 9 1/2  
Difference..... 10.65  
If limited as Para. 18 (f)..... - 10 1/4

CORRECTION FOR IRON DECK.  
Proportion covered, if less than 1/10ths length covered..... 4.64  
Thickness of usual wood deck, less stringer..... 1.6

Rise in Sheer from amidships [Para. 18 (e)]  
At front of bridge house..... ✓  
At after end of forecastle..... ✓  
Fall in Sheer [Para. 18 (d)]  
Length uncovered..... ✓  
Correction.....

CORRECTION FOR ROUND OF BEAM.  
Breadth at Gunwale amidships..... 18ft.  
Round of Beam..... 14  
Normal round..... 14  
Difference..... ✓ ÷ 2 =..... ✓  
Proportion of Deck uncovered (Para. 19)..... ✓

NOTE.— The round of beam should be reported on the full breadth of vessel at the gunwale.

ALLOWANCE FOR DECK ERECTIONS:—  
Freeboard, Table C..... 5-4 1/4  
Correction for Length, if required (Para. 12, 13, and 14)..... + 2 1/4  
Freeboard by Table A, corrected for sheer, and for length, if required (Para. 12, 13, and 14)..... 9-1 1/4  
Difference..... 2-6  
Percentage as below..... 28.92%  
Correction for R. Q. Dk. if engine and boiler openings not covered by bridge house (Para. 11)..... - 8 1/4  
Allowance for Deck Erections.....

Freeboard, Table A..... 8-9 1/2  
Correction for Sheer..... - 10 1/4  
Correction for Length..... + 4 1/4  
Allowance for Deck Erections..... 8-6 1/4  
Correction for Round of Beam..... ✓  
Correction for fall in Sheer (if any)..... ✓  
Correction for Iron Deck (if required)..... - 1 1/2  
Additions for non-compliance with provisions of Para. 11 (d) and (e) †..... ✓  
Other Corrections (if any)..... ✓  
Winter Freeboard..... 4-6  
Summer Freeboard..... 4-0  
Indian Summer Freeboard..... 6-6  
N. A. Winter Freeboard..... ✓

	Length.	Length allowed.	Height.
Forecastle.....	<u>41.25</u>	<u>41.25</u>	<u>8ft.</u>
Bridge House.....	<u>34ft. (+ 2 ft. Sheer)</u>	<u>24.00</u>	<u>8ft.</u>
Raised Qr. Dk.....	<u>105.48</u>	<u>105.48</u>	<u>8ft.</u>
Total.....		<u>194.00</u>	<u>25.64</u>
Length of Ship.....	<u>425</u>		
Corresponding percentage [Para. 11, 12, 13, or 14].....			<u>28.92%</u>


Correction necessary because clearside amidships, measured in accordance with the Statute is not taken at the intersection of the wood or iron deck with side. + 1 1/2  
Winter Freeboard from deck line..... 4-4 1/4  
Summer " " " "..... 4-1 1/4  
Indian Summer " " " "..... 6-4 1/4  
N. A. Winter " " " "..... 4-1 1/4

FREEBOARD recommended amidships from centre of Disc to top of Statutory  
Fresh Water Line above centre of Disc.....  
Indian Summer Line " " " ".....  
Winter Line below " " " ".....  
Winter North Atlantic Line " " " ".....

Deck Line, Wood (Iron) Deck:—  
..... 6 1/4  
..... 6 1/4

† If the frames, skin planking, or ceiling are of unusual thickness the breadth of vessel to inside of ceiling should be reported if possible.  
‡ In vessels obtaining an allowance for deck erections under Para. 11 where the sheer drops abaft amidships the height of the R.Q.D. is to be taken from the level of the top of the amidship beam.  
§ In flush-decked vessels the total standard mean sheer means the sheer measured at the stem and stern-post. In vessels having poops and forecastles, it means the sheer measured at points distant one eighth of the vessel's length from stem and stern-post.

† State dimensions of freeing port area on back of this form.  
‡ The Surveyor should state whether the fall in sheer as reported is measured relatively to the straight line of keel or to the water line. If measured relatively to water line the vessel's draft at time of survey, and also the usual load draft forward and aft should be reported.



Do all the Frames extend to the top height in the Poop? } *Longitudinal framing.*  
 To what height do the Reverse Frames extend? } *Yes*  
 Has the Poop or Raised Quarter Deck an efficient Iron Bulkhead at the fore end? *W. Y. steel doors.*  
 Give particulars of the means for closing the openings in Bulkhead *No.*  
 Is the Poop or Raised Quarter Deck connected with the Bridge House? *W. Y. steel doors.*  
 Give particulars of the means for closing the openings in Bulkhead *1/2"*  
 What is the thickness of the Bridge Front plating? *4/16"* and Coaming plate?  
 Give scantlings and spacing of the Stiffeners *8 x .41 x 3-41 x .26 Channels spaced about 2ft.*  
 Are bracket plates fitted at each end of the Stiffeners? *Yes.* Are hor'l. brackets fitted connecting Bridge Bulk'd. with Bulwarks? *Yes.*  
 Has the Bridge House an efficient Iron Bulkhead at the after end? *Yes.*  
 How are the openings closed? *Striped steel doors.*  
 Is the Forecastle at least as high as the main or top-gallant rail? *Yes.* Has the Forecastle an efficient Iron or Wood Bulk'd. at after end? *Open*  
 Are the Engine and Boiler openings covered by a Bridge, Poop, Raised Quarter Deck, or enclosed by a Strong Iron or Steel Deckhouse? *Yes. Top bulkhead plating 1/2". Stiffeners 10 x 1/4 x 2 1/2 spaced about 20" apart brackets top & bottom*  
 If the openings are not so protected are the exposed parts of the Casings efficiently constructed? *Yes.*  
 Give thickness of plating; scantlings and spacing of Stiffeners  
 What is the height of the exposed Casings? *Yes.* Are suitable means provided for closing all openings in them in bad weather? *Yes.*  
 Are the Weather Deck Hatchways efficiently constructed and at least equal to the requirements of Section 28 of the Rules for 1904-5? Give particulars below:—

Position and Size.		Ship.		Rule.		Ship.		Rule.		Ship.		Rule.	
COAMING	Height above top of DECK	2 1/2"				22 oil tank deck 6'-0" x 4'-0"							
	Thickness	Sides . . . . . 1/4"				10 " "				4'-0" x 2'-6"			
WEATHER DECK OR WEATHER PLATES	Number	One				beaming 8 x 3 1/2 x 1/4 angle with steel							
	Section and Scantlings	12 x 1/4 angle				cover 3/2" thick, efficiently stiffened.							
FORE AND AFTERS	Number												
	Section and Scantlings												
HATCHES	Thickness	3"											
	Remarks	solid											


\* The depth of Fore and Afters should be stated from the underside of the hatches in all cases.  
 (If the sill of the lowest side scuttle will be less than 6 inches above the Indian Summer Load Line if assigned under the tables, state vertical distance from top of deck at side amidships to lower edge of lowest side scuttle.)

The following information is to be given in all Cases of vessels dealt with under Paras. 11, 12 (under 15 feet Moulded depth) and under Shelter Deck Rules.

What is the thickness of the Bridge Sheerstrake? \_\_\_\_\_  
 Delete the words { The Crew are, are not, berthed in the bridge house.  
 that do not apply { The arrangements to enable them to get backwards and forwards from their quarters are, are not satisfactory.  
 Length of Bulwarks in well \_\_\_\_\_  
 Area of Freeing Ports required by Para. 11 (e) each side of vessel = \_\_\_\_\_ Sq. ft.  

Ft.	Tenths.	Ft.	Tenths.	No.	} Freeing Ports (each side of vessel)	=	Sq. ft.
x	x	x	x				
x	x	x	x				

 Total deficiency or excess = \_\_\_\_\_ Sq. ft.



Show hereon line of Floors or Tank Top with position of any Breaks in same; also height of Peak Tank tops, &c., &c.

State any special features in the construction of the Vessel *Like vessel to S/S 'Vacuum' (San Francisco No. # 3283), and also to the S/S 'Pinkhead' (San Fran. No. # 2551). The latter was measured on same basis as given on this report, & former will put in re-measured later.*  
 Owners *Vacuum Oil Co.*  
 Address *61 Broadway, New York.*  
 Fee \$ 100

Received by me

