

Less Crew Space  
Less above Crown of

375.70

Depth "d" at middle of length. See Secs. 2 & 13... 19.42

Managers White Star

250,914.

Kumara Marathon

F.E.

Received by Chief Ship Surveyor

Received from Chief Ship Surveyor

VESSEL'S NAME Steel S.S. "BARDIC" ex "WAR PRIAM". Rpt. Bel. No. 8088

The remarks of the Chief Ship Surveyor are desired on this case for the consideration of the Classing Committee.

("The endorsement to contain a succinct summary of any repairs that have been required and to show the cause or causes of such repairs, and also to bring out clearly any exceptional features in connection with the case, so that the Classing Committee may have all the salient points presented in the endorsement." - Extract from Sub-Committee's Report, 24/5/92.)

Transverse No. 90 Depth "d" 19.42

Framing: Table No. 3 page 16 Description Bulb angle & reversed frames

Longitudinal No. 40500

Proportions Length = 11.25  
Depth

Deck Sheerstrake as approved.

The dnton pump has been dispensed with as approved in Standard vessels. The vessel is now owned by the Oceanic Steam Navigation Co. and it is concluded the new Owners are agreeable to fit the pump at the termination of the War if requested to do so.

This vessel appears to have been built in accordance with the Rules and the approved plans, and it is submitted she is eligible to be classed 100 A.1. Steel "Shelter Dk." with freeboard," as recommended. The Summer freeboard of 11.1 1/2 from centre of disc to top of statutory deck line at Shelter deck, now marked on the vessel's sides, to be inserted in the classification certificate, and recorded in the Register Book, and further, the remaining freeboards, as shown on the accompanying verification form to be inserted in the certificate of classification.

2 Dks. (Steel) and Shelter Dk. (Steel).

Cell D.B. 392' 1461t. DTa 39' 1116t. FPT 119t. APT 76t.

EK. 8 BH. to Shelter Dk. pt. Cem. Lloyd's A. & C.P. P31', F43' on Shelter Dk.

in two decks or shells two decks



Lloyd's Register Foundation 24. 3. 19.

510-0155

Spacing 27' 4 24" 27' 4 24" Bridge Deck Stringer Plate, breadth & thickness