

GINES, &c. — Description of Engines *4 Cycle Single acting Diesel* No. of Cylinders *4*  
No. of Cylinders *400* Length of Stroke *15 3/4"* Revs. per minute *175* Dia. of Screw shaft *2 1/8"* as per rule  
as fitted *2 1/8"* Material of screw shaft  
liner made  
fit tightly  
bush *960*  
Dia. of thru  
face *1490*

LOYDS REGISTER  
LONDON  
6 OCT 1914

Time of Receipt

REC'D  
ANSR

## TELEGRAM.



### POST OFFICE TELEGRAPHS.

If the accuracy of this Telegram be doubted, a part, or the whole, can be repeated under special conditions, particulars of which can be obtained on application at the Office from which it was delivered.

This form must accompany any inquiry made respecting this Telegram.

Office of Origin and Service Instructions.

Charges  
to pay

Office Stamp.



Arrived here at  
+ ROTTERDAM 00361 24 5/10 6.45 N 1 16  
LLOYDS REGISTER 71 FENCHURCH STREET LONDON  
= POSEIDON 903 IN REGISTER BOOK SEATRIALS  
SATISFACTORY COMPLETED FIRST ENTRIES HULL  
AND MACHINERY CAN NOW BE ISSUED = SLEBE +

on. 29a.



© 2019

Lloyd's Register  
Foundation

meter at smallest part *1 7/8"* Area supported by each stay *179 1/2"* Working pressure by rules *160 lb* Material of Front plates at bottom  
Material of Lower back plate *S. 16. S.* Thickness *1 1/8"* Greatest pitch of stays *9 1/2"* Working pressure of plate by



...the vessel will proceed after completion of trials to ...

Referred to the Chief Ship Surveyor  
and the Chief Engineer Surveyor.

OCT 6 1914

*FM*

Referred to Mr. Mayne.

Referred to Mr. Woods.

Urgent



© 2019

Lloyd's Register  
of Cylin...



...the hull a  
...warded t  
...rmation .  
...the sea  
...ome small  
...etpended fr  
...however  
...ing of th  
...eter at small  
...ness 1/16  
...eter of tube

... & VEENDAM DIS  
...ntations to be address  
...IE SURVEYORS.