

3 4 9

SPECIFICATION OF EXTRA SPARE PARTS FOR ENGINES P4K, Nos. 50074/50075,  
BE INSTALLED IN TWIN-SCREW VESSEL AND TO BE CLASSIFIED IN ENG. LLOYD'S.  
/INCLUDING TOTAL REQUIRED FOR BOTH ENGINES./

- 1 Cylinder Cover, complete with all valves, valve seats, springs, et<sup>c</sup>
- 1 Seat for fuel valve
- 1 Working Piston, complete with rings
- 1 Set of Four Screw Wheels for one main engine
- 2 Working Cylinder Bottom-end Bolts with Nuts
- 2 " " Top-eng " " "
- 2 " " Main Bearing Bolts " "
- 2 Main Cylinder Bottom-end Bolts with Nuts
- 2 " " Main Bearing Bolts " "
- 6 /1 Set/ Coupling Bolts between crank and thrust shaft
- 1 Fuel Pump, complete
- 10% of Bolts and Nuts on one engine
- 5 Metres Fuel Delivery Pipes with four couplings
- 5 " Starting Air Delivery Pipe
- 6 /1 Set/ Coupling Bolts between thrust and intermediate shaft

STOCKHOLM, 8th November 1919.

A.-B. ATLAS DIESEL  
AVD. DIESELS MOTORER  
STOCKHOLM

25 NOV 1919



© 2020

Lloyd's Register  
Foundation