

hellplating drilled and considered satisfactory. Drilling sheet attached

VE "CHELOHSIN"

Report Vancouver, No. 7780

B.C.

THICKNESSES OF PLATING ascertained by drilling, and comparison of same with the original thicknesses.

The thicknesses are in  $\frac{1}{40}$  of an inch.

	AMIDSHIP.					FORWARD.					AFT.				REMARKS.		
	Original Thickness.		Thickness by drilling.		Diminution if any.	Original Thickness.		Thickness by drilling.		Diminution if any.	Original Thickness.		Thickness by drilling.			Diminution if any.	
	Port.	Std.	Port.	Std.		Port.	Std.	Port.	Std.		Port.	Std.	Port.	Std.			
J.	10	10	10	-	-	8	10	10	-	-	-	-	-	-	-	-	The Owners have made a practice of fitting heavier plates than original when renewing for wear & tear or damage.
H.	10	10	10	-	-	8	11	12	-	-	-	-	-	-	-	-	
G.	14	13	13	1	1	10	14	12.5	-	-	10	10	10	-	-	-	
F.	13	15	10.5	-	.25	11	12.5	12.5	-	-	11	12.5	10	-	1	-	
E.	13	10	12.5	3	.5	11	16	15	-	-	11	11	11	-	-	-	
D.	14	16	15	-	-	11	stealer		11	14	11	-	-	-	-	-	
C.	14	16	16	-	-	12	doubled		12	14	14	-	-	-	-	-	
B.	14	13	12.5	1	1.5	12	17	17	-	-	12	14	14	-	-	-	
A.	14	13	13	1	1	12	17	17	-	-	12	14	16	-	-	-	
L.	20	20	-	-	-	18	cement		18	cement		-	-	-	-	-	

Drillings at ends to be made in the vicinity of the peak bulkheads.

© 2020  
 Lloyd's Register  
 Foundation  
 7/1/49  
 W1067-0019