

W1067-0099
F.E.

lm,12,15.

Received by Chief Ship Surveyor

Received from Chief Ship Surveyor

VESSEL'S NAME *Steel S.S. "RAKUYO MARU"* Rpt. *Nag* No. *1324*

The remarks of the Chief Ship Surveyor are desired on this case for the consideration of the Classing Committee.

"The endorsement to contain a succinct summary of any repairs that have been required and to show the cause or causes of such repairs, and also to bring out clearly any exceptional features in connection with the case, so that the Classing Committee may have all the salient points presented in the endorsement."—Extract from Sub-Committee's Report, 24/5/92.)

Transverse No. *92.5* Depth "d" _____
Framing: Table No. *3* Description *Bulb angle*
Longitudinal No. *42550*

Shelter Proportions Length = *11.36*
Depth _____
Deck Sheerstrake *as approved*

The Anchors & Chain Cables, with the exception of the Stream Chain, have been tested at a Recognized Proving Establishment in this Country. It is Submitted the Notation "Lloyds Av CP" might be assigned

This vessel appears to have been built in accordance with the Rules and the approved plans, and it is submitted she is eligible to be classed \blacktriangle 100.A.1. (Steel) "Shelter Deck" with freeboard," as recommended. The Summer freeboard of *10'-8 1/2"* from centre of disc to top of statutory deck line at *Shelter* deck, now marked on the vessel's sides, to be inserted in the classification certificate, and recorded in the Register Book, and further, the remaining freeboards, as shown on the accompanying verification form to be inserted in the certificate of classification.

2 Dks (Steel) & Shelter Dk (Steel Ws)
Cell DB 389' 1519t, ITa 24' 549t, FW tanks in E.R 9' 99t, FPT 129t, APT 49t
FK, 6BH to Shelter Dk, 1BH to upper Dk, Cem, Lloyds Av CP. F42' on Shelter Dk

Side
It is Concluded the edges of the Shell plating on the forward & after bodies are truly riveted as shown in the approved plan of hullship Section and the frames in the fore peaks are as approved and not as stated but the Surveyor should be requested to state if this is so

Spacing	max	4'-6"	4'-6"	Forecastle Deck Stringer Plate, b'dth & th'kns	38
BEAMS, Forecastle Deck xxxx , Bulb Angle,	9	3 1/2 .525	9x3 1/2 x .50	Angle on ditto	3 1/2 x 3