

# REPORT ON ELECTRICAL EQUIPMENT.

(OTHER THAN FOR THE PROPULSION OF THE VESSEL)

Received at London Office.....

Date of writing Report.....19..... When handed in at Local Office.....MAR 1949.....19..... Port of.....HULL.....

No. in Survey held at.....HULL..... Date, First Survey.....31.12.48..... Last Survey.....7.2.1949.....  
Reg. Book. (Number of Visits.....11.....)

95617 on the Steam Trawler "ST. LEANDER". Tons { Gross.....658.....  
Net.....232.....

Built at Beverley By whom built Cook, Welton & Gemmell Ltd. Yard No. 799 When built 1949

Owners T. Hamling & Co., Ltd. Port belonging to Hull

Electrical Installation fitted by Wm. Broady & Sons, Ltd. Contract No. - When fitted 1949

Is vessel fitted for carrying Petroleum in bulk No Is vessel equipped with D.F. Yes E.S.D. Yes Gy.C. No Sub.Sig. No  
RADAR - Yes

Have plans been submitted and approved Yes System of Distribution two wire Voltage of supply for Lighting 110

Heating 110 Power 110 Direct or Alternating Current, Lighting D.C. Power D.C. If Alternating Current state periodicity - Prime Movers,

has the governing been tested and found as per Rule when full load is suddenly thrown on and off Yes Are turbine emergency governors fitted with a

trip switch as per Rule - Generators, are they compound wound Yes, are they level compounded under working conditions Yes,

if not compound wound state distance between generators - and from switchboard - Where more than one generator is fitted are they

arranged to run in parallel No, are shunt field regulators provided Yes Is the compound winding connected to the negative or positive pole

negative Have machines over 100 kw. been inspected by the Surveyors during manufacture and testing - Have certificates of

test for machines under 100 kw. been supplied Yes and the results found as per rule Yes Are the lubricating arrangements and the construction

of the generators as per rule Yes Position of Generators Engine room starboard side.

-, is the ventilation in way of generators satisfactory Yes, are they clear of inflammable material Yes, if situated

near unprotected combustible material state distance from same horizontally - and vertically -, are the generators protected from mechanical

injury and damage from water, steam and oil Yes, are the bedplates and frames earthed Yes and the prime movers and generators in metallic

contact Yes Switchboards, where are main switchboards placed Engine room starboard side aft bulkhead near

generator.

are they in accessible positions, free from inflammable gases and acid fumes Yes, are they protected from mechanical injury and damage from water, steam

and oil Yes, if situated near unprotected combustible material state distance from same horizontally - and vertically -, what insulation

material is used for the panels "Sindanyo", if of synthetic insulating material is it an Approved Type Yes, if of

semi-insulating material (slate or marble) are all conducting parts insulated therefrom as per Rule - Is the frame effectually earthed Yes

Is the construction as per Rule Yes, including accessibility of parts Yes, absence of fuses on the back of the board Yes, individual fuses

to pilot and earth lamps, voltmeters, etc., Yes locking of screws and nuts Yes, labelling of apparatus and fuses Yes, fuses on the "dead"

side of switches Yes Description of Main Switchgear for each generator and arrangement of equaliser switches Double pole single

throw quick break knife switches and double pole fuses.

-

and for each outgoing circuit Double pole, double throw knife switches and double pole fuses.

-

Are compartments containing switchboards composed of fire-resisting material or lined as per Rule Yes Instruments on main switchboard two

ammeters two voltmeters - synchronising devices. For compound machines in parallel is the ammeter connected on the pole opposite to the

equaliser connection - Earth Testing, state means provided Lamps coupled to earth via switches & fuses.

Switches, Circuit Breakers and Fuses, are they as per Rule Yes, are the fuses an approved type Yes, are all fuses labelled as

per Rule Yes If circuit breakers are provided for the generators, at what overload current did they open when tested -, are the reversed current


protection devices connected on the pole opposite to the equaliser connection -, have they been tested under working conditions, and at what current

did they operate - Joint Boxes, Section Boards and Distribution Boards, is the construction and position as per Rule Yes

Cables, are they insulated and protected as per the appropriate Tables of the Rules Yes, if otherwise than as per Rule are they of an approved type -,

state maximum fall of pressure between bus bars and any point under maximum load 3V, are the ends of all cables having a sectional area of 0.04

square inch and above provided with soldering sockets Yes. Are paper insulated and varnished cambric insulated cables sealed at the ends -





PARTICULARS OF GENERATING PLANT.

## GENERATOR CABLES.

### MAIN DISTRIBUTION CABLES.

LIGHTING AND HEATING, ETC., CABLES.

MOTOR CABLES.

© 2020  
Lloyd's Register  
Foundation



The Electrical Equipment is installed in accordance with the approved plans and the requirements of the Rules.

All Insulated Conductors are guaranteed to have been tested at the maker's works as specified in the Rules.

The foregoing is a correct description.

WILLIAM B. GADY & SONS LTD.  
ENGLAND

Electrical Engineers.

Date 4-2-1949

#### COMPASSES.

Minimum distance between electric generators or motors and standard compass 50' 0"

Minimum distance between electric generators or motors and steering compass 44' 0"

The nearest cables to the compasses are as follows:—

A cable carrying 2 Ampères inside 6' feet from standard compass 6' feet from steering compass.

A cable carrying 2 Ampères 6' feet from standard compass inside 6' feet from steering compass.

A cable carrying — Ampères — feet from standard compass — feet from steering compass.

Have the compasses been adjusted with and without the electric installation at work at full power Yes

Has the effect of switching on and off circuits, motors and other electro-magnetic apparatus within the vicinity of the compasses been noted Yes

The maximum deviation due to electric currents was found to be Nil degrees on every course in the case of the

standard compass, and Nil degrees on every course in the case of the steering compass.

COOK, WELTON & GEMMELL LTD.

Adlam  
General Manager &  
Chief Draughtsman

Builder's Signature.

Date 9-2-49

Is this installation a duplicate of a previous case Yes If so, state name of vessel "ST. APOLLO".

Plans. Are approved plans forwarded herewith No If not, state date of approval 11/5/48

Certificates. Are certificates of test for motors engaged on essential services and generators forwarded herewith Yes

General Remarks (State quality of workmanship, whether insulation tests, etc., have been made, opinions as to class, etc.)

The electrical equipment of this vessel was installed in accordance with the approved plans and the Rules.

The materials used are of good quality and the workmanship is good.

On completion the equipment was operated under working conditions with satisfactory results and the insulation resistance of all circuits and apparatus was measured and found good.

This equipment is in my opinion suitable for a classed vessel.

Notes sent 25/3/49

Total Capacity of Generators 30 Kilowatts.

The amount of Fee ... £ 1 5: - 2 MAR 1949

Travelling Expenses (if any) £ : : When received. 19

Committee's Minute FEB 1 APR 1949

Assigned Sa F.E. mch. rpt.

J. H. Gemmell

Surveyor to Lloyd's Register of Shipping.