

(Periodical Surveys when held, must be reported in detail and serially in the terms of the Rules and items remaining to

+LOCAL A  
with fre  
218 3/

EL'S NAME "WAHINE" *copy to be retained in file* REPORT Wellington No. 4966


THICKNESSES OF PLATING ascertained by drilling, and comparison of same with the original thicknesses.

The thicknesses are in hundredths of an inch.

PLACE	Original Thickness	AMIDSHIP.				Original Thickness	FORWARD.				Original Thickness	AFT.				REMARKS.
		Thickness by drilling.		Diminution if any.			Thickness by drilling.		Diminution if any.			Thickness by drilling.		Diminution if any.		
		Port.	Std.	Port.	Std.		Port.	Std.	Port.	Std.		Port.	Std.	Port.	Std.	
KEEL	N 58					40					40					
Deck	M 56					40					40					
Deck	L 56					40					40					
Deck	K 56					40					40					
Deck	J 56					40					40					
Deck	H 56					40					40					
Deck	G 64					40					40					
Deck	F 64					40					40					
Deck	E 56					40					40					
Deck	D 52					40					40					
Deck	C 52					40					40					
Deck	B 52					40					40					
Deck	A 62					40					40					
						50					50					

Bar Keel

Drillings at ends to be made in the vicinity of the peak bulkheads.



© 2019

Lloyd's Register Foundation

W1076-0106

Painting of Decks	GOOD	Ceiling	GOOD	Coal Bunkers, Openings, Covers, &c.	
Painting	GOOD	Cement or Asphalt		Oil Bunkers	
Paints & Pastings	GOOD	Rudder	GOOD		

+LOCAL A  
with fre  
218 3/  
ed  
402  
VVF  
ard  
hip an  
n?  
plat  
nd  
ort.  
ed.  
ca  
g  
nd  
I  
cond  
a (e  
r Items:-  
Copper  
(S  
When f